

CyberPower

P6WSUC15
WALL-TAP
SURGE PROTECTION

Protect home and office computers,
and electronics.

The CyberPower P6WSUC15 Wall-Tap Surge Protector with USB charging is designed to protect essential home and office electronics, including computers, networking equipment, and other devices, from power surges and energy spikes caused by storms and electrical fluctuations. Offering 2,400 joules of surge protection, this unit features six surge-protected AC outlets, a USB-A port with 2.4A power output, and a USB-C port delivering 15W of power, ensuring efficient charging for mobile and USB-enabled devices.

This surge protector wall-tap comes with a One-Year Limited Warranty and a Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 2400 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- AC Outlets: 6
- Outlet type: NEMA 5-15R
- USB-A charge ports: 1
- USB-A charge output: 2.4A
- USB-C charge ports: 1
- USB-C charge output: 15W
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$300,000

SPECIFICATIONS

INPUT	
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Wall-tap

OUTPUT	
Outlet Type	6 x NEMA 5-15R
USB Charge Port Type	1 x Type A 1 x Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	18 Watts

P6WSUC15
WALL-TAP SURGE PROTECTION

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	800V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz 100 MHz
Maximum Surge Current	60,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	15,000 A
Surge Suppression (Joules)	2400 J
PHYSICAL	
Color	White
Form Factor	Wall-tap
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	10.39 x 17.6 x 3.51 cm
Physical Dimensions - Width/Height/Depth (mm)	104 x 176 x 35 mm
Physical Dimensions - Width/Height/Depth (in.)	4.09 x 6.93 x 1.38 in.
Weight (kg)	0.29 kg
Weight (lb)	0.64 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	11.51 x 16.51 x 6.1 cm
Shipping Dimensions - Width/Height/Depth (mm)	115.06 x 165.1 x 60.96 mm
Shipping Dimensions - Width/Height/Depth (in)	4.53 x 6.5 x 2.4 in.
Weight (kg)	0.38 kg
Weight (lb)	0.84 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	cULus (UL498A/UL1449) DOE VI NR Can FCC ICES-003
WARRANTY	
CEG Amount	\$300,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited Warranty