

Catalog Number
Notes
Type

FEATURES & SPECIFICATIONS

INTENDED USE — Recessed LED kits include housing, trim, and wire connectors in one package. The LED kit is the most economical means to create a well lit environment with exceptional energy efficiency and near zero maintenance. The LED kit maintains at least 70% light output for 28,000 hours.

CONSTRUCTION — Steel housing with 3 remodel clips and 3 wire nuts for installation in existing plaster, sheet rock or mechanical ceiling. Heavy-gauge galvanized steel raceway arm. Durable, powder coat paint prevents rust.

Galvanized steel junction box with three 7/8" knockouts with slots for pryout. Not suitable for pulling wires.

Hook & hang snap-on J-box doors for easy access.

Rated for 90°C. Ground wire provided.

Available in 3000 K color temperature LEDs.

OPTICS — White baffle recesses optical system into the ceiling to prevent glare and provide a traditional look. Diffused lens provides even illumination throughout the space.

ELECTRICAL — High-efficiency driver mounted on the module. Primary power disconnect provided for simple connection to a dedicated LED connector in the housing.

Dimming down to 15%. See page 2 for recommended triac dimmers.

Standard input wattage is 7.4 W, 60 lumens per watt (3000 K); equivalent to 45 watt PAR20.

LISTINGS — CSA certified for use in the US and Canadian safety standards. Certified to the high efficacy requirements of California T24 JA82016. ENERGY STAR® certified. WSEC ASTM E283 for Air-Tight. Wet location listed.

WARRANTY — 5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.

Specifications

Aperture: 3 (7.6)

Ceiling opening: 3-1/8 (7.9)


Overlap trim: 4 (10.2)

Height: 6 (15.2)

Length: 7-1/8 (18.1)

Max. ceiling thickness: 5/8" gypsum; 3/4" drop ceiling

All dimensions are inches (centimeters) unless otherwise indicated.



LED Recessed Downlighting

LK3B

3" Baffle LED Recessed Kit

IC/Non-IC

New & Remodel Construction



ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.


Example: LK3BMW LED

LK3BMW			LED		
Series	Reflector	Finish	Lamps	Color temp/CRI/Watts/Lumens	Voltage
LK3 3" LED recessed kit	B Baffle	MW Matte white	LED	(blank) 3000 K/93CRI/7.4W/450L	(blank) 120V


3" Baffle LED Recessed Downlighting Kit

INSTALLATION


The following instructions are for remodel applications. New construction applications require new construction pan and hanger bars (see accessories).




Step 1:
Using provided stencil, trace cutout lines for housing hole on ceiling. Use saw to make appropriate 3-1/8" cutout.



Step 2:
Using provided wire connectors, connect wires (black to black; white to white; ground to ground) and insert housing into ceiling.



Step 3:
Snap (3) springs to secure housing to ceiling.



Step 4:
Insert trim into housing.

DIMMING & ENERGY DATA

COMPATIBLE DIMMERS*
Lutron Model No:
• DVELV-300P
• 300P SELV
• NTELV-300P
• DVCL-153P-WH
• CT-603PR-WH
Leviton Model No:
• 6615-P
Pass & Seymour Model No:
• H703PTUTC
• H703PNICCV4
• D1103P
• HCL453PTCCCV6
• TD703PWCCV6
Synergy/Leviton Model No:
• ISD 400 ELV 120 / IPE04
• ISD 600 I 120 / IPI06
• ISD 1000 I 120 / IPI10

*Unlisted dimmers do not imply non-compatibility.

ENERGY DATA*	
	3000 K
Lumens	450
CRI	93
Min. starting temp	-18°C (0°F)
EMI/RFI	FCC Title 47 CFR, Part 15, Class B
Sound rating	Class A standards
Input voltage	120V
Min. power factor	0.80
Input frequency	50/60 Hz
Rated wattage	7.4W
Input power	7.4W
Input current	0.072A

*Values at non-dimming line voltage.

3" Baffle LED Recessed Downlighting Kit

LIGHTING FACTS

LED
LITHONIA LIGHTING

lighting facts®

A Program of the U.S. DOE

Light Output (Lumens)

Watts

Lumens per Watt (Efficacy)

450

7.4

60

Color Accuracy

Color Rendering Index (CRI)

93

Light Color

Correlated Color Temperature (CCT)

3000 (Bright White)

2700K
3000K
4500K
6500K

All results are according to IESNA LM-79-2008: *Approved Method for the Electrical and Photometric Testing of Solid-State Lighting*. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the *Label Reference Guide*.

Registration Number: JB22-YO3P2L (8/14/2014)
Model Number: LK3BMW LED [Upgrade : 7/21/2014]
Type: Luminaire - Downlight

PHOTOMETRICS

Distribution Curve

Distribution Data

Output Data

Coefficient of Utilization

Illuminance Data at 30" Above Floor for a Single Luminaire

LK3BMW LED, 30K, input watts: 7.4, delivered lumens: 443, LM/W = 60, tested in accordance with IESNA LM 63-1995

