

Lightology

lightology.com
866-954-4489
04-08-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EMR615382**
 Approved On: _____ Approved By: _____

Silhouette Rectangle Lighted Mirror By Electric Mirror




Description

The Silhouette Rectangle Lighted Mirror provides a soft halo of light glowing around the perimeter of the mirror. Diffusers on the outside provide for a softer glow. Corrosion resistant OmegaMirror glass. Choice of standard forward phase control or with Keen dimming. Keen touch control features Tap-to-Cycle through On, Night Glow and Off. Hold to dim down to 10%. After one hour of non-use, Energy Save Mode automatically dims lights to 10%. Note: Silhouette can only be hung in the W x H (width x height) orientation as shown; it cannot be installed in any other direction.



Shown in frosted

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)



Base Model*	Base Model with Keen*	Dimensions	Initial Lumens/Fixture	Power Requirements
SIL-2436	SIL-2436-KG	24"W x 36"H x 1.75"D (610mm x 914mm x 44mm)	5,280	120/240 VAC, 67W
SIL-3042	SIL-3042-KG	30"W x 42"H x 1.75"D (762mm x 1067mm x 44mm)	6,720	120/240 VAC, 85W
SIL-4836	SIL-4836-KG	48"W x 36"H x 1.75"D (1219mm x 914mm x 44mm)	8,160	120/240 VAC, 100W
SIL-5442	SIL-5442-KG	54"W x 42"H x 1.75"D (1372mm x 1067mm x 44mm)	9,600	120/240 VAC, 120W
SIL-6036	SIL-6036-KG	60"W x 36"H x 1.75"D (1524mm x 914mm x 44mm)	9,600	120/240 VAC, 120W
SIL-6642	SIL-6642-KG	66"W x 42"H x 2"D (1676mm x 1067mm x 51mm)	11,040	120/240 VAC, 140W

Specifications

COLOR Frosted
 BODY FINISH N/A
 WATTAGE 85W
 DIMMER Included
 DIMENSIONS 30"W x 42"H x 1.75"D
 INTEGRATED LED MODULE 1 x LED/85W/120V LED
 COUNTRY OF ORIGIN United States

Technical Information

LAMP LIFE 52000 hours
 COLOR RENDERING 90 CRI
 LAMP COLOR 3000K
 LUMENS/WATT 79.06
 LUMINOUS FLUX 6720 lumens



CLICK TO VIEW PRODUCT

Notes: