



Materials:

- Screws conform to SAE J429 GR 2 (exceeds ASTM A307).

Finishes:

- **ElectroGalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):** Conforms to ASTM A1059

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 316 (SS):** ASTM A240, Type 316 *

* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	Thread Size	Length (ft)	Finish	Product Weight / Piece (lbs)
PS 602 4 •" x1 -•"	1/2"	1-1/2"	EG	0.116
PS 602 4 •" x1 -•"	1/2"	1-1/2"	DF	0.116
PS 602 4 •" x1 -•"	1/2"	1-1/4"	EG	0.11
PS 602 4 •" x1 - ? "	1/2"	1-3/16"	EG	0.102
PS 602 4 •" x1 - ? "	1/2"	1-3/16"	DF	0.102
PS 602 4 •" x1 - € "	1/2"	1-3/4"	EG	0.131
PS 602 4 •" x ? "	1/2"	15/16"	EG	0.091
PS 602 4 •" x ? "	1/2"	15/16"	DF	0.091
PS 602 4 •" x 2 "	1/2"	2"	EG	0.146
PS 602 4 •" x 2 -•"	1/2"	2-1/2"	EG	0.175
PS 602 4 •" x 2 -•"	1/2"	2-1/4"	EG	0.16
PS 602 4 ~" x1 "	1/4"	1"	EG	0.02
PS 602 4 ~" x1 -•"	1/4"	1-1/2"	EG	0.026
PS 602 4 ~" x1 -•"	1/4"	1-1/2"	DF	0.026
PS 602 4 ~" x € "	1/4"	3/4"	EG	0.013
PS 602 4 ~" x € "	1/4"	3/4"	DF	0.013
PS 602 4 ~" x ? "	1/4"	7/16"	EG	0.01

PS602 4 ?" x1 "	3/8"	1"	EG	0.045
PS602 4 ?" x1 "	3/8"	1"	DF	0.045
PS602 4 ?" x1 -•"	3/8"	1-1/2"	EG	0.06
PS602 4 ?" x1 -•"	3/8"	1-1/2"	DF	0.06
PS602 4 ?" x1 --"	3/8"	1-1/4"	EG	0.053
PS602 4 ?" x 2"	3/8"	2"	EG	0.076
PS602 4 ?" x 2-•"	3/8"	2-1/2"	EG	0.092
PS602 4 ?" x 2-~"	3/8"	2-1/4"	EG	0.084
PS602 4 ?" x €"	3/8"	3/4"	EG	0.04
PS602 4 ?" x t"	3/8"	7/8"	EG	0.044
PS602 4 ?" x 1-~"	5/16"	1-1/4"	EG	0.036

Project:	<input type="text"/>		
Architect / Engineer:	<input type="text"/>		
Date:	<input type="text"/>	Phone:	<input type="text"/>
Contractor:	<input type="text"/>		
Address:	<input type="text"/>		
Notes:	<input type="text"/>		

Approval Stamp: