



SX550G STANDBY UPS SYSTEM

Offers significant energy savings, battery backup and surge protection.

The CyberPower SX550G uninterruptible power supply (UPS) system provides battery backup and surge protection for lightning-induced surges and other power events that can damage electronic equipment. This unit delivers battery backup to power connected electronics during a utility power failure and enough runtime to perform a graceful shutdown to protect against the loss of data and damage to valuable electronics during longer outages.

With a \$100,000 connected equipment guarantee and a three-year warranty, you can trust CyberPower's commitment to the quality of this Battery Backup with Surge Protection.



TYPICAL APPLICATIONS

- Desktop Computers
- Workstations
- Home Theater Equipment
- Personal Electronics
- Home Networking
- Routers & Modems
- VoIP Phone Systems

FEATURES

- 550 VA/330 W
- 8 Standard Outlets
- Standby Topology
- Full-time Surge Protection and Battery Backup
- Three-Year Warranty

SPECIFICATIONS

GENERAL	
Energy Saving	GreenPower UPS™ High-Efficiency
UPS Topology	Standby
INPUT	
Voltage	120V
Frequency Range	47 - 63 Hz
Circuit Breaker	10 A
Plug Type	NEMA 5-15P
Plug Style	Right Angle, 45° Offset Right
Cord Length (ft)	5
OUTPUT	
VA	550 VA
Watts	330 W
On Battery Voltage	120 VAC \pm 5%
On Battery Frequency	50/60 Hz \pm 1%

OUTPUT CONT.	
On Battery Waveform	Simulated Sine Wave
Outlet Type	NEMA 5-15R
Outlets - Total	8
Outlets - Battery & Surge Protected	4
Outlets - Surge-Only Protected	4
BATTERY	
Runtime at Half Load	8 minutes
Runtime at Full Load	2 minutes
Battery Type	Sealed Lead-Acid
Battery Size	12V/5.5Ah
Battery Quantity	1
User Replaceable	No
Typical Recharge Time	8 hours

SX550G STANDBY UPS SYSTEM



SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

Surge Suppression	890
EMI/RFI Filtration	Yes

MANAGEMENT & COMMUNICATIONS

LED Indicators	Power On, Wiring Fault
Audible Alarms	On Battery, Low Battery, Overload
HID Compliant USB Port	Yes
Management Cable	USB Cable
Software	PowerPanel® Personal

PHYSICAL

Color	Black
Form Factor	Compact
Dimensions (WxHxD) (in.)	9.8 x 5.8 x 3.2
Keyhole Mounting Slots	Yes

ENVIRONMENTAL

Operating Relative Humidity	0 - 95% (non-condensing)
Operating Temperature	32 - 104 °F (0 - 40 °C)

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1778

WARRANTY

CEG Amount	\$100,000
Connected Equipment Guarantee	Lifetime
Product Warranty	3 Years Limited