

# TYPAR® BUTYL FLASHING

## TYPICAL CHARACTERISTICS

### FOR COMMERCIAL AND RESIDENTIAL APPLICATIONS

| Characteristic              | Test Method       | Value                       |
|-----------------------------|-------------------|-----------------------------|
| Adhesive                    |                   | Butyl Rubber Copolymer      |
| Thickness                   |                   | 20 mils                     |
| UV Stability                |                   | 180 Days                    |
| Application Temperature     |                   | 30°F (-1°F) to 180°F (82°C) |
| 90° Peel Adhesion (lb/in)   |                   |                             |
| Plywood                     |                   | 7.2                         |
| OSB                         |                   | 2.8                         |
| Facer                       |                   | 6.9                         |
| Low Temperature Flexibility | (per ASTM D-3330) | PASS                        |
| Nail Sealability            | (per ASTM D-1970) | PASS                        |
| Tensile Strength            | (per ASTM D-5034) | 55 lbs/in                   |

|             |                 |                  |                  |                  |
|-------------|-----------------|------------------|------------------|------------------|
| ROLL SIZES: | <b>4" x 75'</b> |                  | <b>6" x 75'</b>  |                  |
|             | Rolls/Case: 12  | Cases/Pallet: 27 | Rolls/Case: 8    | Cases/Pallet: 27 |
|             | <b>9" x 75'</b> |                  | <b>12" x 75'</b> |                  |
|             | Rolls/Case: 4   | Cases/Pallet: 27 | Rolls/Case: 4    | Cases/Pallet: 27 |

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, **we make no warranties, express or implied, other than those warranties described in the TYPAR® weather protection system limited warranty located online at [www.typar.com/downloads](http://www.typar.com/downloads), subject to the limitations and exclusions described therein.**



Made in the USA of US and global components. © 2017, Berry Global Inc.  
TYPAR® is a registered trademark of Berry Global Inc. or its affiliate.  
Please visit [www.typar.com](http://www.typar.com) for installation instructions and warranty information.  
Building Wraps | Flashings | Construction Tape | Fasteners

