



Model #: ABP36VRM-2U

UPC: 649532832385

MSRP: \$649.99



Title

Extended Battery Pack for OL1000RMXL2U & OL1500RMXL2U - 6 x 7AH Batteries - 36V

Description

CyberPower's ABP36VRM-2U 36V Extended Battery Pack offers extended runtimes for the OL1000RMXL2U & OL1500RMXL2U UPS. These 2U packs not only esthetically match the UPS's, but can be rack or tower mounted, just as the UPS's. The heavy gauge power cord is adapted with plug-n-play DC connectors for easy installation. The all metal enclosure safely houses the 6 (six) 12V 7Ah batteries which are connected via 2 strings of 3 in serial. Up to 4 battery packs can be daisy-chained to the UPS for extended runtimes up to 310 minutes.

Features

- Form Factor – 2U configuration supports both rack and tower mounting
- Scaleable – Up to 4 battery packs can be daisy-chained together for increased runtimes.
- Metal Housing – Rigid metal construction allows for placement in areas with a demanding environment.
- Battery Data Link – All extended battery packs transmit diagnostic vitals directly to the main UPS.

Technical Specifications

Technical Information	
Product Type	Extended Battery Pack
Plug/Connector Type	Proprietary
Receptacles	1 x Battery Plug-in Connector
Switching Time	0 ms
AVR	N/A
Power Description	
Load Capacity	1500VA / 1050W
Input Voltage Range	120V AC
Output Voltage	120V AC
Frequency	60Hz
Battery Information	
Batteries	6 x 12V/7Ah Maintenance Free Sealed Lead-acid User-replaceable Hot-swappable
Backup/Run Time	<ul style="list-style-type: none"> • 17 Minute(s) 1050W Full-load • 25 Minute(s) 700W Full-load • 36 Minute(s) 525W Half-load • 57 Minute(s) 350W Half-load
Battery Life	3 Year(s) to 6
Battery Recharge Time	3 Hour(s) Typical
Additional Battery Connections	1 Additional Connection
Environmental Conditions	
Temperature	<ul style="list-style-type: none"> • 32 °F (0 °C) to 95 °F (35 °C) Operating • 5 °F (-15 °C) to 113 °F (45 °C) Non-operating
Humidity	<ul style="list-style-type: none"> • 0 to 95% Non-condensing Operating Humidity • 0 to 95% Non-condensing Non-operating
Altitude	<ul style="list-style-type: none"> • 0 ft to 10000 ft Operating • 0 ft to 50000 ft Non-operating
Physical Characteristics	
Color	Black
Form Factor	2U Tower/Rack Mountable
Power Cord/Cable	6 ft
Dimensions	3.25" Height x 17.25" Width x 19" Depth
Shipping Dimensions	9" Height x 25.25" Width x 21.25" Depth
Weight	55.9 lb
Shipping Weight	67.9 lb
Miscellaneous	
Package Contents	<ul style="list-style-type: none"> • UPS Unit , User Manual , Warranty Card , Serial Cable , Data Link Cable
Certifications & Standards	<ul style="list-style-type: none"> • FCC Class B certified • cUL • UL 1778
Country of Origin	China
Warranty	
Standard Warranty	3 Year(s) Parts & Labor