

# CyberPower

## CSP604UMP6 SURGE PROTECTOR MULTI-PACK

Protect home and office computers,  
electronics, and home theater equipment

The Professional Surge Protector CSP604UMP6 multi-pack from CyberPower offers vital surge suppression for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges and is ideal for safeguarding personal computers, phones/faxes/modems, and other consumer electronics. The CSP604UMP6 provides 1,200 joules of protection and six surge-protected outlets. Each unit has two USB charge ports (2.4 Amp shared) to keep tablets, smartphones, and other rechargeable electronics ready to use. The 4-ft. power cord has a right-angle plug with a 45-degree offset.

Features of the CSP604UMP6 include automatic shutdown, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. It also has an LED indicator (Protected), keyhole mounting slots, and impact-resistant casing. The CSP604UMP6 comes with a 1-Year Limited Warranty and a \$50,000 Connected Equipment Guarantee.

### SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	4 ft (1.2 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset
OUTPUT	
Outlet Type	6 - NEMA 5-15R
Outlets - Total	6
USB Charge Port	Yes
USB Charge Port Amperage	2.4 A (Shared)
USB Charge Port Quantity	2
USB Charge Port Standard	Type A
USB Charge Port Type	2 Type A
USB Charge Port Voltage	5 VDC



### TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

### FEATURES

- Surge suppression: 1,200 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° off-set)
- Outlet type: 6 NEMA 5-15R (surge-protected)
- Power cord: 4 ft
- USB charge ports: 2
- LED indicator: Yes
- Keyhole slots: Yes
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$50,000

SURGE PROTECTION & FILTERING	
Attenuation	43 dB
Clamping Voltage	400V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	60,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,200 J

CSP604U

PROFESSIONAL SURGE PROTECTOR

SPECIFICATIONS CONT.

PHYSICAL	
Color	Black
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	5.59 x 3.78 x 29.46 cm
Physical Dimensions - Width/Height/Depth (mm)	56 x 38 x 295 mm
Physical Dimensions - Width/Height/Depth (in.)	2.2 x 1.49 x 11.6 in.
Weight (kg)	0.47 kg
Weight (lb)	1.03 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	34.62 x 4.62 x 10.67 cm
Shipping Dimensions - Width/Height/Depth (mm)	346.2 x 46.23 x 106.68 mm
Shipping Dimensions - Width/Height/Depth (in.)	13.63 x 1.82 x 4.2 in.
Shipping Weight (kg)	0.56 kg
Shipping Weight (lbs.)	1.23 lbs.

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL 1363
WARRANTY	
CEG Amount	\$50,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited Warranty