
# KINGSBRIDGE - F25010

# **INSTALLATION AND OPERATING INSTRUCTIONS**



**WARNING** To reduce the risk of serious injury or death, you must read and follow these instructions. Keep and refer to these instructions often and give them to any future owner of this play set.

Manufacturer contact information provided below.

OBSTACLE FREE SAFETY ZONE -30' 6" x 29'8" area requires Protective Surfacing. See page 3.

MAXIMUM VERTICAL FALL HEIGHT - 6' 7"

CAPACITY - 14 Users Maximum, Ages 3 to 10; Weight Limit 110 lbs. (49.9 kg) per child.

RESIDENTIAL HOME USE ONLY. Not intended for public areas such as multi-unit residences, schools, churches, nurseries, day cares or parks.

Warning. Only for domestic use.





KidKraft, Inc. 4630 Olin Road Dallas, Texas 75244 USA customerservice@kidkraft.com canadacustomerservice@kidkraft.com 1.800.933.0771 972.385.0100 For online parts replacement visit https://parts.kidkraft.com/

KidKraft Netherlands BV Olympisch Stadion 29 1076DE Amsterdam The Netherlands europecustomerservice@kidkraft.com +31 20 305 8620 M-F from 09:00 to 17:30 (GMT+1) For online parts replacement visit https://parts.kidkraft.eu/

# **Table of Contents**

Warnings and Safe Play Instructions pg. 2
Protective Surfacing Guidelines pg. 3
Instructions for Proper Maintenance pg. 4
About Our Wood – Limited Warranty pg. 5
Keys to Assembly Successpg. 6
Part ID
Step-By-Step Instructions pg. 19-112
Installation of I.D./Warning Plaque pg. 113
RegistrationLast Page

9405010 Rev 07/08/2019

# **Warnings and Safe Play Instructions**



**CONTINUOUS ADULT SUPERVISION REQUIRED.** Most serious injuries and deaths on playground equipment have occurred while children were unsupervised! Our products are designed to meet mandatory and voluntary safety standards. Complying with all warnings and recommendations in these instructions will reduce the risk of serious or fatal injury to children using this play system. Go over the warnings and safe play instructions regularly with your children and make certain that they understand and follow them. Remember on-site adult supervision is required for children of all ages.



# **WARNING**

#### **SERIOUS HEAD INJURY HAZARD**

Installation over concrete, asphalt, dirt, grass, carpet and other hard surface creates a risk of serious injury or death from falls to the ground. Install and maintain shock absorbing material under and around play-set as recommended on page 3 of these instructions.

#### **COLLISION HAZARD**

Place play-set on level ground at least 2m from any obstruction such as a garage or house, fences, poles, trees, sidewalks, walls, landscape timbers, rocks, pavement, planters, garden borders, overhanging branches, laundry lines, and electrical wires. (See OBSTACLE FREE SAFETY ZONE on cover)

#### **CHOKING HAZARD/SHARP EDGES & POINTS**

Adult assembly required. This product contains small parts and parts with sharp edges and points. Keep parts away from children until fully assembled.

#### WARNING LABEL

Owners shall be responsible for maintaining the legibility of the warning labels.

#### STRANGULATION HAZARD

- NEVER allow children to play with ropes, clotheslines, pet leashes, cables, chains or cord-like items when using this play-set or to attach these items to play-set.
- NEVER allow children to wear loose fitting clothing, ponchos, hoods, scarves, capes, necklaces, items with draw-strings, cords or ties when using this play-set.
- NEVER allow children to wear bike or sport helmets when using this play-set.

Failure to prohibit these items, even helmets with chin straps, increases the risk of serious injury and death to children from entanglement and strangulation.

#### **TIP OVER HAZARD**

Choose a level location for the equipment. This can reduce the likelihood of the play set tipping over and loose-fill surfacing materials washing away during heavy rains.

DO NOT allow children to play on the play-set until the assembly is complete and the unit is properly anchored.

Never add extra length to chain or rope. The chains or ropes provided are the maximum length designed for the swinging element(s).

# A

# **WARNING** – Safe Play Instructions

- Observe capacity limitations of your play-set. See front cover.
- Dress children with well fitting and full foot enclosing footwear.
- Teach children to sit with their full weight in the center of the swing seat to prevent erratic swing motion or falling off.
- Check for splintered, broken or cracked wood; missing, loose, or sharp edged hardware. Replace, tighten and or sand smooth as required prior to playing.
- ✓ Verify that suspended climbing ropes, rope ladders, chain or cable are secured at both ends and cannot be looped back on itself as to create an entanglement hazard.
- On sunny and or hot days, check the slide and other plastic rides to assure that they are not very hot as to cause burns. Cool hot slide and rides with water and wipe dry prior to using.
- ✓ Orientate slide such that it gets the least amount of exposure to the sun.

- Do not allow children to wear open toe or heel footwear like sandals, flip-flops or clogs.
- Do not allow children to walk, in front, between, behind or close to moving rides.
- Do not let children twist swing chains or ropes or loop them over the top support bar. This may reduce the strength of the chain or rope and cause premature failure.
- Do not let children get off rides while they are in motion.
- Do not permit climbing on equipment when it is wet.
- Do not permit rough play or use of equipment in a manner for which it was not intended. Standing on or jumping from the roof, elevated platforms, swings, climbers, ladders or slide can be dangerous.
- Do not allow children to swing empty rides or seats.
- Do not allow children to go down slide head first or run up slide.

# $oldsymbol{oldsymbol{oldsymbol{eta}}}$ Protective Surfacing - Reducing Risk of Serious Head Injury From Falls.

One of the most important things you can do to reduce the likelihood of serious head injuries is to install shock-absorbing protective surfacing under and around your play equipment. The protective surfacing should be applied to a depth that is suitable for the equipment height in accordance with ASTM F1292. There are different types of surfacing to choose from; whichever product you select, follow these guidelines:

#### **Loose-Fill Materials**

- Maintain a minimum depth of 9 inches of loose-fill materials such as wood mulch/chips, engineered wood fiber (EWF), or shredded/recycled rubber mulch for equipment up to 8 feet high; and 9 inches of sand or pea gravel for equipment up to 5 feet high. NOTE: An initial fill level of 12 inches will compress to about a 9-inch depth of surfacing over time. The surfacing will also compact, displace, and settle, and should be periodically raked and refilled to maintain at least a 9-inch depth.
- Use a minimum of 6 inches of protective surfacing for play equipment less than 4 feet in height. If maintained properly, this should be adequate. (At depths less than 6 inches, the protective material is too easily displaced or compacted.)

NOTE: Do not install home playground equipment over concrete, asphalt, or any other hard surface. A fall onto a hard surface can result in serious injury to the equipment user. Grass and dirt are not considered protective surfacing because wear and environmental factors can reduce their shock absorbing effectiveness. Carpeting and thin mats are not adequate protective surfacing. Ground level equipment -- such as a sandbox, activity wall, playhouse or other equipment that has no elevated play surface -- does not need any protective surfacing.

- Use containment, such as digging out around the perimeter and/or lining the perimeter with landscape edging. Don't forget to account for water drainage.
- Periodically rake, check and maintain the depth of the loose-fill surfacing material. Marking the correct depth on the play equipment support posts will help you to see when the material has settled and needs to be raked and or replenished. Be sure to rake and evenly redistribute the surfacing in heavily used areas.
- Do not install loose fill surfacing over hard surfaces such as concrete or asphalt.

#### Poured-In-Place Surfaces or Pre-Manufactured Rubber Tiles


You may be interested in using surfacing other than loose-fill materials - like rubber tiles or poured-in-place surfaces.


- Installations of these surfaces generally require a professional and are not "do-it yourself" projects.
- Review surface specifications before purchasing this type of surfacing. Ask the installer/manufacturer for a report showing that the product has been tested to the following safety standard: ASTM F1292 Standard Specification for Impact Attenuation of Surfacing Materials within the Use Zone of Playground Equipment. This report should show the specific height for which the surface is intended to protect against serious head injury. This height should be equal to or greater than the fall height vertical distance between a designated play surface (elevated surface for standing, sitting, or climbing) and the protective surfacing below of your play equipment.
- Check the protective surfacing frequently for wear.

#### **Placement**

Proper placement and maintenance of protective surfacing is essential. Refer to diagram on front cover. Be sure to:

- Extend surfacing at least 2m from the equipment in all directions.
- For to-fro swings, extend protective surfacing in front of and behind the swing to a distance equal to twice the height of the top bar from which the swing is suspended.
- For tire swings, extend surfacing in a circle whose radius is equal to the height of the suspending chain or rope, plus 6 feet in all directions.





From the CPSC Outdoor Home Playground Safety Handbook. At http://www.playgroundregs.com/resources/CPSC%20324.pdf


# **Instructions for Proper Maintenance**

Your KidKraft Play System is designed and constructed of quality materials with your child's safety in mind. As with all outdoor products used by children, it will weather and wear. To maximize the enjoyment, safety and life of your Play Set, it is important that you, the owner, properly maintain it.


## Check the following at the beginning of the play season:

#### HARDWARF.

- Check metal parts for rust. If found, sand and repaint using a non-lead paint complying with 16 CFR 1303.
- ✓ Inspect and tighten all hardware. On wood assemblies DO NOT OVER-TIGHTEN as to cause crushing and splintering of wood.



Check for sharp edges or protruding screw threads, add washers if required.



#### SHOCK ABSORBING SURFACING:

✓ Check for foreign objects. Rake and check depth of loose fill protective surfacing materials to prevent compaction and maintain appropriate depth. Replace as necessary. (See Protective Surfacing, page 3)

#### GROUND STAKES (ANCHORS):

Check for looseness, damage or deterioration. Should firmly anchor unit to ground during use. Re-secure and or replace, if necessary.

#### SWING HANGERS:

- ✓ Check that bolts are secure and tight. Quick clips should be completely closed and threaded clips screwed tight.
- ✓ If squeaking occurs lubricate bushings with oil or WD-40®. SWINGS, ROPES AND RIDES:
- Reinstall if removed during cold season. Check all moving parts including swing seats, ropes, chains and attachments for wear, rust and other deterioration. Replace as needed.
- ✓ Check that ropes are tight, secure at both ends and cannot loop back as to create an entrapment.

### WOOD PARTS:

- ✓ Check all wood members for deterioration, structural damage and splintering. Sand down splinters and replace deteriorated wood members. As with all wood, some checking and small cracks in grain is normal.
- ✓ Unprotected, they will appear weathered over time.

  Periodic application of an exterior water repellent or stain (water-based) will help improve appearance and life.

### Check twice a month during play season:

#### HARDWARE:

- ✓ Inspect for tightness. Must be firmly against, but not crushing the wood. DO NOT OVER-TIGHTEN. This will cause splintering of wood.
- Check for sharp edges or protruding screw threads. Add washers if required.

#### SHOCK ABSORBING SURFACING:

✓ Rake and check depth of loose fill protective surfacing materials to prevent compaction and maintain appropriate depth. Replace as necessary. (See Protective Surfacing, page 3)

### Check once a month during play season:

#### SWING HANGERS:

- Check that they are secure and orientated correctly. Hook should rotate freely and perpendicular to support beam.
- ✓ If squeaking occurs lubricate bushings with oil or WD-40®.

### SWINGS AND RIDES:

 Check swing seats, all ropes, chains and attachments for fraying, wear, excessive corrosion or damage.
 Replace if structurally damaged or deteriorated.

### Check at the end of the play season:

#### SWINGS AND RIDES:

✓ To prolong their life, remove swings and store inside when outside temperature is below 32°F/0°C. Below freezing, plastic parts may become more brittle.

#### SHOCK ABSORBING SURFACING:

✓ Rake and check depth of loose fill protective surfacing materials to prevent compaction and maintain appropriate depth. Replace as necessary.

(See Protective Surfacing, page 3)

**If you dispose of your play set:** Please disassemble and dispose of your unit so that it does not create any unreasonable hazards at the time it is discarded. Be sure to follow your local waste ordinances.

# About Our Wood

KidKraft Premium Play Systems uses only premium playset lumber, ensuring the safest product for your children's use. Although we take great care in selecting the best quality lumber available, wood is still a product of nature and susceptible to weathering which can change the appearance of your set.

### What causes weathering? Does it affect the strength of my Play System?

One of the main reasons for weathering is the effects of water (moisture); the moisture content of the wood at the surface is different than the interior of the wood. As the climate changes, moisture moves in or out of the wood, causing tension which can result in checking and or warping. You can expect the following due to weathering. These changes will not affect the strength of the product:

- 1. **Checking** is surface cracks in the wood along the grain. A post (4" x 4") will experience more checking than a board (1" x 4") because the surface and interior moisture content will vary more widely than in thinner wood.
- 2. **Warping** results from any distortion (twisting, cupping) from the original plane of the board and often happens from rapid wetting and drying of the wood.
- 3. **Fading** happens as a natural change in the wood color as it is exposed to sun-light and will turn a grey over time.

### How can I reduce the amount of weathering to my Play System?

At the factory we have coated the wood with a water repellent or stain. This coating decreases the amount of water absorption during rain or snow thus decreasing the tension in the wood. Sunlight will break down the coating, so we recommend applying a water repellent or stain on a yearly basis (see your local stain and paint supplier for a recommended product).

Most weathering is just the normal result of nature and will not affect safe play and enjoyment for your child. However if you are concerned that a part has experienced a severe weathering problem please call our consumer relations department for further assistance.

# Complete and mail registration card to receive important product notifications and assure prompt warranty service.

# **5 Year Limited Warranty**

KidKraft warrants that this product is free from defect in materials and workmanship for a period of one year from the original date of purchase. In addition, lumber is warranted for 5 years against structural failure due to rot and insect damage. All other parts, such as hardware, swings, rides, accessories, and slides carry a one-year warranty only.

This warranty applies to the original owner and registrant and is non-transferable.

Regular maintenance is required to assure the integrity of your Play System. This warranty does not cover any inspection cost.

This Limited Warranty does not cover:

- Labor for replacement of any defective item(s);
- Incidental or consequential damages;
- Cosmetic defects which do not affect performance or integrity;
- Vandalism; improper use or installation; acts of nature;
- Minor twisting, warping, checking, or any other natural occurring properties of wood that do not affect performance or integrity.

KidKraft products have been designed for safety and quality. Any modifications made to the original product could damage the structural integrity of the unit leading to failure and possible injury. Kidkraft cannot assume any responsibility for modified products. Furthermore, modification voids any and all warranties.

This product is warranted for **RESIDENTIAL USE ONLY**. Under no circumstance should a KidKraft Play System be used in public settings such as schools, churches, playgrounds, parks, day cares and the like. Such use may lead to product failure and potential injury. Any and all public use will void this warranty.

KidKraft disclaims all other representations and warranties of any kind, express or implied.

This Warranty gives you specific legal rights. You may have other rights as well which vary from state to state or province to province. This warranty excludes all consequential damages, however, some states do not allow the limitation or exclusion of consequential damages, and therefore this limitation may not apply to you.

# **Keys to Assembly Success**

### **Tools Required**

- Tape Measure
- Carpenters Level
- Carpenters Square
- Claw Hammer
- Standard or Cordless Drill
- #1, #2 & #3 Phillips or Robertson Bits or Screwdriver
- Ratchet with extension (1/2" & 9/16" sockets)
- Open End Wrench (7/16", 1/2" & 9/16")
- Adjustable Wrench
- 1/8" & 3/16" Drill Bits


before proceeding.

Pencil

- 3/16" Hex Key
- 8' Step Ladder
- Safety Glasses
- Adult Helpers

### Part Identification Key

On each page, you will find the parts and quantities required to complete the assembly step illustrated on that page. Here is a sample.



### **Symbols**

Use

Help

Measure

Distance

Throughout these instructions symbols are provided as important reminders for proper and safe assembly.

This identifies information that requires special attention. Improper assembly could lead to an unsafe or dangerous condition.



Square Assembly

Use Help

Where this is shown, 2 or 3 people are required to safely complete the step. To avoid injury or damage to the assembly make sure to get help!

Check that assembly is square before tightening bolts.

Use a measuring tape to assure proper location.

Pre-drill 1/8" & 3/16" Bit ∕8 🖬 **∕**16 **■** 

Pre-drill a pilot hole before fastening screw or lag to prevent splitting of wood.

Tighten **Bolts** 

Use

Level


This indicates time to tighten bolts, but not too tight! Do not crush the wood. This may create splinters and cause structural damage.

Check that set or assembly is properly level





Once the assembly is tightened, watch for exposed threads. If a thread protrudes from the T-Nut, remove the bolt and add washers to eliminate this condition. Extra washers have been provided for this purpose.




#### **Proper Hardware Assembly**


Lag screws require drilling pilot holes to avoid splitting wood. Only a flat washer is required. For ease of installation liquid soap can be used on all lag-type screws.

For bolts, tap T-Nut into hole with hammer. Insert the hex bolt through lock washer first then flat washer then hole. Because the assemblies need to be squared do not completely tighten until instructed. Pay close attention to diameter of the bolts. 5/16" is slightly larger than 1/4".

Note: Wafer head bolts with blue lock tight or a bolt with a Ny-Lok nut do NOT require a lock washer.



Before mounting Lag Screw, use factory drilled holes as guides to drill 1/8" pilot holes






Lock

Washer

Flat

# Your Key To Quick Assembly


# SORTING WOOD PARTS INTO EACH ASSEMBLY STEP WILL SAVE TIME!



# **SAVE TIME - TIP #1:**

Wood parts are found in Box 2, 3, 4 & 5. Open each box with wood parts and look for the <u>Key Number</u> stamped on the end of the wood part (see chart below). Sort each wood part into the different assembly steps.





# **SAVE TIME - TIP #2:**


In addition to the key number stamp, you can also identify the wood parts by using the Parts Identification pages in the manual or the Parts Identification weather resistant poster.

# **HARDWARE:**


The majority of each hardware part comes packed in a separate bag so you do not need to sort the hardware. Each assembly step indicates which hardware (bolt, screw, washer etc.) you will require to complete the step.

1


Part Identification (Next Generation E)



# Add On "G" Part Identification (Quantities per box) (2 Boxes)




# Add on "H" Part Identification (Reduced Part Size)




10


# Add on "H" Hardware Identification (Actual Size)





# Add on "H" Hardware Identification (Actual Size)
























# Add on "J" Part Identification



# Add on "J" Hardware (Actual Size)







**38pc.** (LW1) - 1/4" Lock Washer - (51303200)

**40pc.** (51103200)

**10pc.** [**TN2**] - 5/16" T- Nut (54503300)



**60pc.** (FW2) - 5/16" Flat Washer - (51103300)

**5pc. BN1** - 1/4" Barrel Nut (54803200)




1pc. (\$5) - Pan Screw #8 x 1/2" (52433502)

**32pc.** (S13) - Pan Screw #6 x 5/8" - (52413908)

**8pc. §10** - Pan Screw #8 x 1" (52433510)

18pc. (\$7) - Pan Screw #12 x 2" - (52433620)



**101pc. So** - Truss Screw #8 x 7/8" - (52933505)

8pc. S18 - Wood Screw #6 x 1" - (52013910)

**65pc.** (\$30) - Wood Screw #8 x 1-1/16" - (52043517)


**78pc.** (S20) - Wood Screw #8 x 1-3/8" - (52043516)

**28pc.** (S11) - Wood Screw #8 x 2" - (52043520)


10pc. \$3 - Wood Screw #8 x 2-1/2" - (52043522)

**4pc.** (\$4) - Wood Screw #8 x 3" - (52043530)


# Add on "J" Hardware (Actual Size)




# Part Identification (Add On "T")




# Part Identification (Reduced Part Size)




# Part Identification (Actual Part Size)




# Part Identification (Reduced Part Size)



# First Step: Inventory Parts - Read This Before Starting Assembly



- **A.** This is the time for you to inventory all your hardware, wood and accessories, referencing the parts identification sheets. This will assist you with your assembly.
  - The wood pieces will have the key number stamped on the ends of the boards. Organize the wood pieces by step, as per the key numbering system below.



- Please refer to Page 6 for proper hardware assembly.
- Each step indicates which bolts and/or screws you will need for assembly, as well as any flat washers, lock washers, t-nuts or lock nuts.
- **B.** If there are any missing or damaged pieces or you need assistance with assembly please contact the consumer relations department directly. <u>Call us before going back to the store.</u>

1.800.933.0771 or 972.385.0100 customerservice@kidkraft.com canadacustomerservice@kidkraft.com For online parts replacement visit https://parts.kidkraft.com/

+31 20 305 8620 europecustomerservice@KidKraft.com For online parts replacement visit https://parts.kidkraft.eu/

- C. Read the assembly manual completely, paying special attention to ANSI warnings; notes; and safety/maintenance information on pages 1 6.
- **D.** Before you discard your cartons fill out the form below.
  - The carton I.D. stamp is located on the end of each carton. The tracking number is located on the KidKraft ID Plaque (9320374).
  - Please retain this information for future reference. You will need this information if you contact the Consumer Relations Department.

# MODEL NUMBER: F25010

CARTON I.D. STAMP: 14459	_ (Box 1)	CARTON I.D. STAMP:	_ 14459	(Box 4)
CARTON I.D. STAMP: 14459	_ (Box 2)	CARTON I.D. STAMP:	_ 14459	(Box 5)
CARTON I.D. STAMP: 14459	_ (Box 3)	CARTON I.D. STAMP:	_ 14459	(Box 6)
TRACKING NUMBER (fro	m ID Plaque): _			

# Step 1: Side Wall Prep Part 1




### It is important to assemble the frame on a flat, smooth surface.


**A:** Place (2771) End Post and (2770) End Post Left side by side with the grooves facing up and in. Put (2770) End Post Left on the right hand side. Place (2775) Panel Cross Support in the top grooves, (2772) Panel Floor Support in the middle grooves and (2769) Panel BT Frame in the bottom grooves. (fig. 1.1)

**B:** Make sure assembly is square then attach with 4 (S30) #8 x 1-1/16" Wood Screws per board. (fig. 1.1)

C: Tap 3 (TN1) 1/4" T-nuts in (2775) Panel Cross Support and (2772) Panel Floor Support and 2 in (2769) Panel BT Frame. (fig. 1.1 and 1.2)







# Step 1: Side Wall Prep Part 2



### It is important to assemble the frame on a flat, smooth surface.

**D:** Turn the assembly over, place (2774) Upright in the middle grooves of (2775) Panel Cross Support and (2772) Panel Floor Support then attach all boards with 8 (H9) 1/4 x 1-1/4" Hex Bolts (with lock washer and flat washer) connecting to the previously installed t-nuts. (fig. 1.3 and 1.4)

**E:** Repeat steps A-D to make 3 more Side Wall Assemblies.

Fig. 1.3


H9 x 3


2777

H9 x 3

2777

Flush





# Step 2: Front Wall Prep Part 1




### It is important to assemble the frame on a flat, smooth surface.


**A:** Place (2771) End Post and (2770) End Post Left side by side with the grooves facing up and in. (2770) End Post Left on the right hand side. Place (2769) Panel BT Frames in the top and bottom grooves and (2768) Panel Floor in the middle grooves. (fig. 2.1)

**B:** Make sure assembly is square then attach with 4 (S30) #8 x 1-1/16" Wood Screws per board. (fig. 2.1)

C: Tap in 2 (TN1) 1/4" T-nuts in (2768) Panel Floor and each (2769) Panel BT Frame. (fig. 2.1 and 2.2)








# **Step 2: Front Wall Prep Part 2**



### It is important to assemble the frame on a flat, smooth surface.

**D:** Turn the assembly over then attach all boards with 6 (H9) 1/4 x 1-1/4" Hex Bolts (with lock washer and flat washer) connecting to the previously installed t-nuts. (fig. 2.3 and 2.4)

**E:** Repeat steps A-D to make a second Front Wall Assembly.



### **Hardware**


12 x (H9) 1/4 x 1-1/4" Hex Bolt (1/4" lock washer & 1/4" flat washer)

### It is important to assemble the frame on a flat, smooth surface.

**A:** Place (2757) LT Post Assembly and (2758) RT Post Assembly on a hard, flat surface with the notches facing down. The top of the post assemblies have the longer notches. (fig. 3.1)

**B:** Tap 1 (TN2) 5/16" T-nut in the top holes and 1 (TN1) 1/4" T-nut in the middle and bottom holes. (fig. 3.1)

Fig. 3.1





2 x 2757 LT Post Assembly 1-1/4 x 2-1/2 x 87"

2 x 2758 RT Post Assembly 1-1/4 x 2-1/2 x 87"

**Hardware** 

4 x (TN2) 5/16" T-nut


8 x (TN1) 1/4" T-nut




### It is important to assemble the frame on a flat, smooth surface.

**C:** Turn the (2757) LT Post Assembly and (2758) RT Post Assembly over and place 2 (2756) Siding Assemblies on top so one sits flush with the top of the middle groove and the second fits flush with the top of the bottom groove. (fig. 3.2 and 3.3)

**D:** Place (2630) SW Top in the top grooves, (2768) Panel Floor in the middle grooves and (2769) Panel BT Frame in the bottom grooves so they sit flush to the outside edges of (2757) LT Post Assembly and (2758) RT Post Assembly. Make sure the assembly is square then attach with 4 (S30) #8 x 1-1/16" Wood Screws per board. (fig. 3.4)








### It is important to assemble the frame on a flat, smooth surface.

**E:** Attach (2630) SW Top to (2757) LT Post Assembly and (2758) RT Post Assembly with 2 (WB1) 5/16 x 1" Wafer Bolts (with flat washer) connecting to previously installed t-nuts. (fig. 3.5 and 3.6)

**F:** Attach (2768) Panel Floor to (2757) LT Post Assembly and (2758) RT Post Assembly with 2 (H9) 1/4 x 1-1/4" Hex Bolts (with lock washer and flat washer) connecting to previously installed t-nuts. (fig. 3.5)

**G:** Place 1 (2778) SW Ground MOD to each side of (2769) Panel BT Frame, notice the hole locations and attach with 1 (H10) 1/4 x 2-1/4" Hex Bolt (with lock washer and flat washer) per board connecting to previously installed t-nuts. (fig. 3.5 and 3.7)


**H:** Place 1 (2607) Diagonal under (2778) SW Ground MOD on the right hand side so the top sits against (2758) RT Post Assembly and loosely attach with 1 (H10) 1/4 x 2-1/4" Hex Bolt (with lock washer, flat washer and t-nut). (fig. 3.5 and 3.7)






### It is important to assemble the frame on a flat, smooth surface.

- **I:** Attach the top board in each (2756) Siding Assembly to (2757) LT Post Assembly and (2758) RT Post Assembly with 4 (S30) #8 x 1-1/16" Wood Screws per board. (fig. 3.8 and 3.9)
- **J:** Attach the remaining boards in each (2756) Siding Assembly to (2757) LT Post Assembly and (2758) RT Post Assembly with 2 (S0) #8 x 7/8" Truss Screws per board. (fig. 3.8 an 3.9)
- **K:** Repeat steps A-J to make a second Swing Wall Assembly.





#### **Hardware**


16 x (\$30) #8 x 1-1/16" Wood Screw


40 x (so) #8 x 7/8" Truss Screw



# It is important to assemble the Fort Assembly on a flat, smooth surface.


**A:** Place Swing Wall from Step 3 between 2 Side Walls from Step 1, noticing the wall orientations. The tops and bottoms of the walls should be flush. Make sure the walls are square then using the pilot holes as a guide predrill with a 3/16" drill bit and fasten the left Side Wall to the Swing Wall and Swing Wall to the right Side Wall with 4 (WL5) 1/4 x 2-1/2" Wafer Lags per side. (fig. 4.1, 4.2 and 4.3)









**B:** Place Front Wall from Step 2 between the Side Walls noticing the wall orientation. The tops and bottoms of the walls should be flush. Make sure the walls are square then using the pilot holes as a guide pre-drill with a 3/16" drill bit and fasten the right Side Wall to the Front Wall and Front Wall to the left Side Wall with 4 (WL5) 1/4 x 2-1/2" Wafer Lags per side. (fig. 4.4)









C: Loosely attach 1 (2607) Diagonal to left (2778) SW Ground MOD with 1 (H10) 1/4 x 2-1/4" Hex Bolt (with lock washer, flat washer and t-nut). (fig. 4.5)

**D:** Place each (2607) Diagonal tight and flush to the front of the Swing Wall then pre-drill pilot holes with a 3/16" drill bit and attach each (2607) Diagonal to the Swing Wall with 1 (LS3) 1/4 x 3" Lag Screw (with flat washer) per board, checking that they remain flush to outside edge. (fig. 4.5 and 4.6)

E: Repeat steps A-D to make a second Fort Assembly. Tighten all bolts in both assemblies.










### Complete Step 5 for both Fort Assemblies.

**A:** From inside of the assembly centre (2608) Floor Joist over the pilot holes in both (2768) Panel Floors in the Swing and Front Walls, measure 5/8" down from the top of boards then attach (2608) Floor Joist to each board using the left and centre holes with 2 (S4) #8 x 3" Wood Screws per board. (fig.5.1, 5.2, 5.3 and 5.4)




### **Wood Parts**


2 x 2608 Floor Joist 1-1/4 x 3 x 40-3/4"

#### **Hardware**

8 x (S4) #8 x 3" Wood Screw



**B:** On the inside of both the Side Walls place 1 (2777) Side Joist MOD against each (2772) Panel Floor Support, line up bolt holes then loosely attach with 2 (H11) 1/4 x 2-3/4" Hex Bolts (with lock washer, flat washer and t-nut) per joist. Make sure both (2777) Side Joist MODs are level with (2608) Floor Joist. (fig. 5.5)



### **Wood Parts**

4 x 2777 Side Joist MOD 2 x 2 x 40-1/4"


#### **Hardware**

8 x (Hit) 1/4 x 2-3/4" Hex Bolt (1/4" lock washer, 1/4" flat washer, 1/4" t-nut)



C: Fasten each (2777) Side Joist MOD to each (2772) Panel Floor Support with 4 (S3) #8 x 2-1/2" Wood Screws per board as shown in fig. 5.6.


**D:** Tighten all (H11) 1/4 x 2-3/4" Hex Bolts in both (2777) Side Joist MOD.




### **Hardware**

16 x (S3) #8 x 2-1/2" Wood Screw

**E:** Starting at the Swing Wall place (2648) Floor Board followed by 8 (2609) Floor Boards. Make sure all boards are evenly spaced then attach to (2608) Floor Joist and each (2777) Side Joist MOD with 5 (S20) #8 x 1-3/8" Wood Screws per board. (fig. 5.7 and 5.8)







# Step 6: Attach Tunnel Inserts Part 1



# MOVE FORT TO FINAL LOCATION PRIOR TO STAKING FINAL LOCATION MUST BE LEVEL GROUND

**A:** The Fort Assembly on the left will be referred to as Unit A and the Fort Assembly on the right will be referred to as Unit B. The inner Side Walls will now be Tunnel Side Walls. (fig. 6.1 and 6.2)

**B:** Place Unit A and Unit B side by side so the opening next to the Swing Wall in Unit A Tunnel Side Wall lines up with the opening next to the Front Wall in Unit B Tunnel Side Wall. (fig. 6.2)

**C:** The distance between Unit A and Unit B must be 33-1/2". Measure at the ground, floor and top to make sure distances are the same. (fig. 6.1)






Fig. 6.2




# Step 6: Attach Tunnel Inserts Part 2

**D:** Place 1 (9084) Lower Tunnel Insert in each of the openings facing each other, tight to the floor boards and attach with 4 (S0) #8 x 7/8" Truss Screws per insert. (fig. 6.3 and 6.4)

**E:** In the opening in Unit B place 1 (9089) Upper Tunnel Insert tight to (2775) Panel Cross Support and attach with 4 (S0) #8 x 7/8" Truss Screws. (fig. 6.3 and 6.4)





12 x (SO) #8 x 7/8" Truss Screw

## Step 7: Tunnel Floor Assembly Part 1







A: Tap in 2 (TN2) 5/16" T-nuts in each (9088) Tunnel Side Joist. (fig. 7.1)

**B:** With the (TN2) 5/16" T-nuts at the bottom measure 1" in from both ends of each (9088) Tunnel Side Joist then attach 1 (9086) Tunnel Top to each end with 4 (S4) #8 x 3" Wood Screws per board. Tops of boards to be flush. (fig. 7.1)

**C:** The distance diagonally from end of each (9088) Tunnel Side Joist must be 39-13/16". Tunnel Floor Frame must be square. (fig. 7.2)





#### **Wood Parts**

2 x 9088 Tunnel Side Joist 1-1/4 x 3 x 36"

2 x 9086 Tunnel Top 1-1/4 x 3 x 14-7/16"

#### **Hardware**

4 x (TN2) 5/16" T-nut


8 x (S4) #8 x 3" Wood Screw


### **Step 7: Tunnel Floor Assembly Part 2**



**D:** Flush to the ends and sides of both (9088) Tunnel Side Joist place 1 (9087) Floor Board followed by 7 (9092) Floor Boards. Make sure the last board is flush to the ends of each (9088) Tunnel Side Joist then attach all floor boards with 4 (S20) #8 x 1-3/8" Wood Screws. (fig. 7.3)

**E:** Measure 1-1/4" in from both ends of each (9088) Tunnel Side Joist then attach 1 Swing Bracket to each end with 1 (WB2) 5/16 x 1-3/8" Wafer Bolt (with flat washer, connects to already installed t-nuts) per bracket. Brackets must be flush to the bottom of the boards. (fig. 7.4)






 Wood Parts
 Hardware
 Other Parts

 1 x 9007 Floor Board 1 x 4 x 16-7/8"
 32 x 520 #8 x 1-3/8" Wood Screw
 4 x Swing Bracket


 7 x 9002 Floor Board 1 x 5 x 16-7/8"
 4 x √ WB2 5/16 x 1-3/8" Wafer Bolt (5/16" flat washer)

### **Step 8: Attach Tunnel Floor Assembly to Fort**



**A:** Place Tunnel Floor Assembly between Unit A and Unit B tight to each (9084) Lower Tunnel Insert then attach with 4 (S4) #8 x 3" Wood Screws from the inside and 4 (S0) #8 x 7/8" Truss Screws from the outside per end. (fig. 8.1, 8.2 and 8.3)

**B:** Pre-drill with a 3/16" drill bit then attach each Swing Bracket to the fort with 1 (WL3) 1/4 x 1-3/8" Wafer Lag (with flat washer) per bracket. (fig. 8.2 and 8.4)



#### **Hardware**

- 4 x (WL3) 1/4 x 1-3/8" Wafer Lag (1/4" flat washer)
- 8 x (so) #8 x 7/8" Truss Screw
- 8 x (S4) #8 x 3" Wood Screw


### Step 9: Tunnel Assembly Part 1

A: Bend all 4 MOD Tunnel Panels as shown in fig. 9.1.

**B:** Match 2 MOD Tunnel Panels together by making a slight "V" with the pieces so the peak of the "V" faces away from you. Make sure connector tabs are coupled then straighten the 2 panels. Push down on one panel and up on the other until you hear the connector tabs click together and the bottom edges are flush. You may have to knock panels on a hard surface to align properly. (fig. 9.2 and 9.3)

C: Press nodules through the connector tab holes to hold Tunnel panels in place. (fig. 9.3)

**D:** Repeat Steps B-C to create a second Tunnel Side.




Other Parts
4 x MOD Tunnel Panels

## Step 9: Tunnel Assembly Part 2

**E:** Attach the tops of each Tunnel Side together using 2 (MB1) #12 x 1/2" Pan Bolts (with #12 Lock Nut) per side. (fig. 9.4 and 9.5)

**F:** Join the 2 Tunnel Sides together so the tops are tight together and attach with 6 (MB1) #12 x 1/2" Pan Bolts (with #12 Lock Nut). (fig. 9.6 and 9.7)




Hardware

10 x (MB1) #12 x 1/2" Pan Bolt (#12 Lock Nut)

## **Step 10: Attach Tunnel Assembly to Fort Part 1**

**A:** From inside Unit A slide the Tunnel Assembly through the opening onto the Tunnel Floor Assembly so it sits tight to the (9089) Upper Tunnel Insert on Unit B, both posts and both (2774) Uprights and the tunnel floor boards. (fig. 10.1, 10.2 and 10.3)




## **Step 10: Attach Tunnel Assembly to Fort Part 2**

**B:** Attach Tunnel Assembly to the posts and (2774) Uprights through the connector tab holes with 4 (S10) #8 x 1" Pan Screws per end. (fig. 10.4 and 10.5)

C: Attach Tunnel Assembly to (9089) Upper Tunnel Insert with 4 (S10) #8 x 1" Pan Screws. (fig. 10.4 and 10.6)

**D:** Attach Tunnel Assembly to each (9088) Tunnel Side Joist with 6 (S10) #8 x 1" Pan Screws per side. (fig. 10.4 and 10.7)




Hardware
32 x (\$10) #8 x 1" Pan Screw

#### **Step 10: Attach Tunnel Assembly to Fort** Part 3

E: From inside Unit A place 1 (9089) Upper Tunnel Insert tight to (2775) Panel Cross Support and attach with 4 (S0) #8 x 7/8" Truss Screws. (fig. 10.8 and 10.9)

F: Attach Tunnel Assembly to (9089) Upper Tunnel Insert with 4 (S10) #8 x 1" Pan Screws. (fig. 10.8 and 10.10)



1 x 9089 Upper Window Insert 1.27 x 8.25 x 18.8"

#### **Hardware**

#8 x 7/8" Truss Screw

#8 x 1" Pan Screw

### **Step 11: Swing Beam Assembly**




**A:** Attach 6 Swing Hangers to the (2614) Engineered Beam using 2 (G7) 5/16 x 5-1/2" Hex Bolts (with 2 flat washers and 1 lock nut) per Swing Hanger as shown in fig. 11.1.

**B:** Flush to the Fort End of (2614) Engineered Beam attach 2 L-Beam Brackets with 2 (G21) 5/16 x 3-3/4" Hex Bolts (with 2 flat washers and 1 lock nut). (fig. 11.1 and 11.2)

C: Install 1 (WB7) 5/16 x 3" Wafer Bolt (with flat washer and t-nut) in the middle bolt hole in (2614) Engineered Beam as shown in fig. 11.3. IT IS IMPORTANT THAT THIS BOLT IS ATTACHED. IT WILL MINIMIZE CHECKING OF WOOD.

**D:** Attach KidKraft Plaque to centre of (2614) Engineered Beam (over top of t-nut) using 4 (S18) #6 x 1" Wood Screws. (fig. 11.4)



Wood Parts	<u>Hardware</u>	Other Parts
1 x 2614 Engineered Beam 4 x 6 x 88"	12 x G7 5/16 x 5-1/2" Hex Bolt (5/16" flat washer x 2, 5/16" lock nut)	6 x Swing Hangers
_ "	2 x (G21) 5/16 x 3-3/4" Hex Bolt (5/16" flat washer x 2, 5/16" lock nut)	2 x L-Beam Bracket
	1 x (WB7) 5/16 x 3" Wafer Bolt (5/16" flat washer & 5/16" t-nut)	1 x KidKraft Plaque
	4 x (s18) #6 x 1" Wood Screw	


### **Step 12: Swing End Assembly**



**A:** Loosely attach 2 (2613) Heavy SW Posts to (2615) SW Upright using 2 (G7) 5/16 x 5-1/2" Hex Bolts (with lock washer, flat washer and t-nut). Notice 2 bolt holes at top of (2615) SW Upright and orientation of angle. (fig. 12.1)

**B:** Attach (2616) SW Support to both (2613) Heavy SW Posts and (2615) SW Upright using 3 (G4) 5/16 x 4" Hex Bolts (with lock washer, flat washer and t-nut). Tighten all bolts (fig. 12.1)

C: Install 2 (WB7) 5/16 x 3" Wafer Bolts (with flat washer and t-nut) in the top bolt holes in (2615) SW Upright as shown in fig. 12.1. IT IS IMPORTANT THAT THESE BOLTS ARE ATTACHED. THEY WILL MINIMIZE CHECKING OF WOOD.



#### **Wood Parts**

2 x 2613 Heavy SW Post 2 x 3 x 86-11/16"

1 x 2615 SW Upright 4 x 4 x 50-15/16"

1 x 2616 SW Support 5/4 x 4 x 46-1/2"

#### **Hardware**

2 x (G7) 5/16 x 5-1/2" Hex Bolt (5/16" lock washer, 5/16" flat washer, 5/16" t-nut)


3 x (G4) 5/16 x 4" Hex Bolt (5/16" lock washer, 5/16" flat washer, 5/16" t-nut)

2 x (WB7) 5/16 x 3" Wafer Bolt (5/16" flat washer & 5/16" t-nut)

### Step 13: Attach Swing End to Swing Beam



**A:** Place Swing End Assembly against Swing Beam Assembly then place 1 Beam Bracket on each side of the assembly (they are specific for left and right side) and attach with 5 (G21) 5/16 x 3-3/4" Hex Bolts (with 2 flat washers and 1 lock nut). (fig. 13.1 and 13.2)



**Hardware** 

5 x (521) 5/16 x 3-3/4" Hex Bolt (5/16" flat washer x 2, 5/16" lock nut)

**Other Parts** 

2 x Beam Bracket (Left/Right)


### **Step 14: Attach Swing Assembly To Fort**








**A:** On Unit B place Swing Assembly against top of (2630) SW Top, make sure assembly is level then attach from inside the fort assembly into each L-Beam Bracket with 4 (G8) 5/16 x 2" Hex Bolts (with 2 flat washers and 1 lock nut). (fig. 14.1 and 14.2)





#### **Hardware**

4 x (G8) 5/16 x 2" Hex Bolt (5/16" flat washer x 2, 5/16" lock nut)


#### **Step 15: Install Ground Stakes**

**A:** In the 6 places shown in fig. 15.1 drive the Rebar Ground Stakes 13" into the ground against all 4 (2607) Diagonals and both (2613) Heavy SW Posts. Be careful not to hit the washer while hammering stakes into the ground as this could cause the washer to break off.

**B:** Attach ground stakes using 1 (S7) #12 x 2" Pan Screw per ground stake. (fig. 15.2)

**C:** After driving stakes into the ground, check for sharp edges caused by the impact of the hammer. Smooth any sharp edges from impact area and touch up with outdoor paint.

AWarning! To prevent tipping and avoid potential injury, stakes must be driven 13" into ground. Digging or driving stakes can be dangerous if you do not check first for under-ground wiring, cables or gas lines.




Hardware
6 x (S7) #12 x 2" Pan Screw

Other Parts
6 x Rebar Ground Stake

## Step 16: Install Upper and Lower Jambs Part 1



**A:** In the lower opening of each Unit A Side Wall and Tunnel Side Wall and the outer Side Wall in Unit B place 1 (2601) Lower Jamb so it measures 17" to the inside of each post then attach each (2601) Lower Jamb with 2 Jamb Mounts using 4 (S0) #8 x 7/8" Truss Screws per mount. (fig. 16.1, 16.2, 16.3, 16.4 and 16.5).



 Wood Parts
 Hardware
 Other Parts

 3 x 2501
 Lower Jamb 1-1/4 x 3 x 41-15/16"
 24 x (50) #8 x 7/8" Truss Screw
 6 x Jamb Mount

### Step 16: Install Upper and Lower Jambs Part 2




**Other Parts** 

6 x Jamb Mount

**B**: On the Front Wall in Unit A place 1 (2602) Upper Jamb in the upper opening so it measures 9-5/8" to the inside of the right post and 1 (2601) Lower Jamb in the lower opening so it measures 17" to the inside of each post then attach each board with 2 Jamb Mounts to (2769) Panel BT Frames and (2768) Panel Floor using 4 (S0) #8 x 7/8" Truss Screws per mount. The bottom Jamb Mount in each (2602) should not measure more than 1" down from top of board. (fig. 16.6, 16.8, 16.9 and 16.10)

**C:** In the upper opening of Unit B Front Wall place 1 (2602) Upper Jamb so it measures 17" to the inside of each post then attach to (2769) Panel BT Frame and (2768) Panel Floor with 2 Jamb Mounts using 4 (S0) #8 x 7/8" Truss Screws per mount. (fig. 16.7, 16.8, 16.9 and 16.10). Note 1" measurement as noted in B.



**Hardware** 

24 x (so) #8 x 7/8" Truss Screw

**Wood Parts** 

2 x 2602 Upper Jamb 1-1/4 x 3 x 35-15/16"

1 x 2601 Lower Jamb 1-1/4 x 3 x 41-15/16"

## Step 17: Install Window and Wall Inserts Part 1 - Unit A Front Wall

A: In the lower openings of Unit A Front Wall install 2 (2649) Lower Window Inserts using 9 (S0) #8 x 7/8" Truss Screws per insert. (fig. 17.1, 17.2 and 17.3) B: In the upper openings of Unit A Front Wall install 1 (8935) Lower SL Insert with 4 (S0) #8 x 7/8" Truss Screws and 1 MOD Side Lite with 14 (S0) #8 x 7/8" Truss Screws. (fig. 17.1, 17.2 and 17.4) MOD Side Lite Fig. 17.2 Fig. 17.1 Unit A **Outside View** 2602 8935 2649 2649 **Front Wall** Fig. 17.3 **Inside View** Fig. 17.4 MOD Side Lite **Inside View** 2649 S0 8935 S0 -Tight


 Wood Parts
 Hardware
 Other Parts

 2 x 2649
 Lower Window Insert 1.27 x 18.8 x 41.91"
 36 x (50) #8 x 7/8" Truss Screw
 1 x MOD Side Lite (from TNR III box)

 1 x 8935
 Lower SL Insert 1.36 x 8-1/8 x 26-1/4" (from TNR III box)
 (from TNR III box)

## **Step 17: Install Window and Wall Inserts Part 2 - Unit A Tunnel Side Wall**

C: In the lower opening of Unit A Tunnel Side Wall under the tunnel install 1 (2649) Lower Window Insert and in the upper opening beside the tunnel install 1 (2655) Upper Window Inserts using 9 (S0) #8 x 7/8" Truss Screws per insert. (fig. 17.5, 17.6 and 17.7) Fig. 17.5 Unit A Tunnel **Tunnel Position** Fig. 17.6 Outside View 2655 Fig. 17.7 Inside View 2655 and 2649 (S0<sup>°</sup> 2601 2649 S0



\_Tight

## **Step 17: Install Window and Wall Inserts Part 3 - Unit A Side Wall**


**D:** In the upper openings of Unit A Side Wall install 2 MOD Arches using 3 (S0) #8 x 7/8" Truss Screws per insert. (fig. 17.8, 17.9 and 17.10)


**E:** In the left hand upper opening and both lower openings install 3 (649A) Short Half Walls using 4 (S0) #8 x 7/8" Truss Screws per insert. (fig. 17.8, 17.9 and 17.11)


Fig. 17.8

Side Wall

Unit A







Wood Parts
3 x 649A Short Half Wall 1.27 x 18.8 x 20-15/16"

Hardware


18 x (SO) #8 x 7/8" Truss Screw

Other Parts
2 x MOD Arch

## Step 17: Install Window and Wall Inserts Part 4 - Unit B Front Wall

**F:** In the lower opening of Unit B Front Wall install 1 (2665) Half Wall Insert using 4 (S0) #8 x 7/8" Truss Screws. (fig. 17.12, 17.13 and 17.14)

**G:** In the right hand upper opening of Unit B Front Wall install 1 (2655) Upper Window Insert using 9 (S0) #8 x 7/8" Truss Screws and in the upper opening on the left hand side install 1 MOD Arch using 3 (S0) #8 x 7/8" Truss Screws. (fig. 17.12, 17.13, 17.15 and 17.16)



 Wood Parts
 Hardware
 Other Parts

 1 x 2665
 Half Wall Insert 1.4 x 20-1/4 x 38.8"
 16 x 50 #8 x 7/8" Truss Screw
 1 x MOD Arch

 1 x 2655
 Upper Window Insert 1.27 x 18.8 x 35.86"
 1 x MOD Arch

## Step 17: Install Window and Wall Inserts Part 5 - Unit B Tunnel Side Wall

H: In the upper opening of Unit B Tunnel Side Wall beside the tunnel install 1 (2655) Upper Window Inserts using 9 (S0) #8 x 7/8" Truss Screws. (fig. 17.17, 17.18 and 17.19) I: In the lower opening of Unit B Tunnel Side Wall install 1 (2665) Half Wall Insert using 4 (S0) #8 x 7/8" Truss Screws. (fig. 17.17, 17.18 and 17.20) Tunnel Fig. 17.18 Fig. 17.17 **Outside View Unit B** 2655 Tunnel Position 2665 Fig. 17.19 **Inside View** 2655 Fig. 17.20 2665 Inside View (SO Tight **Tight** 

### Wood Parts

1 x 2665 Half Wall Insert 1.4 x 20-1/4 x 38.8"

1 x 2655 Upper Window Insert 1.27 x 18.8 x 35.86"

#### **Hardware**


13 x (SO) #8 x 7/8" Truss Screw


## Step 17: Install Window and Wall Inserts Part 6 - Unit B Side Wall


**J:** In the lower right hand opening of Unit B Side Wall install 1 (2649) Lower Window Insert using 9 (S0) #8 x 7/8" Truss Screws. (fig. 17.21, 17.22 and 17.23)

**K:** In the upper openings and left hand lower opening of Unit B Side Wall install 3 MOD 3-Pane Transoms with 4 (S0) #8 x 7/8" Truss Screws per insert. (fig. 17.21, 17.22 and 17.24)

Fig. 17.23
Inside View







1 x 2649 Lower Window Insert 1.27 x 18.8 x 41.91"

**Wood Parts** 

<u>Hardware</u> 21 x (so) #8 x 7/8" Truss Screw

Other Parts
3 x MOD 3-Pane Transom

### **Step 18: Clock Assembly**

1 x 2717 Clock Block 3/4 x 1-3/4 x 9-3/4"




1 x Gable Clock Assembly

**A:** From inside the assembly place (2717) Clock Block centred on the panel of (2655) Upper Window Insert then attach with 1 (S13) #6 x 5/8" Pan Screw. (fig. 18.1 and 18.2)

**B:** On Unit B Front Wall place Gable Clock Assembly centred under window of (2655) Upper Window Insert then attach to (2602) Upper Jamb and (2771) End Post with 2 (S10) #8 x 1" Pan Screws. (fig. 18.3 and 18.4)

**C:** Attach peak of Gable Clock Assembly through insert into (2717) Clock Block with 1 (S10) #8 x 1" Pan Screw and bottom centre to insert with 1 (S5) #8 x 1/2" Pan Screw. (fig. 18.4)




3 x (S10)

#8 x 1" Pan Screw

#6 x 5/8" Pan Screw

### Step 19: Rock Wall Assembly





Complete Step 19, A-E twice to make 2 Rock Wall Assemblies.

A: Lay 2 (2776) Rock Rails down, side by side with angled edges facing down. (fig. 19.1)

**B:** Place (2779) Access Board on the bottom of each (2776) Rock Rail as shown in fig. 19.1. Make sure (2779) Access Board is flush to the outside and bottom edges of each (2776). Attach using 4 (S20) #8 x 1-3/8" Wood Screws.

C: 7-5/8" down from the top of both (2776) Rock Rails place 1 (2781) Rk Board B, making sure the sides are flush to the outside edges of each (2776) Rock Rail. Attach using 4 (S20) #8 x 1-3/8" Wood Screws. (fig. 19.1)

**D:** In between the (2779) Access Board and (2781) Rk Board B stagger 2 (2781) Rk Board Bs and 2 (2780) Rk Board As using 4 (S20) #8 x 1-3/8" Wood Screws per board. Placing them as shown in fig. 19.1, this will prevent rocks from forming a straight line. Make sure the boards are evenly spaced and do not exceed 2-3/8" between boards.




Fig. 19.2

E: Place 1 rock on each (2780) Rk Board A and (2781) Rk Board B (fig. 19.2) and attach using 1 (PB2) 1/4 x 1-1/4" Pan Bolt (with lock washer, flat washer and barrel nut) and 1 (S10) #8 x 1" Pan Screw per rock. The Screw must be in the hole directly under the Pan Bolt, it will stop the rock from spinning. (fig. 19.3)

#### **Wood Parts Hardware Other Parts** 10 x Rocks (6 green/4 yellow) 2 x 2779 Access Board 1 x 6 x 19" 48 x (\$20) #8 x 1-3/8" Wood Screw 6 x 2781 Rk Board B 1 x 6 x 19"

4 x 2780 Rk Board A 1 x 6 x 19"

4 x 2776 Rock Rail 1-1/4 x 2-1/2 x 51"

#8 x 1" Pan Screw


(1/4" lock washer, 3/16" flat washer & 1/4" barrel nut)

# Step 20: Attach Rock Wall Assembly to Fort Part 1

**A:** Place the Rock Wall Assemblies centred in openings of Unit A Side Wall and Unit B Front Wall flush as shown below. Attach (2776) Rock Rails using 2 (S11) #8 x 2" Wood Screws per rail. (fig. 20.1, 20.2 and 20.3)

**B:** Attach 1 (2779) Access Board to top of each Rock Wall Assembly, flush to top of (2776) Rock Rails using 4 (S20) #8 x 1-3/8" Wood Screws per board. (fig. 20.1 and 20.4)

Note: Make sure (2776) Rock Rails do not cover the bolt heads, move assembly over so it is tight to the bolt head. (fig. 20.3)



2 x 2779 Access Board 1 x 6 x 19"

**Wood Parts** 

**Hardware** 

8 x (\$20) #8 x 1-3/8" Wood Screw

8 x (S11) #8 x 2" Wood Screw


## Step 20: Attach Rock Wall Assembly to Fort Part 2


**C:** Drive 1 Rebar Ground Stake 13" into the ground against 1 (2776) Rock Rail per assembly then attach with 1 (S7) #12 x 2" Pan Screw per ground stake. Be careful not to hit the washer while hammering stake into the ground as this could cause the washer to break off. (fig. 20.5 and 20.6)

**D:** After driving stake into the ground, check for sharp edges caused by the impact of the hammer. Smooth any sharp edges from impact area and touch up with outdoor paint.

**AWarning!** To prevent tipping and avoid potential injury, stakes must be driven 13" into ground. Digging or driving stakes can be dangerous if you do not check first for under-ground wiring, cables or gas lines.

Fig. 20.5





**Hardware** 

2 x (S7) #12 x 2" Pan Screw

Other Parts
2 x Rebar Ground Stake


### Step 21: Attach Hand Grip to Fort





**A:** Measure 6" from the top of the floor boards on the left hand side of each Rock Board, pre-drill with a 1/8" drill bit then attach 1 Hand Grip per wall with 2 (WL3) 1/4 x 1-3/8" Wafer Lags per Hand Grip. (fig. 21.1)

Fig. 21.1




Hardware
4 x WL3 1/4 x 1-3/8" Wafer Lag


Other Parts 2 x Hand Grip

### **Step 22: Cafe Table Assembly**

**A:** Place 1 (2612) Table Support flush to the notched out ends of 1 (2611) Table Top and attach with 4 (S7) #12 x 2" Pan Screws as shown in fig. 22.1.

**B:** Place Table Top Assembly tight in the opening of Unit B Tunnel Side Wall with the overhang on the outside of the assembly as shown in fig. 22.3 then attach (2612) Table Support to the End Wall posts with 2 (S3) #8 x 2-1/2" Wood Screws. (fig. 22.2 and 22.3)





#### **Wood Parts**

- 1 x 2612 Table Support 2 x 2 x 39-5/8"
- 1 x 2611 Table Top 5/4 x 5 x 39-5/8"


#### <u>Hardware</u>

- 4 x (S7) #12 x 2" Pan Screw
- 2 x (S3) #8 x 2-1/2" Wood Screw

#### Step 23: Attach Wall Tops

**A:** From inside the assembly place 1 (2804) Wall Top tight to the posts and top of (2665) Half Wall Insert on Front Wall of Unit B and tight to the posts and top of (2756) Siding Assembly on Swing Wall of Unit B then attach to the posts with 2 (S11) #8 x 2" Wood Screws per (2804) Wall Top. (Fig. 23.1, 23.2 and 23.3)

**B:** Attach (2804) Wall Tops to (2756) Siding Assembly and (2665) Half Wall Insert with 2 Corner Brackets per panel using 3 (S13) #6 x 5/8" Pan Screws per bracket. Corner Brackets are attached to the inside slats of the panels. (fig. 23.4)




## **Step 24: Attach Door Components Part 1**



**A:** On the inside of (2709) Door Window Panel measure 15" up from the bottom and attach Catch Plate flush to the edge using 2 (S18) #6 x 1" Wood Screws. (fig. 24.1)

**B:** On the inside of (2709) Door Window Panel measure 22" up from the bottom and attach 1 Door Handle using 2 (S13) #6 x 5/8" Pan Screws. (fig. 24.1)



Wood Parts Hardware Other Parts

1 x 2709 Door Window Panel 1-1/4 x 15-3/4 x 40-3/4"

2 x (\$18) #6 x 1" Wood Screw 2 x (\$13) #6 x 5/8" Pan Screw

1 x Door Handle
1 x Catch Plate


## **Step 24: Attach Door Components Part 2**



**C:** On the outside of the (2709) Door Window Panel attach the second Door Handle at approximately the same place as the one on the inside. Use 2 (S13) #6 x 5/8" Pan Screws. (fig. 24.2)

**D:** On the opposite side of the Door Handle measure 5/8" from the top and bottom of (2709) Door Window Panel attach 2 Door Hinges on the outside using 3 (S13) # 6 x 5/8" Pan Screws per Hinge. (fig. 24.2 and 24.4)

**Note:** Hinge stops must be tight to (2709) Door Window Panel. (fig. 24.3)



Hardware 8 x (S13) #6 x 5/8" Pan Screw Other Parts
1 x Door Handle
2 x Door Hinge

### **Step 24: Attach Door Components**

#### Part 3



**E:** On the outside bottom edge of (2709) Door Window Panel measure 1" up from the hinge and install 1 Door Bumper using 1 (S0) #8 x 7/8" Truss Screw. There should be a measurement of 5/8" from the back of (2709) Door Window Panel to the screw hole. (Fig. 24.5 & 24.6)

Fig. 24.5
Side View

5/8"
1.59cm

Door Bumper

1"

2.54cm

Fig. 24.6


Hardware
1 x (so) #8 x 7/8" Truss Screw

Other Parts
1 x Door Bumper

### **Step 25: Attach Door Assembly to Fort**



**A:** On the Tunnel Side Wall of Unit A measure 5/8" up from the top of (2769) Panel BT Frame and a maximum 5/8" from the inside edge of (2601) Lower Jamb then attach the remaining side of the hinges to (2601) Lower Jamb using 3 (S13) #6 x 5/8" Pan Screws per hinge. (fig. 25.1, 25.2 and 25.3)



Hardware
6 x (513) #6 x 5/8" Pan Screw

### Step 26: Attach Door Stop


1 x 2715 Door Stop 5/4 x 3 x 10"



1 x Magnetic Catch

**A:** In the notched out opening of (2715) Door Stop attach the Magnetic Catch using 2 (S18) #6 x 1" Wood Screws. (fig. 26.1) **Important: Use a hand held screw driver and DO NOT over tighten.** 

**B:** On the inside of the assembly, attach (2715) Door Stop to (2770) End Post Left with 3 (S11) #8 x 2" Wood Screws, making sure (2715) Door Stop has an overhang of 1-1/4" and is in position to receive the Catch Plate. (fig. 26.2 and 26.3)



2 x (S18) #6 x 1" Wood Screw


(S11) #8 x 2" Wood Screw

### Step 27: Counter Assembly Part 1

**A:** Flush to each end and to the top of (2687) Counter Back attach 1 (5736) Counter Joist per end with 1 (S20) #8 x 1-3/8" Wood Screw per joist. Notice the remaining holes at the bottom of (2687) Counter Back. (fig. 27.1)

**B:** Place the remaining 2 (5736) Counter Joists centred over the pilot holes in the middle of (2687) Counter Back and flush to the top of the board, then attach, in the top holes, with 1 (S20) #8 x 1-3/8" Wood Screw per joist. (fig. 27.1)

Fig. 27.1





1 x 2687 Counter Back 1 x 4 x 40-5/8"


4 x 5736 Counter Joist 1 x 2 x 8-1/4"

#### **Hardware**

4 x (S20) #8 x 1-3/8" Wood Screw

#### **Step 27: Counter Assembly** Part 2


C: On the inside of the Swing Wall on Unit B place Counter Assembly so the top of (2687) Counter Back is flush to



**Hardware** #8 x 1-3/8" Wood Screw

## **Step 27: Counter Assembly Part 3**

**D:** Place 1 (6136) Counter Brace flush to the front and outside edge of each outer (5736) Counter Joist and tight to Swing Wall then attach with 2 (S3) #8 x 2-1/2" Wood Screws per brace. (fig. 27.4 and 27.5)




2 x 6136 Counter Brace 1 x 2 x 12-9/16"

4 x (S3) #8 x 2-1/2" Wood Screw



**E:** Place (2686) Counter Front against (5736) Counter Joists so the ends are flush and the centre (5736) Counter Joists are centred over the pilot holes. Measure 5/8" down from the top of (2686) Counter Front on both ends and attach to the (5736) Counter Joists with 4 (S20) #8 X 1-3/8" Wood Screws. (fig. 27.6)



1 x 2686 Counter Front 5/8 x 2-3/4 x 40-5/8"

**Wood Parts** 


Hardware
4 x (\$20) #8 x 1-3/8" Wood Screw

**F:** Tight to (2687) Counter Back attach (2685) Counter Top to each (5736) Counter Joist with 4 (TS) #6 x 30 mm Trim Screws. (fig. 27.7)

**G:** Tight to (2685) Counter Top and flush to the outside edges of the outer (5736) Counter Joists attach 1 (5536) Counter Side per joist with 3 (TS) #6 x 30 mm Trim Screws per board. (fig. 27.7)

**H:** Tight to (2685) Counter Top and centred over the middle 2 (5736) Counter Joists with ends flush to the outside edges attach 2 (2716) Counter Mid Tops with 4 (TS) #6 x 30 mm Trim Screws per board. (fig. 27.7)

I: Attach (2685) Counter Top to (2627) SW Wall Panel with 2 (TS) #6 x 30 mm Trim Screws per board. (fig. 27.8)



#### **Wood Parts**

2 x 2716 Counter Mid Top 1 x 4 x 17-5/8"

1 x 2685 Counter Top 1 x 4 x 40-5/8"

2 x 5536 Counter Side 5/8 x 2 x 6-3/4"


#### **Hardware**

20 x (TS) #6 x 30 mm Trim Screw

J: Place Faucet and 2 Sink Knobs in opening of Sink and attach Sink Knobs with included hardware. (fig. 27.9)

Important: Use a hand held screw driver and DO NOT over tighten.

Fig. 27.9




#### **Other Parts**


- 1 x Sink
- 2 x Sink Knobs
- 1 x Faucet

**K:** Place Sink and Stove in the openings of the Counter Assembly then attach 4 Mount Clips with included hardware to the bottom of the Sink and Stove to secure in place. (fig. 27.10 and 27.11)

Important: Use a hand held screw driver and DO NOT over tighten.

Note: To remove the Sink or Stove loosen screw 1/4 turn then twist Mount Clips.





#### **Other Parts**


1 x Stove

8 x Mount Clip

### Step 28: Attach Utensil Shelf

**A:** From inside the assembly, centred in the top of (2768) Panel Floor above the counter attach Utensil Shelf with 2 (S13) #6 x 5/8" Pan Screws as shown in fig. 28.1 and 28.2.

**B:** Attach Pot, Pan and Spatula to the Utensil Shelf. (fig. 28.2 and 28.3)



2 x (S13) #6 x 5/8" Pan Screw

1 x Pot 1 x Pan 1 x Spatula

## Step 29: Slide Section Assemblies Part 1




Note: When installing Pan Bolts make sure to look at holes so bolts go through the side with the round recess and the lock nuts go through the side with the hexagonal recess. (fig. 29.3)

**A:** Fit 2 TNR2 Slide Elbows together and attach with 8 (PB1) 1/4 x 3/4" Pan Bolts (with lock nut) as shown in fig. 29.1. It is very important to attach bolts as indicated.

**B:** Repeat Step A 3 more times to create 4 Elbow Sections in total.

**C:** Attach TNR3 Extend Flange RT and TNR3 Extend Flange LT together using 9 (PB1) 1/4 x 3/4" Pan Bolts (with lock nut) as shown in fig. 29.2. This creates the Flange Assembly.



### Hardware

41 x (PB1) 1/4 x 3/4" Pan Bolt (1/4" lock nut)


#### **Other Parts**

- 1 x TNR3 Extend Flange RT 1 x TNR3 Extend Flange LT
- 8 x TNR2 Slide Elbow

### **Step 29: Slide Section Assemblies** Part 2

Note: When installing Pan Bolts make sure to look at holes so bolts go through the side with the round recess and the lock nuts go through the side with the hexagonal recess. (fig. 29.3)

**D:** Attach TNR2 Slide Exit Top and the remaining TNR2 Slide Elbow together using 8 (PB1) 1/4 x 3/4" Pan Bolts (with lock nut) as shown in fig. 29.4. It is very important to attach bolts as indicated. This creates the Exit Elbow Assembly.



(1/4" lock nut)

### Step 30: Attach Flange Assembly to Fort Part 1






A: With a helper place the Flange Assembly flush to the top opening in the Front Wall on Unit A as shown in fig. 30.1, then pre-drill 1/8" pilot holes in (8935) Lower SL Insert for the 4 bottom mounting locations (approximate spots where circles are on figure), making sure the pre-drilled holes are a minimum of 1" deep. (fig. 30.2)

**B:** Attach Flange Assembly to (8935) Lower SL Insert using 4 (S7) #12 x 2" Pan Screws (with #12 Screw Bezel) in the pre-drilled holes. (fig. 30.2) Make sure the flat surfaces of the Flange Assembly are flush to (2769) Panel BT Frame, (2770) End Post Left and (2602) Upper Jamb as shown in fig. 30.3.

**C**: Attach the Flange Assembly flush to top of (2769) Panel BT Frame using 4 (S6) #12 x 1" Pan Screws (with #12 Screw Bezel) and to (2602) Upper Jamb and (2770) End Post Left using 5 (S6) #12 x 1" Pan Screws per side. (fig. 30.2)



#### **Hardware**

14 x (S6) #12 x 1" Pan Screw

4 x (\$7) #12 x 2" Pan Screw


8 x #12 Screw Bezel

## Step 30: Attach Flange Assembly to Fort Part 2



**D:** Place (8934) SL Gusset tight to (2768) Panel Floor, flush to the top of the bottom opening and attach to Flange Assembly with 2 (S6) #12 x 1" Pan Screws. (fig. 30.4 and 30.5)

**E:** Pre-drill pilot hole with a 3/16" drill bit then attach (8934) SL Gusset to (2768) Panel Floor with 1 (WL5) 1/4 x 2-1/2" Wafer Lag (with flat washer). (fig. 30.4 and 30.5)





### Step 31: Attach Elbow Assembly to Flange Assembly Part 1



Note: When installing Pan Bolts make sure to look at holes so bolts go through the side with the round recess and the lock nuts go through the side with the hexagonal recess. Keep all bolts loose until further step.

**A:** Fit one of the Elbow Assemblies to the Flange Assembly by lining up the arrows on each assembly. (fig. 31.2 and 31.3)

**B:** Attach 1 TNR2 Slide Clamp Ring to the top of the joined Assemblies using 3 (PB1) 1/4 x 3/4" Pan Bolts (with lock nut), making sure to match the arrows up with the end of the clamp ring (where a seam will be) as shown in fig. 31.2 and 31.3.

**Quadrex Driver** Use Quadrex Driver as a guide pin for each hole before inserting bolt. (fig. 31.3) Use special driver provided in locations where the curve of the elbow are difficult to Fig. 31.4 reach with a standard driver. Fig. 31.1 Fig. 31.3 Do not install bolt in Clamp Ring ends until Step 31D Fig. 31.2 Lock Nut Flange Assembly **Top Slide Bolt Holes** Align each elbow using the molded arrows with the seam of the clamp ring. Lock Nut PB1 Elbow Assembly

### Hardware


3 x (PB1) 1/4 x 3/4" Pan Bolt (1/4" lock nut)

#### Other Parts

- 1 x Quadrex Driver
- 1 x TNR2 Slide Clamp Ring

### Step 31: Attach Elbow Assembly to Flange Assembly Part 2





5 x (PB1) 1/4 x 3/4" Pan Bolt (1/4" lock nut)

1 x TNR2 Slide Clamp Ring

### Step 32: Attach Elbow Assembly to Elbow Assembly Part 1





Note: When installing Pan Bolts make sure to look at holes so bolts go through the side with the round recess and the lock nuts go through the side with the hexagonal recess. Keep all bolts loose until further step.

**A:** Fit a second Elbow Assembly to the first Elbow Assembly by lining up the arrows on each assembly. Notice the elbow orientation. (fig. 32.1)

**B:** Attach 1 TNR2 Slide Clamp Ring to the top of the joined Assemblies using 3 (PB1)  $1/4 \times 3/4$ " Pan Bolts (with lock nut), making sure to match the arrows up with the end of the clamp ring (where a seam will be) as shown in fig. 32.2 and 32.3.

Use Quadrex Driver as a guide pin for each hole before inserting bolt.





#### **Hardware**

3 x (PB1) 1/4 x 3/4" Pan Bolt (1/4" lock nut)

**Other Parts** 

1 x TNR2 Slide Clamp Ring


### Step 32: Attach Elbow Assembly to Elbow Assembly Part 2



Note: When installing Pan Bolts make sure to look at holes so bolts go through the side with the round recess and the lock nuts go through the side with the hexagonal recess. Keep all bolts loose until further step.

**C:** Attach 1 TNR2 Slide Clamp Ring to the bottom of the joined Assemblies using 3 (PB1) 1/4 x 3/4" Pan Bolts (with lock nut), making sure to match the arrows up with the end of the clamp ring (where a seam will be) as shown in fig. 32.3 and 32.4.

**D:** Connect the 2 TNR2 Slide Clamp Rings together in 2 spots using 1 (PB1) 1/4 x 3/4" Pan Bolt (with lock nut) per hole. Make sure seams and arrows line up and then tighten all bolts. (fig. 32.3 and 32.5).



**Hardware** 


5 x (PB1) 1/4 x 3/4" Pan Bolt (1/4" lock nut)

Other Parts
1 x TNR2 Slide Clamp Ring

### **Step 33: TNR Brace Assembly**



**A:** Attach (8965) TNR Upright to (8963) TNR Ground Brace with 1 (H8) 1/4 x 4-1/4" Hex Bolt (with lock washer, flat washer and t-nut) in the top hole. Make sure both boards are square then attach with 1 (S11) #8 x 2" Wood Screw. (fig. 33.1)



#### **Wood Parts**

1 x 8963 TNR Ground Brace 1-1/4 x 3 x 32-1/4"

1 x 8965 TNR Upright 1-1/4 x 3 x 20-1/4"

#### **Hardware**

1 x (S11) #8 x 2" Wood Screw

1 x (H8) 1/4 x 4-1/4" Hex Bolt (1/4" lock washer, 1/4" flat washer, 1/4" t-nut)

## Step 34: Attach Elbow Assemblies and TNR2 Slide Support



Note: When installing Pan Bolts make sure to look at holes so bolts go through the side with the round recess and the lock nuts go through the side with the hexagonal recess. Keep all bolts loose until further step.


A: Attach the two remaining Elbow Assemblies as instructed in Steps 31 and 32.

**B:** Place TNR Brace Assembly against (2770) End Post Left so it sits under the slide. It is not attached yet. (fig. 34.1)

**C:** On the fourth Elbow Assembly attached remove the pan bolt and nut which is facing the fort (installed in Step 29). (fig. 34.1) **The bolt will no longer be needed, but keep the lock nut.** 

**D:** Loosely attach TNR3 Tube Support (at the slightly bent end) to the Clamp Ring using 1 (PB6) 1/4 x 1" Pan Bolt (with flat washer and the previously removed lock nut). (fig. 34.2)

**E:** Rotate TNR3 Tube Support and attach to (2770) End Post Left using 1 (S6) #12 x 1" Pan Screw as shown in fig. 34.2.





### **Step 35: Attach TNR Brace Assembly**




**A:** Use (8965) TNR Upright as a guide to judge the proper bolt location, remove the bottom pan bolt and nut. **The bolt will no longer be needed, but keep the lock nut.** (fig. 35.1 and 35.2)

**B:** Attach the top of the TNR3 Post Mount to TNR2 Slide Clamp Ring using 1 (PB2) 1/4 x 1-1/4" Pan Bolt (with the previously removed lock nut and 1 flat washer). (fig. 35.2)

**C:** Insert TNR3 Post Mount on (8965) TNR Upright, pre-drill with a 1/8" drill bit then attach with 2 (S6) #12 x 1" Pan Screws. (fig. 35.2)

**D:** Attach (8963) TNR Ground Brace flush to the bottom of (2770) End Panel Left with 2 (S11) #8 x 2" Wood Screws and 1 (S4) #8 x 3" Wood Screw. (fig. 35.1 and 35.3)



Hardware  1 x (PB2) 1/4 x 1-1/4" Pan Bolt 1 - (1/4" flat washer, 1/4" lock nut - previously removed)	Other Parts 1 x TNR3 Post Mount
2 x (S6) #12 x 1" Pan Screw	
1 x (S4) #8 x 3" Wood Screw	
2 x (S11) #8 x 2" Wood Screw	
00	


### Step 36: Attach TNR2 Slide Exit to Exit Elbow Assembly



A: Insert flange of Exit Elbow Assembly (slide elbow) into the slots on TNR3 Short Exit. (fig. 36.1)

**B:** Rotate Slide Exit and use Quadrex Driver as a guide pin so the holes are aligned and attach with 5 (PB1) 1/4 x 3/4" Pan Bolts (with lock nuts) starting with the bottom middle hole and working up each side. (fig. 36.2 and 36.3)

C: At this point make sure all the slide bolts are tight. Use a 7/16" open end wrench to hold nut and then tighten bolt with Quadrex Driver on Clamp Rings.



**Hardware** 

5 x (PB1) 1/4 x 3/4" Pan Bolt (1/4" lock nut)

Other Parts
1 x TNR3 Short Exit

### Step 37: Attach Exit End Assembly to Fort



Note: When installing Pan Bolts make sure to look at holes so bolts go through the side with the round recess and the lock nuts go through the side with the hexagonal recess. Keep all bolts loose until further step.


A: Fit the Exit End Assembly to the last Elbow Assembly by lining up the arrows on each assembly. Notice the elbow orientation. (fig. 37.1)

**B:** Place 1 TNR2 Slide Clamp Ring to the top of the joined Assemblies, rotate counter clockwise 1 hole location then attach with 3 (PB1) 1/4 x 3/4" Pan Bolts (with lock nut) as shown in fig. 37.1.

Use Quadrex Driver as a guide pin for each hole before inserting bolt.

C: Attach 1 TNR2 Slide Clamp Ring to the bottom of the joined Assemblies using 3 (PB1) 1/4 x 3/4" Pan Bolts (with lock nut) as shown in fig. 37.2.

**D:** Connect the 2 TNR2 Slide Clamp Rings together in 2 spots using 1 (PB1) 1/4 x 3/4" Pan Bolt (with lock nut) per hole. Make sure seams and arrows line up and then tighten all bolts. (fig. 37.3).



After the clamp rings are attached to the

elbows, fasten them end to end with two

Fig. 37.3





Fig. 37.2 **Bottom Slide Bolt Holes** 



**Hardware** 

1/4 x 3/4" Pan Bolt (1/4" lock nut)

**Other Parts** 2 x TNR2 Slide Clamp Ring

### Step 38: Attach Ground Stake to TNR Upright


**A:** In the spot shown in fig. 38.1 drive 1 Rebar Ground Stake 13" into the ground against the (8965) TNR Upright. Be careful not to hit the washer while hammering stake into the ground as this could cause the washer to break off.


**B:** Attach the ground stake to (8965) TNR Upright just below the t-nut using 1 (S7) #12 x 2" Pan Screw as shown in fig. 38.2.

**C:** After driving stakes into the ground, check for sharp edges caused by the impact of the hammer. Smooth any sharp edges from impact area and touch up with outdoor paint.



Warning! To prevent tipping and avoid potential injury, stakes must be driven 13" into ground. Digging or driving stakes can be dangerous if you do not check first for under-ground wiring, cables or gas lines.





<u>Hardware</u> 1 x (s<sup>7</sup>) #12 x 2" Pan Screw Other Parts

1 x Rebar Ground Stake

### **Step 39: Roof Support Assembly**

**A:** Attach 1 (2760) Roof Support to a second (2760) Roof Support at peak using 1 (S4) #8 x 3" Wood Screw. Repeat this step so there are 4 Roof Support Assemblies. (fig. 39.1 and 39.2)





Fig. 39.2



**Wood Parts** 

8 x 2760 Roof Support 1-1/4 x 2-1/4 x 37-1/2"

**Hardware** 


4 x (S4) #8 x 3" Wood Screw

### **Step 40: Roof Panel Assembly**

**A:** Place 1 (2751) MOD Roof Bottom tight to the bottom of (2752) MOD Roof Front and (2753) MOD Roof Back. (fig. 40.1)

**B:** Place a (2761) Roof Sleeper C on the middle strip of each Roof Panel Assembly so the ends are flush and attach with 4 (S20) #8 x 1-3/8" Wood Screws per panel. (fig. 40.2)

C: Repeat A and B to create a second Roof Panel Assembly.



#### **Wood Parts**

4 x 2751 MOD Roof Bottom 1-3/16 x 16-13/16 x 44"

2 x 2752 MOD Roof Front 1-1/4 x 20-7/16 x 44"

2 x 2753 MOD Roof Back 1-1/4 x 20-3/16 x 44"

4 x 2761 Roof Sleeper C 3/4 x 2 x 35"

#### **Hardware**

16 x (S20) #8 x 1-3/8" Wood Screw


## Step 41: Roof Assembly Part 1



#### Complete Step 41, A-D, twice so there are 2 Roof Assemblies

**A:** Place Front Roof Panel against Back Roof Panel so the tops form a peak then tight to the inside edge of the outside slats attach 1 Narrow Angle Bracket per slat with 2 (S0) #8 x 7/8" Truss Screws per bracket. (fig. 41.1 and 41.2)

**B:** Attach the third Narrow Angle Bracket centred on the middle slat with 2 (S0) #8 x 7/8" Truss Screws. (fig. 41.1 and 41.3)




Hardware
12 x so #8 x 7/8" Truss Screw

Other Parts
6 x Narrow Angle Bracket

## Step 41: Roof Assembly Part 2

**C:** Place 1 Roof Support Assembly against one side so the peaks meet and the ends of the roof supports are flush with the ends of the roof panels. Attach with 8 (S11) #8 x 2" Wood Screws. (fig. 41.4)

**D:** Attach the second Roof Support Assembly on the opposite side, peaks to meet and ends are flush with 8 (S11) #8 x 2" Wood Screws. (fig. 41.4)



Hardware

32 x (S11) #8 x 2" Wood Screw


## Step 41: Roof Assembly Part 3






**E:** On the inside of each Roof Assembly on the bottom siding of the (2752) MOD Roof Fronts (6th siding down from top of Roof Assembly), measure 1" from each side of (2761) Roof Sleeper C and pre-drill 2 holes with a 3/16" drill bit as shown in fig. 41.5 and 41.6. This will now be referred to as the front of each Roof Assembly.

**F:** On the outside of each Roof Assembly place 1 (8069) Dormer Cleat over the pre-drilled holes and from inside the assembly attach with 2 (S20) #8 x 1-3/8" Wood Screws per Roof Assembly. (fig. 41.5, 41.7 and 41.8)







### Step 42: Dormer Assembly Part 1

#### Complete Step 42, A-H, twice to create 2 Dormer Assemblies.


**A:** Lay 2 (8070) Dormer Sides flat on the ground so the tops are tight together and form a peak. The side facing up will be the back. (fig. 42.1 and 42.2)

**B:** Tight to the bottom of both (8070) Dormer Sides place (8073) Dormer Bottom so the outside edges are flush. (fig. 42.1 and 42.2)

**C:** On the front of the assembly, centred on top of (8073) Dormer Bottom, place (8074) Dormer Burst. (fig. 42.1 and 42.2)

**D:** Place (8071) Dormer Centre on the back side, flush to the bottom of (8073) Dormer Bottom so the tip is centred at the peak of the (8070) Dormer Sides then attach with 4 (S30) #8 x 1-1/6" Wood Screws. (fig. 42.2)

**E:** Place 1 (8072) Dormer Side Burst tight to each side of (8071) Dormer Centre so they are flush to the bottom of (8073) Dormer Bottom then attach with 2 (S30) #8 x 1-1/6" Wood Screws per board. (fig. 42.2)



#### 


## Step 42: Dormer Assembly Part 2



**F:** Pre-drill with a 1/8" drill bit then attach Dormer Roof Right to Dormer Roof Left, from (8068) Dormer Roof Set at the inside peak with 1 Narrow Angle Bracket using 2 (S5) #8 x 7/8" Truss Screws. (fig. 42.3)

**G:** Place the Dormer Burst Assembly from Step 42, Part 1 on the inside edge of each Dormer Roof and attach with 6 (S30) #8 x 1-1/6" Wood Screws. (fig. 42.3)

**H:** Place 1 completed Dormer Assembly over each (8069) Dormer Cleat and attach with 2 (S3) #8 x 2-1/2" Wood Screws per Roof Assembly. (fig. 42.4)



Wood Parts

2 x 8068 Dormer Roof Set Includes:
1 x Dormer Roof Right
1 x Dormer Roof Left

12 x (\$30) #8 x 1-1/6" Wood Screw 4 x (\$0) #8 x 7/8" Truss Screw


4 x (so) #8 x 7/8" Truss Screw 4 x (so) #8 x 2-1/2" Wood Screw 2 x Narrow Angle Bracket

# **Step 43: Attach Roof Ends Part 1 - Unit A Front Wall**



**A:** On the Front Wall of Unit A remove the 2 outside (H9) 1/4 x 1-1/4" Hex Bolts attached at the top of the assembly from Step 2, Part 2. Leave the T-nuts in. The Flat Washers and Lock Washers will be used in Step B. (fig. 43.1)







Remove these bolts on Unit A Front Wall, keeping lock washers and flat washers for next step. Do not remove the t-nuts.


## Step 43: Attach Roof Ends Part 2 - Unit A Front Wall



**B:** Loosely attach 1 (2759) Roof End to each corner of the End Wall, flush to the top of (2769) Panel BT Frame, with 1 (H3) 1/4 x 2-1/2" Hex Bolt per board, using the (FW1) Flat Washer and (LW1) Lock Washer from Step A and connecting to the (TN1) T-nut. Notice which bolt holes are to be used. (fig. 43.2, 43.3 and 43.4)









# Step 43: Attach Roof Ends Part 3 - Unit A Front Wall



**C:** Measure overhang so it is 4-7/8" then attach (2759) Roof Ends with 2 (S11) #8 x 2" Wood Screws and 1 (S3) #8 x 2-1/2" Wood Screw per side. Tighten the bolts. (fig. 43.5, 43.6 and 43.7)

Fig. 43.5 Top View





#### **Hardware**

2 x (S3) #8 x 2-1/2" Wood Screw


4 x (S11) #8 x 2" Wood Screw


# **Step 43: Attach Roof Ends Part 4 - Unit A Swing Wall**





**D:** Attach 1 (2759) Roof End to each corner of the Swing Wall, flush to the top of (2630) SW Wall and overhanging 4-7/8" then attach with 2 (S11) #8 x 2" Wood Screws and 1 (S3) #8 x 2-1/2" Wood Screw per (2759) Roof End. Notice which holes are to be used. (fig. 43.8, 43.9, and 43.10)







2 x 2759 Roof End 1-1/4 x 3 x 10"

#### **Hardware**

2 x (S3) #8 x 2-1/2" Wood Screw

4 x (S11) #8 x 2" Wood Screw


# **Step 44: Attach Roof Ends Part 1 - Unit B Side and Tunnel Side Walls**



**A:** On the Side and Tunnel Side Walls of Unit B remove the 4 outside (H9) 1/4 x 1-1/4" Hex Bolts attached at the top of the assembly from Step 1, Part 2. Leave the T-nuts in. The Flat Washers and Lock Washers will be used in Step B. (fig. 44.1)

Fig. 44.1


**Unit B** 





## Step 44: Attach Roof Ends Part 2 - Unit B Side and Tunnel Side Walls



**B:** Loosely attach 1 (2759) Roof End to each corner of the Side and Tunnel Side Walls, flush to the top of (2775) Panel Cross Supports, with 1 (H3) 1/4 x 2-1/2" Hex Bolt per board, using the Flat Washer and Lock Washer from Step A and connecting to the T-nut. Notice which bolt holes are to be used. (fig. 44.2, 44.3 and 44.4)









# **Step 44: Attach Roof Ends Part 3 - Unit B Side and Tunnel Side Walls**



**C:** Measure overhang so it is 4-7/8" then attach (2759) Roof Ends with 2 (S11) #8 x 2" Wood Screws and 1 (S3) #8 x 2-1/2" Wood Screw per corner. Tighten the bolts. (fig. 44.5, 44.6 and 44.7)

Fig. 44.5 Top View





#### **Hardware**

4 x (S3) #8 x 2-1/2" Wood Screw

8 x (S11) #8 x 2" Wood Screw

## Step 45: Attach Roof Assembly to Fort Part 1







**A:** With 2 people on the ground and at least 1 person in Unit A, lift 1 Roof Assembly up and over the Swing Wall side of the fort. Guide the Roof Assembly onto the fort so all four (2760) Roof Supports sit flush to the front and outside edges of (2759) Roof Ends. Dormer Assembly faces Unit B. (fig. 45.1 and 45.2)

**B:** Attach (2760) Roof Supports to (2759) Roof Ends with 1 (S3) #8 x 2-1/2" Wood Screw per support. (fig. 45.1 and 45.2)

**C:** Repeat A and B for Unit B lifting it over the Side Wall so the Dormer Assembly faces the Front. (fig. 45.1 and 45.2)





#### **Hardware**

8 x (S3) #8 x 2-1/2" Wood Screw

### Step 45: Attach Roof Assembly to Fort Part 2

#### For Unit A


**D:** Place (9450) Roof Tie so that the angled end is flush against (2761) Roof Sleeper C and the other end is flat against (2775) Panel Cross Support, centered between the Hex Bolts. Attach using 4 (S11) #8 x 2" Wood Screws, making sure that the top 2 screws are installed on an angle as shown in fig. 45.3.

**E:** Repeat Step D to install a (9450) Roof Tie to (2761) Roof Sleeper C and (2769) Panel BT Frame on the opposite side of the roof.

#### For Unit B

**F:** Place (9450) Roof Tie so that the angled end is flush against (2761) Roof Sleeper C and the other end is flat against (2630) SW Top, centered between the Hex Bolts. Attach using 4 (S11) #8 x 2" Wood Screws, making sure that the top 2 screws are installed on an angle as shown in fig. 45.3.

**G:** Repeat Step F to install a (9450) Roof Tie to (2761) Roof Sleeper C and (2769) Panel BT Frame on the opposite side of the roof.



#### **Wood Parts**

4 x 9450 Roof Tie 1-1/4 x 2 x 7-9/16" (31.8 x 50.8 x 192mm)

#### **Hardware**

16 x (S11) #8 x 2" Wood Screw

### Step 46: Sunburst Assemblies




A: From inside Unit A place 1 (9082) MOD Sunburst Bottom against the (2760) Roof Supports on the Roof Assembly opening on the Front Wall. Make sure it sits tight to the Roof Assembly on each side then attach with 2 (S20) #8 x 1-3/8" Wood Screws. (fig. 46.1 and 46.2)


B: Centre (8305) Starburst Centre lengthway on the outside of (9082) MOD Sunburst Bottom then measure 1-1/4" up from the bottom of (9082) Sunburst Bottom and attach (8305) Starburst Centre with 2 (S20) #8 x 1-3/8" Wood Screws. (fig. 46.1 and 46.3)

C: On the inside of the assembly place (9080) MOD Sunburst A tight to the top of (9082) MOD Sunburst Bottom so the tip is centred at the peak of the Roof Assembly then attach to each (2760) Roof Support and (8305) Starburst Centre with 3 (S20) #8 x 1-3/8" Wood Screws. (fig. 46.1 and 46.2)

D: Place 1 (9081) MOD Sunburst B tight to each side of (9080) MOD Sunburst A and tight to the top of (9082) MOD Sunburst Bottom then attach to each (2760) Roof Support and (8305) Starburst Centre with 2 (S20) #8 x 1-3/8" Wood Screws per board. (fig. 46.1 and 46.2)

E: Repeat Steps A - D on Unit B Roof Assembly for the opening on the Side Wall.





#### **Hardware Wood Parts** 4 x 9082 MOD Sunburst Bottom 1 x 4 x 30" #8 x 1-3/8" Wood Screw 4 x 8305 Starburst Centre 5/4 x 6 x 12"

8 x 9081 MOD Sunburst B 1 x 4 x 7-1/4"

4 x 9080 MOD Sunburst A 1 x 4 x 11-1/2"

# Step 47: Attach Steering Wheel Part 1






**A:** On the Swing Wall of Unit B measure 2" in from each slat and 1-1/2" down from the top of (2756) Siding Assembly then pre-drill 2 holes with a 3/16" drill bit. (fig. 47.1, 47.2 and 47.3)

**B:** Centred between the first 2 pre-drilled holes measure 3/4" down and pre-drill a third hole. (fig. 47.1 and 47.2)

**C:** Place (9083) Steering Wheel Block on the inside and flush to the top of (2756) Siding Assembly and covering the pre-drilled holes then attach from the outside through the pre-drilled holes with 3 (S20) #8 x 1-3/8" Wood Screws. (fig. 47.3 and 47.4)




1 x 9083 Steering Wheel Block 1-1/4 x 3 x 19-1/4"


<u>Hardware</u> 3 x (\$20) #8 x 1-3/8" Wood Screw

# **Step 47: Attach Steering Wheel Part 2**



**D:** Place Steering Wheel on the inside of (2756) Siding Assembly then pre-drill with a 1/8" drill bit. Attach Steering Wheel to (2756) Siding Assembly and (9083) Steering Wheel Block with 1 (WL5) 1/4 x 2-1/2" Wafer Lag (with 5/16" flat washer). (fig. 47.5 and 47.6)







Other Parts

1 x Steering Wheel

## **Step 48: Attach Flower Box**

**A:** On the Tunnel Side Wall on Unit A place 1 Flower Box on (2655) Upper Window Insert centred under the window then attach with 2 (S13)  $\#6 \times 5/8$ " Pan Screws. (fig. 48.1 and 48.2)






Hardware
2 x (\$13) #6 x 5/8" Pan Screw

Other Parts

1 x Flower Box

## Step 49: Attach Slides to Fort






112

## Step 50: Attach Belt Swings and Acro Swing

**A:** Using 1 Threaded Quick Link per chain, join 1 Long Swing Chain to each side of the Swing Belt Seat. Make sure to close the Threaded Quick Link tightly using an adjustable wrench. (fig. 50.1 and 50.2).


**B:** Using 1 Threaded Clip per chain, join the Short Swing Chain to the Acro Bar and Acro Handle. Make sure to close the Threaded Clip tightly using an adjustable wrench. (fig. 50.2 and 50.3)

**C:** Attach the other end of the swing chains to the Spring Loaded Quick Links attached to the Heavy Duty Swing Hangers. (fig. 50.1)



2 x Swing Belt Seat 2 x Short Chain 4 x Long Chain 6 x Threaded Quick Link


## **Step 51: Bench Assembly**



**A:** Open the (2658) Folding Bench Assembly. (fig. 51.1, 51.2 and 51.3)

**B:** Make sure assembly is level then secure with 2 (H1)  $1/4 \times 1-1/2$ " Hex Bolts (with lock washer, flat washer and t-nut) per side. (fig. 51.4)

C: Tighten the top screws in all 4 Bench Legs. (fig. 51.4)



**Wood Parts** 

1 x 2658 Folding Bench 2-13/32 x 6-3/4 x 34"

**Hardware** 

4 x (H1) 1/4 x 1-1/2" Hex Bolt (1/4" lock washer, 1/4" flat washer, 1/4" t-nut)

## Final Step: Attach I.D. Plaque

## ATTACH THIS WARNING & I.D. PLAQUE TO THIS LOCATION ON YOUR PLAY **EQUIPMENT!**

This provides warnings concerning safety and important contact information. A Tracking Number is provided to allow you to get critical information or order replacement parts for this specific model.



### CONTINUOUS ADULT SUPERVISION REQUIRED!

### STRANGULATION HAZARDS

Never allow children to play with ropes, clotheslines, pet leashes, cables, chains or cord-like Items when using this playset for to attach these Items to play-set.

Never allow children to wear loose fitting clothing, ponchos, hoods, scares, capes, nexblaces, or items with draw-strings, cords or ties when using this play-set.

Never allow children to wear bike or sport helmets when using

s piay-set.
Failure to prohibit these items increases the risk of serious injury and death to children from entanglement and strangulation.

SERIOUS HEAD INJURY HAZARD

Maintain shock absorbing material under and around play-set
as recommended in the Installation & Operating Instructions.

Installation over concrete, asphalt, dirt, grass, carpet and other
hard surfaces creates a risk of serious injury or death from falls
to the remund. to the ground.

## SURVEILLANCE CONSTANTE D'ADULTES EST REQUIS!

### Risques D'étranglement

Ne jamais laisser les enfants jouer avec des cordes, cordes à linge, laisses pour animaux, des câbles, des chaînes ou ces type articles pendant de l'utilisation de cet portique de jeu ou à l'attaché de ces éléments à la portique de jeu.

l'attaché de ces éléments à la portique de jeu.

Ne jamale lisseze les enfants de porter des veléments amples, des ponchos, des hottes, des foulards, capes, des colliers ou des articles avec cordes attient ou les cordons pendant l'utilisation de cet portique de jeu.

Ne jamals laissez les enfants porter un casque de vélo oude sport quand lis utilisent ce portique de jiue.

Défaut d'interdire ces éléments augmente le risque de blessures graves et de décès des enfants de enchevêtrement et d'étranglement.

### RISQUE DE BI ESSURES GRAVES DU TÂTE

Maintenir le matériau absorbant les chocs sous et autour de la portique de jeu comme recommandé danslesInstructions D'installation.Installation sur béton, de l'asphalte, sol, de l'herbe, tapis et autres surfaces hdure crée un risque de blessure à la tête graves ou la mort causé par tomber à la sol.


THIS PRODUCT IS INTENDED FOR USE BY CHILDREN FROM AGES 3 TO 10; weight limit of 110 lbs. per child. Maximum number of users, Installation & Operating Instructions; other information is available at:


POUR LES ENFANTS DE 3 À 10 ANS D'ÂGE: limite de 110 Livres par enfant. Nombre maximum d' utilisateurs, installation et d'utilisation; d'autres informations sont disponibles sur:

www.KidKraft.com Contact us at: KidKraft Dallas, TX 75244 USA 1-800-933-0771

A: Attach I.D. Plaque KidKraft to a location on your set that is easily seen and read by a supervising adult using 4 (S13) #6 x 5/8" Pan Screws as shown below.

I.D. Plaque - KK





**Hardware** 

4 x (S13) #6 x 5/8" Pan Screw

**Other Parts** 

1 x I.D. Plaque - KidKraft

# KIDKRAFT Consumer Registration Card

First Name	Initial	Last Name				
Street		Apt. No.				
City		State/Province ZIP/Postal Code				
Country		Telephone Number				
E-Mail Address						
Model Name		Model Number (Box Labels)				
Serial Number (on ID Plaque)						
Date Purchased From						
MM/DD/YY						
How would you rate this product for quality?  ☐ Excellent ☐ Very Good ☐ Average ☐ Below Average ☐ Poor						
How would you rate this product for ease of assembly?						
Excellent Very Good Average Below Average Poor						
How would you rate our instructions?						
☐ Excellent ☐ Very Good	☐ Ave	rerage				
How would you rate the quality of packaging?						
☐ Excellent ☐ Very Good	☐ Ave					
Would you recommend the purchase of our products to friends and family?  ☐ Yes ☐ No						
Comments:						



MAIL TO: KidKraft 4630 Olin Road Dallas, TX 75244 United States

Attention: Customer Service

Fill out your registration card online at <a href="https://prdregistration.kidkraft.com/">https://prdregistration.kidkraft.com/</a>

KidKraft would like to say Thank You for your time and feedback.

