

36800

ANTI-SLIP ABRASIVE GRAIN PE WITH ACRYLIC ADHESIVE

DESCRIPTION

Heavy duty product engineered to provide a durable, non-slip surface. This Anti-Slip Tape features a 60 grit silicone carbide on PE backing that offers long-lasting slip resistance with an easy release liner, making it an essential safety solution in various environments, including Construction, OEM and Agricultural worksites, fitness facilities, and many more.

PRODUCT APPLICATIONS

Designed to be applied indoor and outdoor on frequently used surfaces such as floors, steps, pedals, and more. It can also be used to improve safety at work, home, and for recreation.

STANDARD SIZES

- 25MM X 6M
- 50MM X 6M
- 25MM X 18M
- 50MM X 18M

STORAGE & SHELF LIFE

Store new stock behind current stock.
Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 22 months from date of manufacture.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 06/22

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

| | |
|---|---|
| Adhesive | Acrylic |
| Backing | 60 Grit on PE film |
| Total Thickness w/ liner (mil) PSTC-133 | 33.9 (0.861 mm) |
| Peel Adhesion to Steel (oz/in) PSTC-101 | 110 (30 N/25mm) 24 hr dwell; 95 oz/in (26 N/25mm) 15 hr dwell |
| Shear Adhesion to Steel ½" x ½" x 1000g PSTC-107 | 1 hour |
| Service Temperature | -20°F ~ 175°F (-28.8°C ~ 79.4°C) |
| Color | Black |
| Government Compliance | CA Prop 65, ADA, OSHA safety standards, and NFSI for High Traction |

