



**Divoflow<sup>TM/MC</sup> TC 86**

**VS8**

## Low foam chlorinated detergent for hard water

### Description

Divoflow TC 86 cleaner is a low foaming, chlorinated alkaline detergent for CIP and spray washing use in the food, beverage and dairy industries.

### Effective

- Highly efficient in the removal of organic material including food soil, stains and off-flavors
- Low foaming under conditions of high turbulence
- Good hard water control and free rinsing, leaves no hard water films, minimizes acid cleaning cycles in most clean-in-place (CIP) operations

### Cost-Effective

- Free-rinsing, minimizes water usage
- For use in hard water


### Easy-to-Use

- Liquid can be fed and controlled automatically in CIP systems

### Discussion

Divoflow TC86 cleaner contains a blend of caustic alkali, sodium hypochlorite and organic sequestrants/threshold agents. This combination of ingredients provides excellent soil and stain removal properties for use in hard water conditions. It is recommended as a single-stage cleaner for use in a wide range of CIP and spray washing applications. This product is used in brewing and beverage plants for cleaning fillers, sugar/syrup tanks, open vessels, yeast handling and filtration equipment. It can be used in bars and restaurants for beer line cleaning. It is also used in dairies for cleaning milk reception areas and in food processors for general CIP of equipment and drain cleaning.

This product is low foaming and is suitable for use with a variety of CIP and spray washing equipment.



**Divoflow**



**Divoflow<sup>TM/MC</sup> TC 86**

**VS8**

## Low foam chlorinated detergent for hard water

### Use Instructions

Use at concentrations between 1.6–32 mL/L (0.2–4 U.S. fl. oz / U.S. gal) depending on the type and degree of soiling. Always rinse thoroughly after use.

### Technical data

Certification	Acceptable for use in food processing facilities.
Color/Form	Clear light yellow liquid
Scent	Chlorine
Specific Gravity	1.24
% P	0.14
pH (1%)	11.9
pH (neat)	12.9
% Free Alkalinity (as Na <sub>2</sub> O)	8.8
% Total Alkalinity (as Na <sub>2</sub> O)	11.0
% Available Chlorine	3.8

The above data is typical of normal production and should not be taken as specification.

### Safe handling and storage information

Store in original closed containers, away from extreme temperatures. Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet.

### Product compatibility

Divoflow TC86 cleaner, when applied at the recommended concentration and temperature, is suitable for use on the grades of stainless steel commonly found in the processed food industry. It is unsuitable for use on soft metals such as aluminum and galvanized materials. Always rinse surfaces thoroughly after use. In the event of uncertainty it is advisable to evaluate individual materials before any prolonged use.

### Test Kit

Alkaline Test Kit #409879/409790

### Precautionary Statement

Refer to current Safety Data Sheet.