

FROGTAPE® BRAND PAINTER'S TAPE - PRO GRADE

TYPICAL APPLICATIONS

- For interior or exterior use on cured painted walls and trim, glass and metal

PRODUCT FEATURES

- Multi-surface FrogTape® Pro Grade Painter's Tape
- Medium adhesion
- Treated with PaintBlock® Technology that seals tape edges for very sharp paint lines
- 14-day clean removal
- Solvent-free, high performance adhesive bonds quickly to the surface, allowing for painting immediately after application
- *Test before use on all surfaces and when using solvent-based coatings; FrogTape® was designed for use with latex paint

CONSTRUCTION

Backing: Fine structured crepe

Adhesive: Synthetic rubber-based adhesive

STANDARD WIDTHS

0.94 in; 1.41 in; 1.88 in

24 mm; 36 mm; 48 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	32.5 oz/in width	3.56 N/10 mm
Elongation	10%	10%
Service Temperature Range	50 F to 200 F	10 C to 93 C
Tensile	22.5 lbs/in width	39.4 N/10 mm
Thickness	5.08 mils	0.13 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



The mark of responsible forestry
FSC® C154304

*Test before use on all surfaces and when using solvent-based coatings; FrogTape® was designed for use with latex paint