

Slotted Polypro Flush Plug

- With or without threaded brass insert
- Combine with FIP adapters to make your own cleanouts
- Plugs are durable, glass-filled polypropylene:
 - Will not seize or weld in ABS or PVC fittings
 - Acid resistant and chemically inert
 - More durable than traditional ABS or PVC plugs



Available with threaded brass insert for cleanout covers.



878-40


SUPPLY

DRAINAGE

SUPPORT

APPENDIX

White Polypro Item No	Black Polypro Item No	Plug Size	Pkg	Min Qty	Case Qty
PLUGS WITH THREADED BRASS INSERT					
878-15	879-15	1½"	B	25	25
878-20	879-20	2"	B	25	25
878-25	879-25	2½"	B	25	25
878-30	879-30	3"	B	25	25
878-35	879-35	3½"	B	25	25
878-40	879-40	4"	B	25	25
878-50	879-50	5"	B	20	20
878-60	879-60	6"	B	8	8
878-15PK	879-15PK	1½"	C*	25	25
878-20PK	879-20PK	2"	C*	25	25
878-25PK	879-25PK	2½"	C*	25	25
878-30PK	879-30PK	3"	C*	25	25
878-35PK	879-35PK	3½"	C*	25	25
878-40PK	879-40PK	4"	C*	25	25
PLUGS WITHOUT THREADED BRASS INSERT					
878-015	879-015	1½"	B	25	25
878-020	879-020	2"	B	25	25
878-025	879-025	2½"	B	25	25
878-030	879-030	3"	B	25	25
878-035	879-035	3½"	B	25	25
878-040	879-040	4"	B	25	25
878-015PK	879-015PK	1½"	C*	25	25
878-020PK	879-020PK	2"	C*	25	25
878-025PK	879-025PK	2½"	C*	25	25
878-030PK	879-030PK	3"	C*	25	25
878-035PK	879-035PK	3½"	C*	25	25
878-040PK	879-040PK	4"	C*	25	25



flush pipe plug

842-9 series
fitting socket ring

Sch. 40 hub

2" - 4" plugs can be used with our 842-9 series fitting socket rings for an inexpensive threaded access hole cover.