

2024 Specification Sheet - English

**LONG DESCRIPTION –**

Long Description Marketing Copy

A deep rod opening and smooth operation ensures that the driver will not jump off of rods. Light weight allows easy mounting on top of rods. Can be used with Open and Closed-Center hydraulic systems. Dual guide rods provide excellent control for driving rods straight, and the remote on/off valve makes it easy to control the depth of the rod

PRODUCT NAME –

Page Title

Ground Rod Driver 5/8" (16 mm) Opening

PRODUCT OVERVIEW –

Marketing Text 1

A deep rod opening and smooth operation ensures that the driver will not jump off of rods

Marketing Text 2

Light weight allows easy mounting on top of rods

Marketing Text 3

Can be used with Open and Closed-Center hydraulic systems

Marketing Text 4

Dual guide rods provide excellent control for driving rods straight, and the remote on/off valve makes it easy to control the depth of the rod

PRODUCT SPECIFICATION –

Product Specification 1

Accessory : 54923 HTMA Male Coupler, 54924 HTMA Female Coupler

Product Specification 2

Blow Energy : 63.000 FT-LB (85 J)

Product Specification 3

Blow Frequency : 1740/MIN At 8 GPM (30 LPM)

Product Specification 4

Hose Length : 70.000 IN (178.000 CM)

Product Specification 5

Hydraulic Flow Range : 5 - 8 GPM (19 - 30 LPM)

Product Specification 6

Hydraulic System : Open And Closed-Center

Product Specification 7

Jaw Opening : 5/8 IN (16.000 MM)

Product Specification 8

Length : 25-1/2 IN (654.000 MM)

Product Specification 9

Maximum Input Pressure : 2000 PSI (138 BAR)

Product Specification 10

Pressure Port : 9/16 - 18 SAE O-Ring On/Off Valve

Product Specification 11

Replacement Part : 02872 70 IN Hose Assembly, 111952 Remote Valve

Product Specification 12

Return Port : 3/4 - 16 SAE O-Ring On/Off Valve

Product Specification 13

Type : HRD Ground Rod

Product Specification 14

Weight : 45.000 LB (20.500 KG) Power Unit Only, 53.000 LB (24.000 KG) With Hoses And Control Valve