

# NICOR® | select

## Edge Lit Recessed **LED** Downlight **DLE Select**



4" & 6"  
CCT Selectable  
3K 4K 5K

**Simple Installation with a Flip of a Switch**



# DLE Select

## Edge Lit Recessed LED Downlight

### Ultra-Slim CCT Selection

Now part of the NICOR Select line, the DLE Edge Lit Recessed LED Downlight Series offers a clean appearance coupled with simple, housing free installation. Eliminating the need for a J-box or recessed housing, the DLE fixture uses a plenum-rated cable connector to link the downlight module to the remote driver box and then pops into place with its spring loaded retention tabs for a secure fit. The ultra-thin fixture depth and off-board driver allow for a more flexible installation and increased lifetime with improved thermal management. With a micro-switch on the driver housing, the DLE Select offers the ability to adjust the CCT to 3000K, 4000K, or 5000K. Simplify your installations using a single fixture that can be adjusted on the fly with NICOR Select.



**Cast Aluminum Housing**  
Routes heat away from electrical components

**4-Step MacAdams LED**  
Tight LED binning for color consistency

**Selectable CCT**  
CCT Selection is housed on the off-board driver for easy access

**Retention Clips**  
For easy installation, no housing needed



# DLE Select

## Product Information

### Construction

- Cast aluminum housing routes heat away from electrical components
- Edge-Lit technology allows for extremely thin fixture depth
- Adjustable, spring loaded retention tabs ensure secure fixture retention
- Low profile micro-switch on driver housing for CCT selection
- Certified for direct contact with insulation
- Includes gasket to meet AirTight requirements

### Optical System

- Precision engineered optical stack creates uniform light distribution that maximizes lumen output

### Electrical

- Off-board driver minimizes installation height and maximizes fixture life through improved heat management
- Input voltage of 120VAC
- Dimmable to less than 5% with compatible leading edge (TRIAC) and trailing edge (ELV) dimmers
- LM-79 testing performed in accordance with IESNA standards

### Finish

- White powder coat finish standard
- Accessory color trims available in Black, Nickel and Oil-Rubbed Bronze

### Installation

- Spring loaded retention tabs allow for easy installation into ceilings up to 3/4" with no need for a recessed housing
- Off-board driver/junction box includes two 1/2" KOs, two 3/8" KOs and four-port poke-in connectors
- Included paper cutting template
- Accessory metal rough in template available
- Accessory extension power cables (2' & 10') available
- Suitable for wet locations
- Operating temperature of 0° to 120°F (-18°C to 49°C)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

### Warranty


- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)

### Ordering Information



Series	Version	Voltage	CCT	Trim Shape	Trim Color
DLE4	3	120	S (Selectable: 3000, 4000, 5000K)	RD (Round)	WH (White)
DLE6					

*Example: DLE3120SRDWH*

### DLE4



### DLE6



\* Not available on 5000K

Performance Data			
Model Number	Lumens	Watts	Lumens/Watt
DLE43120SRDWH (3000K)	655	10.1	64.9
DLE43120SRDWH (4000K)	727	9.9	73.4
DLE43120SRDWH (5000K)	679	10.0	67.9
DLE63120SRDWH (3000K)	859	13.1	65.6
DLE63120SRDWH (4000K)	949	12.9	73.6
DLE63120SRDWH (5000K)	897	13.1	68.5

## Warehouse Locations

Albuquerque, NM  
Atlanta, GA  
Detroit, MI  
Houston TX  
Indianapolis, IN

Lombard, IL  
Miami, FL  
Syracuse, NY  
Van Nuys, CA

**T 800.821.6283**

F 800.892.8393

[www.nicorlighting.com](http://www.nicorlighting.com)

2200 Midtown Pl. NE  
Albuquerque, NM 87107 USA



LIT-DLE-SELCECT  
20190626

©2019 NICOR® • ALL RIGHTS RESERVED



**NICOR**® | select