

FL50-SERIES

Submersible Effluent Pumps

Liberty Pumps®

A Family and Employee Owned Company

1/2 hp

1-1/2" or 2" Discharge

3/4" Solids handling

Features

- Semi-open impeller permits passage of solids without clogging
- Heavy-duty iron construction
- Stainless steel fasteners
- Stainless steel rotor shaft
- Permanently lubricated upper and lower ball bearings
- Oil-filled hermetically sealed motor with thermal overload protection
- Unitized carbon ceramic shaft seal
- Dual-sized discharge flange: 1-1/2" or 2"
- Quick-connect power cord in 10' standard length (25', 35' and 50' optional lengths available on certain models)



Patent: See
www.libertypumps.com/patents



innovate. evolve.

FL50-Series

Impeller

Semi-open cast iron class 25
3/4" Solids handling

Finish

Powder coat

Maximum Fluid Temperature

104°F, 40°C Continuous duty
140°F, 60°C Intermittent

Motor

Oil-filled, hermetically sealed, and class B
insulation rating

Power Cord Type

SJTW (10', 25') or SJOOW (35', 50')
Quick-connect 10' standard length (25', 35',
or 50' lengths optional)

Motor Housing

Class 25 cast iron

Volute

Class 25 cast iron

Dimensional Data

Weight: FL51M: 61 lbs
Height: 16.4"
Major Width: 11.2" (manual model)

Shaft

Stainless

Fasteners

300 Series stainless steel

Hardware

Stainless

Mechanical Shaft Seal

Carbon ceramic

Bearings


Upper and lower ball bearings

Float Switch [automatic models]

Wide-angle float switch with piggyback plug

Performance Curve

60 Hz 3450 RPM



Models

MODEL	HP	VOLTS	PHASE	AMPS	DISCHARGE	AUTOMATIC	CORD LENGTH IN FEET	WEIGHT IN LBS
FL51A	1/2	115	1	12	1-1/2" or 2"	Yes	10	62
FL51A-2	1/2	115	1	12	1-1/2" or 2"	Yes	25	64
FL51A-3	1/2	115	1	12	1-1/2" or 2"	Yes	35	66
FL51M	1/2	115	1	12	1-1/2" or 2"	No	10	61
FL51M-2	1/2	115	1	12	1-1/2" or 2"	No	25	62
FL51M-3	1/2	115	1	12	1-1/2" or 2"	No	35	63
FL51M-5	1/2	115	1	12	1-1/2" or 2"	No	50	65
FL52A	1/2	208-230	1	6.5	1-1/2" or 2"	Yes	10	62
FL52A-2	1/2	208-230	1	6.5	1-1/2" or 2"	Yes	25	64
FL52A-3	1/2	208-230	1	6.5	1-1/2" or 2"	Yes	35	66
FL52M	1/2	208-230	1	6.5	1-1/2" or 2"	No	10	61
FL52M-2	1/2	208-230	1	6.5	1-1/2" or 2"	No	25	62
FL52M-3	1/2	208-230	1	6.5	1-1/2" or 2"	No	35	63
FL52M-5	1/2	208-230	1	6.5	1-1/2" or 2"	No	50	65

10' Cord standard on above models. 25', 35', and 50' cord lengths available (50' cord not available on automatic models).