

43103/43104

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

- 1.Unscrew the screw(5) use a Phillips screwdriver (not included) and remove the shade(6) from fixture body (4)
- 2.Unscrew the install screws(2) use a Phillips screwdriver (not included) ,and remove the mounting bracket (3)from back plate(1).
- 3.Attach the mounting bracket (3) with box screws (8) to the outlet box (7).
- 4.Fasten the steel rope(9) to the mounting bracket(3), the purpose of the steel rope is to provide the installer a means to support the fixture from the junction box while connecting the electrical wires. This enables the fixture to hang from the junction box and your hands are free to make the wire connections.
- 5.Tie the ground wire (13) from fixture and supply ground wire (11) from outlet box to the ground screw (12) on the mounting bracket (3).
- 6.Connect the white fixture wire (18) from the fixture to the white wire (neutral wire 17) from the supply circuit. Connect the black fixture wire (16) from the fixture to the black wire (live wire 15) from the supply circuit.
- 7.Cover the connections by using provided wire connectors (14). Position wires back inside the outlet box(7).
- 8.Place fixture back plate (1) to the outlet box (7) ,Make sure no wires are pinched or exposed. and secure it into place using the install screws (2).

9. Install the bulbs (not included 19) and make sure they do not exceed the maximum wattage specified on the fixture's wattage rating label.

10.Align the shade (6) onto the fixture body (4), use a Phillips screwdriver (not included) to screw the screws (5) through the holes on the shade(6) into the threaded holes on the fixture body (4).

11.To prevent moisture from entering the outlet box and the fixtures mounting plate causing a short, apply a bead of clear caulk to outline the outside of the fixtures mounting plate where it meets the wall. Leave a small space at the bottom to allow any condensation or moisture to escape.

12.Turn on the power

INSTALLATION IS NOW COMPLETED

