



Stop Slip™/MC

D3.3

Traction Treatment

Traction treatment and no rinse floor cleaner for quarry tile floors. Designed to be applied full strength for traction treatment, which micro-texturizes the tile floor, helping make the floor safer. Use diluted for effective daily cleaning.

Features & Benefits

- Patented technology that micro-textures quarry tile floors, improving the slip resistance of the floor
- Does not shorten the life of the floor during traction treatment
- Deep cleans the floor during traction treatment
- Effective daily cleaner

Applications

- Use on quarry tile, porcelain, glazed ceramic tile and other unglazed ceramic tile floors
- Not for use on wood, cork, floors with finish, marble, terrazzo, linoleum, or aluminum
- Apply full strength for traction treatment, or dilute for daily floor cleaning





Suma[®] Stop Slip^{™/MC} D3.3

Traction Treatment

Use Instructions

- Avoid contamination of food during use or storage. Do not use on food contact surfaces.

Traction Treatment (once per month or to spot treat slippery areas)

- Use floor cones to mark off area to be treated. Wipe up spills and sweep up debris.
- Apply a heavy coat of this product full strength using a clean mop and bucket without a wringer. Evenly spread this product across the floor.
- On quarry tile, allow to stand for 20 minutes and agitate with a deck brush or other agitation tool
- On ceramic and porcelain tile, allow to stand for an additional 20 minutes so that the total contact time is 40 minutes. If the surface starts to dry out, reapply this product to keep floor wet. On glazed tile, Suma[®] Stop Slip^{™/MC} Traction Treatment can dull/discolor tile as it works to improve the floors' slip resistance (when used full strength, always test Suma[®] Stop Slip^{™/MC} Traction Treatment first in an inconspicuous area).
- Mop up solution or squeegee to floor drain. Rinse or damp mop floor with water.
- Dry floor surface using a wrung out mop or squeegee

Daily Cleaning

- Use floor cones to mark off area to be cleaned. Wipe up spills and sweep up debris.
- Dispense or mix proper strength solution of product and warm water in a mop bucket
- Using a clean mop, apply the cleaning solution generously to the floor, overlapping mop strokes. For best results, scrub the floor with a deck brush, especially if the floor has grout and allow the cleaning solution to stand for 10 minutes before rinsing or using squeegee.
- Repeat if necessary on heavily soiled areas. Pick up soil and excess solution with a tightly wrung out mop, wringing it out frequently, or squeegee to floor drain. Rinse or damp mop floor clean.
- Dry mop or squeegee floor dry or allow floor to air dry before reuse. Once dry, remove "Wet Floor" signs.
- **Note:** Floor will be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials.

Technical data	Suma [®] Stop Slip ^{™/MC} D3.3
Certifications	CFIA
Color/Form	Clear orange, liquid
pH	4.75
Scent	Surfactant
Shelf Life	2 Years

Product	Pack size	Dilution	Product code
Suma [®] Stop Slip ^{™/MC} D3.3	4 x 1 gal. / 3.78 L Containers	Ready-to-Use (Monthly Traction Treatment) 1:128 (Daily Cleaning)	904678



Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up-to-date shipping information.