

CP 150



8-DAY PAINTER'S MATE GREEN® PAINT MASKING TAPE

TYPICAL APPLICATIONS

- For use on painted walls, woodwork, glass, metal and vinyl

ADVANTAGES AND BENEFITS

- Professional results
- Delivers crisp paint lines
- 8-day clean removal
- UV resistant

CONSTRUCTION

Overall Grade/Function: 8-day

Backing: Green crepe paper

Adhesive: Rubber-based

COLOR(S)



Green (GRN)



STANDARD WIDTH(S)

6 mm 18 mm 24 mm
36 mm 48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	16 lbs/in width	28 N/10 mm
Adhesion to Stainless Steel	29.3 oz/in width	3.21 N/10 mm
Thickness	5.4 mils	0.14 mm
Elongation	9%	9%
Adhesion to Backing	6.5 oz/in width	0.65 N/10 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Painter's Mate® is a registered trademark of ShurTech Brands, LLC

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-CP-150-03/12/2014