

# CyberPower

## OL10KRT3UHW Smart App Online UPS

Providing mission-critical enterprise applications maximum power protection.

The CyberPower Smart App Online OL10KRT3UHW rack/tower uninterruptible power supply (UPS) with Maintenance Bypass Switch, LCD Control Panel, and sine wave output safeguards mission-critical servers, data center and telecom equipment, VoIP, and networking hardware that require seamless power correction. Maintenance Bypass Switch allows for the UPS power module to be hot-swapped for service or replacement without cutting power to the connected equipment.

Configurable GreenPower UPS™ ECO Mode improves UPS efficiency up to 97% and reduces electrical and cooling costs. Smart Battery Management (SBM) uses a 3 cycle charging mode to improve battery life while reducing heat being generated.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$300,000 Connected Equipment Guarantee.



### TYPICAL APPLICATIONS

- Data Center Servers
- Network and Storage Devices
- Complex Security Systems
- PBX and VoIP Installations

### FEATURES

- 10,000VA / 9,000W
- Double Conversion Topology
- Sine wave output, zero transfer time
- Output: 200-240V UPS with Maintenance Bypass Switch
- Outlets: Hardwire output only
- SNMP options for remote monitoring
- Generator compatibility mode
- Isolated output for clean and consistent power
- PowerPanel® Business Edition Management Software

## SPECIFICATIONS

### GENERAL

UPS Topology	Double Conversion
Energy Saving	Yes - ECO Mode Efficiency >97%

### INPUT

Nominal Input Voltage	200-240Vac
Input Frequency Range	40Hz - 70Hz (auto-sensing)
Plug Type	Hardwire

### OUTPUT

VA	10,000 (10 kVA)
Watts	9,000 (9 kVA)
On Battery Waveform	Sine Wave

### OUTPUT CONT.

On Battery Voltage	200, 208, 220, 230, 240Vac (Configurable) $\pm 2\%$
On Battery Frequency	50/60Hz (Auto-Sensing or Configurable) $\pm 0.25\text{Hz}$
Rated Power Factor	0.9
Harmonic Distortion	THD < 3% at Linear Load, < 5% at Non-linear Load
Crest Factor	3:1
Outlets - Total	1
Outlet Type	Hardwire Terminal Block (1)
Bypass	Internal Bypass (Automatic and Manual), Maintenance Bypass
Transfer Time	0ms
ECO Mode Bypass Voltage Range	$\pm 10\%$ , $\pm 15\%$ (Configurable)

# OL10KRT3UHW Smart App Online UPS



## SPECIFICATIONS CONT.

### BATTERY

Runtime at Half Load (min)	11
Runtime at Full Load (min)	4.3
Battery Type	Sealed Lead-Acid
Battery Size	12V/9Ah
Battery Quantity	20
User Replaceable	Yes
Hot Swappable	Yes
Typical Recharge Time	4 Hours (0-90%)
Smart Battery Management Mode	Yes
Extendable Battery Module	BP240V30ART3U

### SURGE PROTECTION & FILTERING

Surge Suppression	2430 Joules, IEC 61000-4-5 Level 3
-------------------	------------------------------------

### MANAGEMENT & COMMUNICATIONS

LCD Control Panel	Access 44 information status and configuration settings via the Information and Configuration Menus, in addition to an Event Log Menu.
Extendable LCD Control Panel	Yes - Requires a separate DB26 Cable (not included)
HID Compliant USB Port	Yes
EPO Port	Yes
Dry Contacts	Yes
Software	PowerPanel Business Edition
SNMP / HTTP Remote Monitoring	Yes - Optional RMCARD305 or RELAYIO600

### PHYSICAL

Form Factor	Rack / Tower
Power Module, Battery Module, & PDU Module	
Dimensions (WxHxD) (in.)	17.05 x 10.4 x 32.3
Dimensions (WxHxD) (mm.)	433 x 264 x 820
Weight (lbs.)	299.9
Weight (kg.)	104.5
Installed Rack Height	6U

### ENVIRONMENTAL

Operating Temperature	32 °F to 104°F / 0°C to 40 °C
Operating Humidity	0% - 90% non condensing
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-4°F to 113 °F (-20°C to 45 °C)
Storage Relative Humidity	0 - 95% (non-condensing)
Storage Elevation	0 - 50,000 ft (0 - 15,000 m)
Audible noise at 1.5m from surface of unit	55 dBA
Online Thermal Dissipation	2890 BTU/hr

### CERTIFICATIONS

Safety	UL1778, CSA C22.2 NO.107.3-05, FCC DOC Class A
ROHS	ROHS Compliant

### WARRANTY

Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$300,000