

WAC LIGHTING

Cylinder

Outdoor Wall Sconce

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model	Color Temp & CRI	Lumens	Finish
WS-W230301	30 3000K - 90	1085	BK Black BZ Bronze WT White

Example: **WS-W230301-30-WT**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Offered in a curvaceous single and double head configuration, the adjustable Cylinder Indoor/Outdoor Sconces provide strong energy efficient LED spot lighting precisely where you need it. Cleanly finished with no visible hardware, these stylish aluminum cylinders are available in three architectural powder coat finishes.

FEATURES


- Multiple LED array for uniform illumination
- Grooved swivel joint to allow precise and secure aiming
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	50000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box,Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL,Title 24 JA8 Compliant,ADA Wet Location Listed
Construction:	Die-cast aluminum with TIR lens



FINISHES:



LINE DRAWING:

WAC LIGHTING

Cylinder

Outdoor Wall Sconce

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model	Color Temp & CRI	Lumens	Finish
WS-W230302	30 3000K - 90	1085 x 2	BK Black BZ Bronze WT White

Example: **WS-W230302-30-WT**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Offered in a curvaceous single and double head configuration, the adjustable Cylinder Indoor/Outdoor Sconces provide strong energy efficient LED spot lighting precisely where you need it. Cleanly finished with no visible hardware, these stylish aluminum cylinders are available in three architectural powder coat finishes.

FEATURES


- Multiple LED array for uniform illumination
- Grooved swivel joint to allow precise and secure aiming
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	50000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box,Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL,Title 24 JA8 Compliant,ADA Wet Location Listed
Construction:	Die-cast aluminum with TIR lens



FINISHES:



White Bronze Black

LINE DRAWING: