



Duct Tape 3939

The all-around holding, splicing, masking, patching, sealing, and seaming tape



Wider widths provide extra holding power for large, heavy containment sheets.

Physical Properties

Adhesion to steel (ASTM D-3330)	55 oz./in. width (60 N/100mm)
Tensile strength (ASTM D-3759)	25 lbs./in. (438 N/100mm)
Use temperature	Up to 200°F (93°C)
Backing	Polyethylene coated cloth scrim
Adhesive	Natural rubber
Tape thickness (ASTM D-3652)	9.0 mil (0.23mm)
Roll length	54.8m (60 yds.)
Roll widths/color	Silver – 24, 48, 72, 96mm (1, 2, 3, 4 in.)

Note: Data should be considered representative or typical only, and should not be used for specification purposes.

Among the many proven 3M industrial tapes, this duct tape is the heavy duty all-around performer for jobs ranging from containment sealing to masking for sandblast overspray protection.

Features include the following:

- Natural rubber adhesive grips on contact and holds with medium tensile strength to many surfaces
- Waterproof backing resists wear, abrasion, moisture, and weathering

- Tears easily straight across and down without curling
- Tack-free edges
- Surface can be written on
- Meets UL723, HUD, BOCA codes



The only officially licensed Duct Tape by NASCAR

Application Ideas

- Insulation taping and splicing
- Hanging and splicing polyethylene drapes
- Reinforcing, moisture-proofing, patching
- Heavy duty industrial masking
- Holding and seaming carpet padding

Versatility of 3M™ Duct Tape 3939

Markets

General Industrial

Electrical

Construction

MRO (Maintenance and Repair)

Trade Shows and Displays

Aerospace

Automotive

Specialty and Commercial Vehicles

Applications



Write on the surface of 3M™ Duct Tape 3939 with pen or marker to leave a reminder or mark and identify work-in-progress, components, items bundled, and more.



Polyethylene coated cloth with rubber resin adhesive conforms and adheres to seal around insulation and duct work.



To secure carpeting at trade shows, 3M™ Duct Tape 3939 secures the edges to the concrete floor to help prevent curling and tripping.



PRODUCT USE: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

WARRANTY AND LIMITED REMEDY: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

LIMITATION OF LIABILITY: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



**Industrial Business
Industrial Adhesives and Tapes Division**

Building 21-1W-10
900 Bush Avenue
St. Paul, MN 55144-1000
1 800 362 3550
www.3M.com/duct

© 2006, 3M. All rights reserved.
70-0709-5188-7