

PlumBite® Push On 90° **Elbow**

Specifications

• A heat-free method of joining Copper, CPVC, PE-RT or PEX tubing. Fittings can be removed and re-used, using the disassembly tool (sold seperately).

Applications

• Commercial and residential potable and non-potable water applications

Materials

- Body-DZR Brass
- O-Ring- EPDM, Peroxide Cured
- Gripper Ring- Stainless Steel

Job Name Location _____ Engineer _____ Contractor _____ ___ PO#___ Tag_



Dimensions and Product Offering

Part Code	Part Code Bulk	A -Nominal (in.)	B -Nominal (in.)	C -(in.)	C -Tolerance +/- (in.)
C77425LF	C76507LF	1/2	1/2	1.35	0.10
C77426LF	C76508LF	3/4	3/4	1.51	0.08
C77427LF	-	1	1	1.80	0.08
C77428LF	-	1-1/4	1-1/4	2.26	0.08
C77429LF	-	1-1/2	1-1/2	2.58	0.08
C77430LF	-	2	2	2.95	0.08

Performance Specifications

- Maximum Temperature: 180°F
- Maximum Pressure: 200 PSI
- Service: Potable Water
- Exposure to water with elevated levels of inorganic materials (including but not limited to: Cl, Na, Mg, Ca, K), especially in high temperatures and high water velocity areas, could quicken the corrosion process.

Certifications/Listings/Approvals

- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372
- NSF/ANSI 14
- IAPMO listed
- IAPMO certified for use in manufactured joints without access panels
- ASSE 1061



