# CALI bamboo



### The CALI® Difference

The proprietary manufacturing process used to make our Fossilized® bamboo flooring packs 30% more raw material into each plank, making them far denser than traditional hardwood. This also results in scores topping 5000 on the Janka Hardness Scale. That unmatched durability is available in a wide array of style options -- offering rich colors, hand-scraped and distressed surfaces, various lengths and widths, color-coordinated accessories, and both click-lock and tongue-and-groove milling. It's a brand of quality that makes building green the smartest option.

### **Available Colors**



Boardwalk



Vintage Port



Natural



Mocha



Java



**Antique Java** 



**Bourbon Barrel** 



Treehouse



Bordeaux



# **Style Meets Sustainability**

In addition to being beautiful and remarkably strong, bamboo flooring (made from the fastest growing plant on Earth) is a far more eco-friendly alternative to traditional hardwood.

## Safe for the Home

Strict quality control, a commitment to ultra low VOCs, and the use of superior materials, adhesives, and manufacturing techniques produces flooring that is safe for children, pets, and those with allergies and odor sensitivities. All flooring VOC emissions measure lower than the air we breathe, and even as "nondetectable" in several flooring styles.

## **50 Year Guarantee**

This residential warranty covers structural integrity as well as the finish, which is made to last, unlike traditional hardwood flooring which requires expensive refinishing every 10-15 years.

Grain	Fossilized* Strand Bamboo
Construction	Solid Strand Woven Bamboo
Plank Length*	Options ranging from 36" to 72-7/8"
Plank Width*	Options ranging from 3-3/4" to 5-3/8"
Plank Thickness*	Options ranging from 11 to 14mm
Sqft./Box*	Options ranging from 19.91 to 27.01sqft.
Milling*	Click, Tongue-and-Groove
Installation Method**	Floated, Glue-Down, Nail Down
Finish	Aluminum Oxide
Warranty	50 Year Residential / 15 Year Commercial
Indoor Air Quality	CARB 93120 & EPA TSCA Title VI Compliant for Formaldehyde, Prop 65 Compliant. Test Results Available upon Request
Radiant Heat Compatible	Yes (up to 80°F)
LEED Points	EQC4.3   MRc6   MRc7
Fire Rating	0.47 W/cm2 (Class 1)
Certification	FloorScore <sup>*</sup> Certified, FSC <sup>*</sup> Available Upon Request (FSC-C041329)

<sup>\*</sup>Specs may vary between skus. For more information, please consult your Green Building Consultant or visit CaliFloors.com.







<sup>\*\*</sup>Installation method may vary based on milling type.