

PC 567

Shurtape®
TRUE TO YOUR WORK™

SPECIALTY GRADE, OUTDOOR CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- For protecting surfaces when pressure washing and applying stucco

PRODUCT FEATURES

- 14-day UV-resistant
- Conformable to most surfaces
- Removes cleanly
- Made using Polybonded CO-EX Technology®

CONSTRUCTION

Overall Grade/Function: Specialty/outdoor

Backing: Waterproof, UV-resistant polyethylene film with a cloth carrier

Adhesive: Blended rubber

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

Tested in accordance with UL 723; FSI 0/SDI 0

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

STANDARD

METRIC

Tensile Strength	21 lbs/in width	36.8 N/10 mm
Adhesion to Stainless Steel	46 oz/in width	5.03 N/10 mm
Thickness	8 mils	0.20 mm
Elongation	14%	14%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

