

# SAFETY DATA SHEET

# 1. Identification

Product identifier	Fuel Therapy® with Anti-Gel		
Other means of identification			
Product Code	No. 05428 (Item# 1003809)		
Recommended use	Fuel additive		
ecommended restrictions	None known.		
lanufacturer/Importer/Supplier/I	Distributor information		
lanufactured or sold by:			
Company name	CRC Industries, Inc.		
Address	885 Louis Dr.		
	Warminster, PA 18974 US		
Telephone			
General Information	215-674-4300		
Technical Assistance	800-521-3168		
Customer Service	800-272-4620		
24-Hour Emergency	800-424-9300 (US)		
(CHEMTREC)	703-527-3887 (International)		
Website	www.crcindustries.com		
2. Hazard(s) identification			
hysical hazards	Flammable liquids	Category 3	
lealth hazards	Acute toxicity, inhalation	Category 4	
	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 2A	
	Germ cell mutagenicity	Category 2	
	Carcinogenicity	Category 2	
	Specific target organ toxicity, single exposure	Category 3 narcotic effects	
	Specific target organ toxicity, repeated exposure	Category 2	
	Aspiration hazard	Category 1	
invironmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2	
	Hazardous to the aquatic environment, long-term hazard	Category 2	
SHA defined hazards	Not classified.		
abel elements			
	$\land \land \land$		
Signal word	Danger		

Signal word Hazard statement

Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. Suspected of causing genetic defects. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement		
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.	
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire. Collect spillage.	
Storage	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

# 3. Composition/information on ingredients

**Mixtures** 

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrodesulfurized middle		64742-80-9	60 - 70
distillates (petroleum), hydrotreated light		64742-47-8	10 - 20
naphtha (petroleum), hydrotreated heavy		64742-48-9	10 - 20
solvent naphtha (petroleum), heavy arom.		64742-94-5	3 - 5
naphthalene		91-20-3	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
5. Fire-fighting measures	 S

## Suitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

y form explosive mixtures with air. Vapors may travel considerable distance to a source
and flash back. During fire, gases hazardous to health may be formed.
ned breathing apparatus and full protective clothing must be worn in case of fire.
fire and/or explosion do not breathe fumes. Move containers from fire area if you can do risk. Cool containers exposed to heat with water spray and remove container, if no risk .
e liquid and vapor.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent product from entering drains.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

**Conditions for safe storage, including any incompatibilities** Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Keep container tightly closed. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### **Occupational exposure limits**

# US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)	PEL	400 mg/m3	
		100 ppm	
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	PEL	400 mg/m3	
·		100 ppm	
naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	PEL	400 mg/m3	
		100 ppm	

US. OSHA Table Z-1 Limits Components	Туре		Value	
naphthalene (CAS 91-20-3)	PEL		50 mg/m3	
			10 ppm	
solvent naphtha	PEL		400 mg/m3	
(petroleum), heavy arom.				
(CAS 64742-94-5)			100	
			100 ppm	
US. ACGIH Threshold Limit			Malaa	Болла
Components	Туре		Value	Form
distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)	TWA		5 mg/m3	Inhalable fraction.
naphthalene (CAS 91-20-3)	TWA		10 ppm	
solvent naphtha	TWA		200 mg/m3	Non-aerosol.
(petroleum), heavy arom. (CAS 64742-94-5)			200 mg/mo	
US. NIOSH: Pocket Guide to	Chemical Hazards			
Components	Туре		Value	
distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)	TWA		400 mg/m3	
			100 ppm	
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA		100 mg/m3	
naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA		400 mg/m3	
04742-40-3)			100 ppm	
naphthalene (CAS 91-20-3)	STEL		75 mg/m3	
	012E		15 ppm	
	TWA		50 mg/m3	
	IWA		•	
	No biological evenesure limit	to noted for the ingradic	10 ppm	
logical limit values	No biological exposure limit	is noted for the ingredie	ent(S).	
osure guidelines	logianation			
US - California OELs: Skin o	-	Con be abaarbad t	brough the akin	
naphthalene (CAS 91-20 US ACGIH Threshold Limit		Can be absorbed t	nrough the skin.	
naphthalene (CAS 91-20	-3)	Can be absorbed t	hrough the skin.	
solvent naphtha (petroleu 64742-94-5)	im), heavy arom. (CAS	Can be absorbed t	hrough the skin.	
propriate engineering trols	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.			
vidual protection measures, Eye/face protection	such as personal protectiv Wear safety glasses with si			
Skin protection Hand protection	Wear protective gloves suc	h as: Nitrile. Neoprene.	Polyvinyl chloride	e (PVC).
-		-	- ,,	x - /
Other	Wear appropriate chemical resistant clothing.			

Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke.

# 9. Physical and chemical properties

er i nyelear ana enemiea	
Appearance	
Physical state	Liquid.
Form	Liquid.
Color	Dark amber.
Odor	Petroleum.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	315 °F (157.2 °C) estimated
Flash point	140 °F (60 °C) Setaflash
Evaporation rate	Slow.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	plosive limits
Flammability limit - lower (%)	0.6 % estimated
Flammability limit - upper (%)	7.5 % estimated
Vapor pressure	0.7 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.81
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	450 °F (232.2 °C) estimated
Decomposition temperature	Not available.
Percent volatile	97.2 % estimated
Other information	
Pour point	8.6 °F (-13 °C)

# 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Hydrocarbons.

# 11. Toxicological information

Inhalation

## Information on likely routes of exposure

Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact	Causaa akin irritation		
Skin contact	Causes skin irritation.		
Eye contact	Causes serious eye irritation.		
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.		
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.		
Information on toxicological effe	ects		
Acute toxicity	May be fatal if swallowed and	enters airways. Harmful if inhaled.	
Components	Species	Test Results	
distillates (petroleum), hydrodesulf	urized middle (CAS 64742-80-	3)	
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
distillates (petroleum), hydrotreate	d light (CAS 64742-47-8)		
<u>Acute</u>			
Dermal			
LD50	Rat	> 2000 mg/kg	
naphtha (petroleum), hydrotreated	heavy (CAS 64742-48-9)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
naphthalene (CAS 91-20-3)			
<u>Acute</u>			
Oral			
LD50	Rat	490 mg/kg	
solvent naphtha (petroleum), heav	y arom. (CAS 64742-94-5)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory or skin sensitizatior	l		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected	o cause skin sensitization.	
Germ cell mutagenicity	Suspected of causing genetic	defects.	
Carcinogenicity	Suspected of causing cancer		
IARC Monographs. Overall I	Evaluation of Carcinogenicity		
naphthalene (CAS 91-20- OSHA Specifically Regulate	3) <mark>d Substances (29 CFR 1910</mark> .1	2B Possibly carcinogenic to humans. 001-1052)	
Not regulated.			
	gram (NTP) Report on Carcir		
naphthalene (CAS 91-20-	,	Reasonably Anticipated to be a Human Carcinogen.	
Reproductive toxicity		o cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause drowsiness and d	izziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs	s through prolonged or repeated exposure.	
Aspiration hazard		enters airways. If aspirated into lungs during swallowing or vomiting, nia, pulmonary injury or death.	
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.		

12. Ecological informati	on		
Ecotoxicity	Toxic to a	quatic life with long lasting effects.	
Components		Species	Test Results
distillates (petroleum), hydro	desulfurized r	niddle (CAS 64742-80-9)	
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours
distillates (petroleum), hydro	treated light (	CAS 64742-47-8)	
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	1.1 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	3 mg/l, 96 hours
naphtha (petroleum), hydrotr <b>Aquatic</b>	reated heavy	(CAS 64742-48-9)	
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
naphthalene (CAS 91-20-3)			
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	1.6 mg/l, 96 hours
solvent naphtha (petroleum)	, heavy arom.	(CAS 64742-94-5)	
Aquatic			
Acute			
Crustacea	EC50	Daphnia magna	1.1 mg/l, 48 hours
Fish	EC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2 mg/l, 96 hours
	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2 mg/l, 96 hours
Persistence and degradability	No data is	available on the degradability of any ingredien	nts in the mixture.
Bioaccumulative potential			
Partition coefficient n-octa naphthalene	nol / water (I	<b>og Kow)</b> 3.3	
Mobility in soil	No data a	vailable.	
Other adverse effects		adverse environmental effects (e.g. ozone depl endocrine disruption, global warming potential)	
13. Disposal considerat	ions		
Hazardous waste code	Not regula	ited.	
Contaminated packaging		otied containers may retain product residue, fol Empty containers should be taken to an approv	
Disposal instructions	This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.		

14. Transport information	
DOT	
Road	
Not regulated as dangerous go	ods by around
DOT	ou by ground.
-	
Air	
UN number	UN1268
UN proper shipping name	Petroleum distillates, n.o.s. or Petroleum products, n.o.s., Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	144, B1, IB3, T4, TP1, TP29
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242
DOT	
Maritime	
UN number	UN1268
UN proper shipping name	Petroleum distillates, n.o.s. or Petroleum products, n.o.s., Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	
Label(s)	3
Packing group	
	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	144, B1, IB3, T4, TP1, TP29
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1268
UN proper shipping name	Petroleum products, n.o.s., Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	-
ERG Code	3L
	Read safety instructions, SDS and emergency procedures before handling.
Other information	riced carety methodoloho, ebo and emergency procedures before nandining.
	Allowed with restrictions.
Passenger and cargo aircraft	
	Allowed with restrictions.
Cargo aircraft only IMDG	Allowed with restrictions.
	1014000
UN number	UN1268
UN proper shipping name	PETROLEUM DISTILLATES, N.O.S. or PETROLEUM PRODUCTS, N.O.S., Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special processions for user	Read safety instructions, SDS and emergency procedures before handling

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

# 15. Regulatory information

ier regulatory mornati	•		
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.		
TSCA Section 12(b) Export	Notification (40 CFR 707, S	ubpt. D)	
Not regulated.			
SARA 304 Emergency relea	ase notification		
Not regulated. OSHA Specifically Regulate	ed Substances (29 CFR 191	0.1001-1052)	
Not regulated. US EPCRA (SARA Title III) \$		al: Listed subst	tance
naphthalene (CAS 91-20 CERCLA Hazardous Substa			
naphthalene (CAS 91-20 CERCLA Hazardous Substa		Listed.	
naphthalene (CAS 91-20	)-3)	100 LBS	
	ng in the loss of any ingredien 24-8802) and to your Local E		RQ require immediate notification to the Nationa ning Committee.
Other federal regulations			
Clean Air Act (CAA) Section	n 112 Hazardous Air Polluta	nts (HAPs) List	st
Not regulated. Clean Air Act (CAA) Section	n 112(r) Accidental Release	Prevention (40	0 CFR 68.130)
Not regulated.			
Safe Drinking Water Act (SDWA)	Not regulated.		
Food and Drug Administration (FDA)	Not regulated.		
Superfund Amendments and Re	eauthorization Act of 1986 (	SARA)	
Classified hazard categories	Flammable (gases, aeroso Acute toxicity (any route of Skin corrosion or irritation Serious eye damage or eye Germ cell mutagenicity Carcinogenicity Specific target organ toxici Aspiration hazard	exposure)	
SARA 302 Extremely hazar Not listed.	•		
SARA 313 (TRI reporting)			
Chemical name	С	AS number	% by wt.
naphthalene	(	91-20-3	<1
US state regulations			
US. New Jersey Worker and	d Community Right-to-Knov	/ Act	
	ydrodesulfurized middle (CAS drotreated heavy (CAS 64742 )-3)	,	
US. Massachusetts RTK - S			
naphtha (petroleum), hyd	vdrodesulfurized middle (CAS drotreated heavy (CAS 64742		
naphthalene (CAS 91-20 US. Pennsylvania Worker a		owlaw	
•	vdrodesulfurized middle (CAS		
	vdrotreated light (CAS 64742-		
naphthalene (CAS 91-20	)-3)		
US. Rhode Island RTK		04740.00.0	
	ydrodesulfurized middle (CAS drotreated heavy (CAS 64742 )-3)		
Material name: Fuel Therapy® with A	ati Cal		

#### **California Proposition 65**



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 6	5 - CRT: Listed date/Carcinog	enic substance	
benzene (CAS 71-43	3-2)	Listed: February 27, 1987	
ethylbenzene (CAS 1	100-41-4)	Listed: June 11, 2004	
ethylene oxide (CAS	75-21-8)	Listed: July 1, 1987	
naphthalene (CAS 97	1-20-3)	Listed: April 19, 2002	
propylene oxide (CAS 75-56-9)		Listed: October 1, 1988	
California Proposition 6	5 - CRT: Listed date/Developr	nental toxin	
benzene (CAS 71-43		Listed: December 26, 1997	
ethylene oxide (CAS		Listed: August 7, 2009	
methanol (CAS 67-50	,	Listed: March 16, 2012	
toluene (CAS 108-88		Listed: January 1, 1991	
	5 - CRT: Listed date/Female re	eproductive toxin	
ethylene oxide (CAS		Listed: February 27, 1987	
California Proposition 6	5 - CRT: Listed date/Male rep	roductive toxin	
benzene (CAS 71-43		Listed: December 26, 1997	
ethylene oxide (CAS		Listed: August 7, 2009	
US. California. Candidat subd. (a))	te Chemicals List. Safer Cons	umer Products Regulations (Cal. Code Regs, tit. 22, 69502.3,	
	), hydrodesulfurized middle (CA , hydrotreated heavy (CAS 6474 1-20-3)		
Volatile organic compounds (VC	OC) regulations		
EPA			
VOC content (40 CFR 51.100(s))	97.2 %		
Consumer products (40 CFR 59, Subpt. C)	Not regulated		
State			
Consumer products	Not regulated		
VOC content (CA)	97.2 %		
VOC content (OTC)	97.2 %		

#### International Inventories

Country(s) or region	Inventory name On invent	ory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Toxic Chemical Substances (TCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
	and a fair and the second with the increase of a second second second by the second second second second second	( - )

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Revision date Prepared by Version # Further information	02-20-2018 Allison Yoon 03 CRC # 892A/1002876
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc
Revision information	This document has undergone significant changes and should be reviewed in its entirety.