

X343

Bright XGA Projector



Features

- Luminous XGA projection with 3,600 lumens and 22,000:1 contrast ratio
- HDMI, VGA and composite connectivity
- Up to 15,000-hour lamp life
- Vertical keystone for easy positioning
- Integrated 10-watt speaker



Robust I/O and superior performance

Experience luminous XGA images with the 3,600 lumens Optoma X343. Its 22,000:1 contrast ratio, 1.94 – 2.15:1 throw ratio and 1.1x zoom make it ideal for small-to-medium spaces, such as classrooms, offices and training spaces.

Vertical keystone support simplifies placement for easy installation. An integrated 10-watt speaker delivers crisp, room-filling audio that enhances presentations and videos without additional equipment.

Robust input options, including HDMI, VGA and composite enable connectivity to a wide range of devices. A 15,000-hour lamp life enables many years of use with minimal maintenance.



X343



TECHNICAL SPECIFICATIONS

Aspect Ratio	4:3
Audio	10W speaker
Brightness	3,600 lumens
Compatible Aspect Ratio	4:3 (native), 16:9 and auto compatible
Connections	1 x HDMI v1.4a, 1 x VGA, 1 x composite, 1 x audio-in, 1 x USB-A (5v / 1.0 amp), 1 x VGA, 1 x audio, 1 x RS232
Contrast Ratio	22,000:1
Control Unit	RS-232C
Display Technology	Texas Instrument 0.55" XGA DMD
Displayable Colors	1.07 billion
Keystone Correction	± 40° Vertical
Light Source Type	203W
Light Source Life	15,000/12,000/10,000/6,000 (Eco+/Dynamic/Eco/Bright)
Lens Shift	None
Maximum Resolution	UXGA (1600 x 1200)
Native Resolution	XGA (1024 x 768)
Noise Level	27dB
Offset	115% ±5%
On-Screen Display	Complete on-screen menu adjustments in 26 languages
Operating Temperature	Sea Level to 10,000 feet (@73°F); must manually switch to high-altitude mode at 5,000 feet & above
Power Consumption	230W (Bright) / 190W (Eco)

Power Supply	AC input 100-240V, 50-60Hz, auto-switching
Projection Distance	3.9' - 46.9' (without zoom)
Projection Lens	F=2.41~2.53 ; f = 21.85~24 mm
Projection Method	Front, rear, ceiling count, tabletop
Projection Screen Size	27.7" - 304.4"

COMPATIBILITY SPECIFICATIONS

3D Compatibility	Side-by-Side: 1080i50 / 60, 720p50 / 60, Frame-pack: 1080p24, 720p50 / 60, Over-Under: 1080p24, 720p50 / 60
Computer Compatibility	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA resized, VESA, PC and Mac
Horizontal Scan Rate	15.3 - 91.1kHz
RoHS	Compliant
Vertical Scan Rate	50-85 Hz (120Hz for 3D feature projector)
Video Compatibility	SDTV, HDTV

PHYSICAL SPECIFICATIONS

Dimensions (W x H x D)	12.4" x 3.9" x 9.6"
Security	Security bar, Kensington lock, password protection, keypad lock
Weight	6.7 lbs.

Other

What's in the Box?	X343, AC power cable, remote control, batteries, quick start user manual
Accessories Part Numbers	Carrying case: BK-4028Lamp (replacement): BL-FU200DRemote (replacement): BR-3079NUniversal ceiling mount: BM-5001UUniversal Ceiling mount: OCM815WUniversal Ceiling mount: OCM818W-RU
UPC	796435 44 248 4
Warranty Info	1 Year limited parts and labor warranty on the projector, 90 days lamp warranty

*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

† 3D content can be viewed with DLP® Link active shutter glasses when projector is used with a compatible 3D player. Please visit Optoma.com for more information.

Optoma.com

Copyright © 2020 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change.

Published on 10/29/20