

# HP6862C-1.2 (H 6.7) MS

Two-Channel, Single-Ended, Dual-Power Amplifier

HP6862C-1.2 (H 6.7) MS is a two-channel, single-ended, dual-power amplifier. It is designed for use in a variety of applications, including signal processing, data acquisition, and control systems.

The amplifier is characterized by its high gain, wide bandwidth, and low noise. It is also capable of operating in a variety of modes, including single-ended and differential.

The amplifier is available in a variety of packages, including through-hole and surface-mount. It is also available in a variety of quantities, including single units and bulk quantities.

For more information on the HP6862C-1.2 (H 6.7) MS, please contact your local HP representative or visit our website at [www.hp.com](http://www.hp.com).

HP6862C-1.2 (H 6.7) MS is a high-performance amplifier that is designed for use in a variety of applications. It is characterized by its high gain, wide bandwidth, and low noise.

The amplifier is available in a variety of packages, including through-hole and surface-mount. It is also available in a variety of quantities, including single units and bulk quantities.

For more information on the HP6862C-1.2 (H 6.7) MS, please contact your local HP representative or visit our website at [www.hp.com](http://www.hp.com).

HP6862C-1.2 (H 6.7) MS is a high-performance amplifier that is designed for use in a variety of applications. It is characterized by its high gain, wide bandwidth, and low noise.

The amplifier is available in a variety of packages, including through-hole and surface-mount. It is also available in a variety of quantities, including single units and bulk quantities.

For more information on the HP6862C-1.2 (H 6.7) MS, please contact your local HP representative or visit our website at [www.hp.com](http://www.hp.com).

HP6862C-1.2 (H 6.7) MS is a high-performance amplifier that is designed for use in a variety of applications. It is characterized by its high gain, wide bandwidth, and low noise.

The amplifier is available in a variety of packages, including through-hole and surface-mount. It is also available in a variety of quantities, including single units and bulk quantities.

For more information on the HP6862C-1.2 (H 6.7) MS, please contact your local HP representative or visit our website at [www.hp.com](http://www.hp.com).

HP6862C-1.2 (H 6.7) MS is a high-performance amplifier that is designed for use in a variety of applications. It is characterized by its high gain, wide bandwidth, and low noise.

The amplifier is available in a variety of packages, including through-hole and surface-mount. It is also available in a variety of quantities, including single units and bulk quantities.

For more information on the HP6862C-1.2 (H 6.7) MS, please contact your local HP representative or visit our website at [www.hp.com](http://www.hp.com).

HP6862C-1.2 (H 6.7) MS is a high-performance amplifier that is designed for use in a variety of applications. It is characterized by its high gain, wide bandwidth, and low noise.

The amplifier is available in a variety of packages, including through-hole and surface-mount. It is also available in a variety of quantities, including single units and bulk quantities.

For more information on the HP6862C-1.2 (H 6.7) MS, please contact your local HP representative or visit our website at [www.hp.com](http://www.hp.com).

HP6862C-1.2 (H 6.7) MS is a high-performance amplifier that is designed for use in a variety of applications. It is characterized by its high gain, wide bandwidth, and low noise.

The amplifier is available in a variety of packages, including through-hole and surface-mount. It is also available in a variety of quantities, including single units and bulk quantities.

For more information on the HP6862C-1.2 (H 6.7) MS, please contact your local HP representative or visit our website at [www.hp.com](http://www.hp.com).

