

13,000 LB. GVW VEHICLE RAMPS

SIDE OPENINGS

Allow for easy carrying, positioning, and hanging ramps

CONCAVE WHEEL REST

Raised stop end provide added strength and stability

HEAVY DUTY CONSTRUCTION

With slip-resistant rubber feet to resist sliding while loading

17-DEGREE INCLINE

Provide easy loading even for low clearance vehicles

13,000 LB. TOTAL GVW CAPACITY

Strong enough for safe repair and maintenance underneath your vehicle



Item #	Inner	Master	UPC	Packaging
W41013	0	0	039564153334	Color Box

- 13,000 lb. (5909 kg) total gross vehicle weight capacity allows safe performance of repair and maintenance underneath your vehicle
- Concave wheel rest surface and raised stop end provide added strength and stability
- Molded traction treads and gentle 17-degree incline provide easy loading even for low clearance vehicles
- Heavy duty polypropylene construction with slip-resistant rubber feet to resist sliding while loading
- Openings in the side and low end allow for easy carrying, positioning, and hanging ramps in storage
- Specifications: maximum 3,250 lb. (1477 kg) per ramp, 6,500 lb. (3955 kg) per pair working load capacity, dimensions: 35-5/8 x 12-1/8 x 8-1/4 in. (90.5 x 30.8 x 21 cm); 6-1/4 in. (15.9 cm) maximum lift height

