



# Discharge<sup>®</sup>

## Static Dissipative Floor Finish

Floor finish formulated to help control electrostatic discharge while keeping floors looking good.

### Features & Benefits

- Prevents build up of electrostatic charges on floor by establishing the static dissipative path
- Dissipates a 500 volt charge to zero in less than 0.01 seconds at 30% RH
- Meets ASTM D-2047 slip resistance requirements
- Solids content 16%

### Applications

- Designed for use as a static dissipative finish. Use with Ground Out<sup>®</sup> Cleaner to enhance static dissipation
- Rich high gloss formula resists black heel marks





# Discharge®

## Static Dissipative Floor Finish

### Use Instructions

- Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- Before the first application of product, remove all old finish with any Diversey stripper
- Apply 3 coats of product with a clean finish mop. Before applying the second and third coats, be sure finish is completely dry to the touch, particularly in corners and areas with poor air movement. Finish dries significantly slower in humid conditions. After the last coat is completely dry, allow at least 60 minutes before traffic.

### Maintenance

- Allow new finish to cure for 72 hours before any wet maintenance. Dry mop daily with an untreated dust mop. Clean with Diversey Ground Out® Cleaner in an autoscrubber with a red pad or with a clean damp mop 1–3 times per week, as needed. Dilute Ground Out® Cleaner accurately to maximize static dissipative performance. Avoid over-wetting the floor finish.
- To remove marks and restore shine, first clean the floor using Ground Out® Cleaner then dry buff using white pad. This will ensure that the static dissipative property of the Discharge® Finish will remain.

### Recoating

- Recoat periodically to maximize appearance and static dissipative performance
- Clean thoroughly. Dry mop. Machine scrub with a floor machine or autoscrubber using a red pad and Diversey Ground Out® Cleaner.
- Apply 1–2 coats of product

### For Best Results

- Do not dilute
- Do not use on surfaces colder than 50° F (10° C) @ 15% RH
- To avoid contamination, do not return unused product to original container

**Note:** Floors will be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials. Not intended for outdoor use. Meets ASTM D-2047 requirement for slip resistance.

Technical data	Discharge® Static Dissipative Floor Finish
Color/Form	Milky Off-White, Liquid
pH	8.25
Scent	Ammonia
Shelf Life	2 Years

Product	Pack size	Dilution	Product code
Discharge® Static Dissipative Floor Finish	4 x 1 gal. / 3.78 L Containers	Ready-to-use	4008110



### Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at [www.diversey.com](http://www.diversey.com) or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up-to-date shipping information.