

FEATURES & SPECIFICATIONS

INTENDED USE

For use with housings L3 and L3R.

CONSTRUCTION

Antique bronze, oil-rubbed bronze, brushed nickel, white and black finishes are one piece aluminum open reflectors with integral flange.

INSTALLATION

Socket to trim interface.

Retaining clips pull and snap onto top of reflector to hold trim inside housing.

LISTINGS

U.L. Listed to U.S. and Canadian safety standards.

Damp location listed.

Pull on clip Patent # (U.S.) 5707143, (Canada) 2193902.

WARRANTY

1-year limited warranty. Complete warranty terms located at www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Specifications subject to change without notice.



Notes

Туре


3" Finishing Trim

3**B**1

BAFFLE SHALLOW Narrow Flange

Specifications

Height: 4-3/4 (12.1) Lamp opening: 3-1/2 (8.9) Diameter: 4-7/8 (12.4)



All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION For shortest lead times, configure product using bolded options.					
381					
Series	Finish				
381	(blank) TRMW W MW BN BZA ORB	Black baffle, white flange Black baffle, matte white flange White baffle Matte white baffle Brushed nickel baffle Antique bronze baffle Oil-rubbed bronze baffle			

Housing Compatibility: Housing and trim ordered separately.						
Application	Source	Maximum wattage	Housing			
		35 PAR20				
IC	Incandescent	50 PAR20 ¹	L3, L3R			
		50 R201				
Non-IC	Incandescent	50 PAR20	L3, L3R			

Notes

1 White baffle (3B1W) only.

