

**HOLDRITE**

14284 Danielson Street Poway  
CA 92064

**Phone:** 800-321-0316

**Email:** sales@holdrite.com

**Website:** www.holdrite.com

## Item # 280, Sound rated variable closure clamp, supports up to 2" IPS pipe sizes (Mounts to Stout and EZ-Strut)

Sound rated variable closure clamp that may be installed to HOLDRITE® EZ-Strut™ or Stout Brackets™ with only one to three screws (for maximum load in suspension mode). Two acoustical inserts isolate the pipe from the supporting structure, reducing waterline noise and vibration, while allowing normal pipe expansion and contraction. Variable closure clamp supports 1" - 2" CTS and IPS pipe sizes. Supports Copper, PEX, CPVC tubing, conduit, etc. Frame complies with UL94V-2 flame rating.



### Specifications | Features

#### Specifications

<b>Top &amp; Bottom Clamp Material</b>	Nylon, medium blue
<b>Pads Material</b>	TPR, natural (off-white), 50 shore A
<b>Industry Standards/Certifications</b>	FR UL94V-2
<b>Load Rating (Suspended Mode)</b>	75 lb
<b>Load Rating (Top Mount)</b>	300 lb

**Operating Temperature [Min]** -10 °F

**Operating Temperature [Max]** 180 °F

## Features

Patent pending  
UPC / IPC / IAPMO listed