



Pro Strip™ SC

High Efficiency Floor Stripper

Pro Strip™ SC High Efficiency Floor Stripper is a highly concentrated low odor floor stripper formulated to meet Green Seal® requirements.

Features & Benefits

- Powerful, fast-acting, low foam formula quickly bites through layers of finish as soon as it is applied
- Delivers fast, consistent removal of floor finish
- Green Seal® Certification
- Suitable for facilities where odor is a concern
- Not formulated with butyl or ammonia

Applications

- Designed for floor finish removal on VCT, terrazzo and concrete flooring
- Can be used on tile and grout. Not intended for use on wood, linoleum, rubber, marble, painted surfaces or on surface colored and acid dyed concrete floors as this product may harm these surfaces
- Test for softening or color bleeding on asphalt floors before using






Pro Strip™ SC

High Efficiency Floor Stripper



Use Instructions

- Blockade areas to be stripped. Floors will become very slippery when stripper is applied. Exercise caution.
- Gloves, goggles and protective footwear recommended when using this product.
- Dispense stripper solution from dispenser using cold water at 1:20 into appropriate container.
- Apply liberal amounts of stripper solution uniformly to floor with mop. Start at edges to provide more soak time. If splashing occurs, wipe off surfaces with a clean, damp rag.
- Let stripper solution soak 10-15 minutes. Mop agitate to loosen finish. Re-wet as necessary – do not allow solution to dry on floor. Longer soak times may be necessary in cases of extreme buildup.
- Hand or machine scrub thoroughly using appropriate stripper pads or stripping brush. Pick up all solution with a clean mop, wet vac, or automatic scrubber. Mop up any 'tracks' left by wet vacs or scrubbers before they dry.
- Thoroughly rinse floor with clean water, using a mop and bucket. Let floor dry completely before applying a Diversey Green Seal-Certified finish or other recommended Diversey brand floor finish or sealer.

For RTD:

- Dispense stripper solution from dispenser using cold water at 1:13  for heavy duty stripping (14+ coats) or 1:20  for light/medium duty stripping (4-13 coats) into appropriate container.

Technical data	Pro Strip™ SC High Efficiency Floor Stripper
Certifications	Green Seal®
Color/Form	Clear Light Amber Orange, liquid
pH	12.25
Scent	Solvent
Shelf Life	2 Years

Product	Pack size	Dilution	Product code
Pro Strip™ SC High Efficiency Floor Stripper	2 x 2.5 L / 84.5 oz. J-Fill® Bottles	1:20	95547355* 
Pro Strip™ SC High Efficiency Floor Stripper	1 x 5 L / 1.32 gal. RTD® Unit	1:13, 1:20	95547312* 

* Green Seal GS-40 Certified

Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate.

*This product meets Green Seal® Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org. Green Seal® Certified mark is a registered certification mark owned by Green Seal, Inc.

www.diversey.com

© 2022 Diversey, Inc. All Rights Reserved. PSS30354 (22/181)