



Spray Adhesives for Convenient Maintenance and Repair

MRO
Essentials



*At the touch of a finger – bonding power
for fiberglass insulation, laminate, labels, fabric, and more*

3M aerosol adhesives go to the job and give maintenance professionals a fistful of real power for bonding many surfaces.

With **3M™ Super 77 Multipurpose Spray Adhesive**, fast tack bonds many lightweight materials including insulation (above), plastics, foils, papers, foams, fabric, light gauge metal, and cardboard.

3M™ Hi-Strength 90 Spray Adhesive targets a neat 1-3" track of contact adhesive that typically bonds decorative laminate in 60 seconds (right). Many bulk contact adhesives take 15-20 minutes.

And 3M aerosol adhesives contain no methylene chloride, 1, 1, 1-trichloroethane, or chlorofluorocarbons.



3M™ Spray Adhesives

Product	UPC # 00021200-	Size	Features	Spray Width	Bonding Range Surfaces One/Both	Coverage Sq. Ft./ Container* (Typical)	Packaging
Super 77 Multipurpose Adhesive	21210-9	24 fl. oz.	Fast tack for bonding many lightweight materials.	4" fan	15 min./30 min.	220	12 per case
Hi-Strength 90 Spray Adhesive	30023-3	24 fl. oz.	High contact bond strength for decorative laminate.	1-3"	N/R /15 min.	100	12 per case

Note: The technical information and data above should be considered representative or typical only, and should not be used for specification purposes.

*Coverage based on 24 fl. oz. can size at 0.5 grams/sq. ft. of dry adhesive.



3M™ Super 77 Multipurpose Spray Adhesive –Low misting gives you more useable adhesive for your money on applications ranging from equipment labeling to reattaching office partition fabric. Long bonding range lets you reposition for at least 15 minutes. Low soak-in provides a secure, long-lasting bond.



3M™ Hi-Strength 90 Spray Adhesive –Adheres polyethylene, polypropylene, and other decorative laminate to wood, metal, and more in one minute. Select a spray pattern from 1-3" for targeted application such as edge banding. Strength increases to an ultimate 230 psi in shear and 25 piw in peel for reliable bond performance.

MRO Essentials – You could browse through the thousands of products at 3M to find time and work saving solutions for MRO tasks and problems. Or you could make one call to **1-800-362-3550** or go to the one site that focuses specifically on your needs. From abrasives to adhesives, masking tape to ear plugs, cushion matting to cleaning products, simply click...

www.3M.com/mro

Product Use: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Business

Customer Response Center
900 Bush Avenue, Building 21-1W-10
St. Paul, MN 55144-1000



Minimum 10% Post-Consumable Fiber

3M is a trademark of 3M

Printed in U.S.A.
© 3M 2004 78-6901-2107-0