

# VOLCORE"

PROTECT YOURSELF.
PROTECT YOUR HARNESS.



Diagram A

**Cotton/Poly Blend** 

When a \$300+ harness burns because of welding slag, personal safety becomes an issue.

The Radwear® VOLCORETM

AR-FR Rated Vest

can be your first
line of defense.

Diagrams A and B show the difference in flame resistance. The AR-FR Rated vest reduces the odds of charing and burned pinholes to your inner layer or harness.

Protecting yourself is a priority.

Protecting your equipment is essential to jobsite safety.

7

Diagram B

AF-FR Rated Vest



### *HEADQUARTERS*

5305 Distriplex Farms Drive Memphis, Tennessee 38141 Toll Free: 877-723-4267 Phone: 901-388-7776 / Fax: 901-266-2558









# ILCORE

**CUSTOM MADE IN USA VEST READY IN TWO WEEKS\*** 

\*up to 300 pieces



FR COTTON • TYPE O / CLASS 1 - OFF ROAD • ANSI/ISEA 107-2015 • MADE IN USA





## CSVW-01Z4

### **Features:**

- Yellow Two Tone ANSI Rated FR Contrast Trim
- Westex Indura® 7oz. FR 100% Cotton
- NFPA 2112 Rated FR Cotton
- **ASTM F1506**
- 70e AR PPE Cat 2 (HRC 2)
- ATPV: 8.0
- One Inside Chest Pocket
- One Inside Lower Pocket
- D-Ring Pass trough
- 3M® Laminated Reflective Tape
- **Heavy Zipper Closure**
- Sizes: M-5X

**Applications:** 





- Struck by Vehicle Hazards not near Public Right of Way with traffic speeds below "roadway" speed.
- FR Hazards; Arc Flash, Flash Fire
- Welding with or without Fall Protection
- Role/Responsibility Indication
- **Extremely Dirty Environment**







