

FEATURES & SPECIFICATIONS

INTENDED USE — To provide protection from vandalism for the ELMLT, ELM and ELM2 (ELA VS), and large QUANTUM® products (ELA VS2).

CONSTRUCTION — 1/8" thick (ELA VS2) or 3/16" thick (ELA VS), high-impact, transparent polycarbonate. Fits all QUANTUM ELMLT, ELM and ELM2 (ELA VS), and larger QUANTUM units (ELA VS2).


Contemporary rounded-corner design.

INSTALLATION — Twelve 3/6" diameter pre-drilled mounting holes.


Vandal-resistant hardware not provided.

Note: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

Catalog Number
Notes
Type



ELA VS2



ELA VS

Unit Accessories

ELA VS ELA VS2

VANDAL-RESISTANT SHIELD

Specifications

	ELA VS2	ELA VS
Length:	22"	15"
Depth:	9-3/4"	9 3/4"
Height:	10"	4-3/4"
Shipping Weight:	4.15lbs (1.88kgs)	1.90lbs (0.86kgs)

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: ELA VS

Series	
ELA VS	Vandal shield for ELMLT, ELM and ELM2 unit equipment
ELA VS2	Vandal shield for large Quantum products (ELM618, ELM627, ELM654, ELM1254 and ELM1272) ¹

Notes

¹ ELA VS2 can be used with discontinued 6ELM2P, ELM4 and ELM10.