



# CSP706TG TIER 1 ADVANCED POWER STRIP

Safeguard your equipment from damaging power transients and help lower your electric bill

The Professional Surge Protector CSP706TG from CyberPower offers vital surge suppression for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges and is ideal for safeguarding personal computers, phones/faxes/modems, and consumer electronics. The CSP706TG provides 2,250 joules of protection and seven surge-protected outlets (four energy-saving and one widely-spaced for transformer plugs). Data line protection occurs with RJ11 ports for telecommunication devices (phones, faxes, modems, and DSL lines).

Features of the CSP706TG include automatic shutdown, data line protection, a power cord (6 ft.), a right-angle plug with 45° offset, LED indicators, impact-resistant casing, keyhole mounting slots, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. The CSP706TG comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

## TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

## FEATURES

- Surge suppression: 2,250 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 7 NEMA 5-15R (surge-protected)
- Energy-saving outlets: 3
- Transformer outlet: 1
- Power cord: 6 ft.
- LED indicators: Yes
- Data line protection: Telephone, DSL, Fax
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$175,000



## SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset
OUTPUT	
Outlet Type	7 - NEMA 5-15R
Outlets - Energy-saving	3
Outlets - Total	7
Outlets - Widely-spaced	1

SURGE PROTECTION & FILTERING	
Attenuation	43 dB
Clamping Voltage	400V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	105,000 A
Maximum Surge Current H-G	30,000 A
Maximum Surge Current H-N	45,000 A
Maximum Surge Current N-G	30,000 A
Maximum Surge Voltage	6,000 V
Phone Protection RJ11	1-In / 2-Out
Response Time	<1 Nanosecond
Surge Suppression (Joules)	2,250 J

# CSP706TG

## TIER 1 ADVANCED POWER STRIP

### SPECIFICATIONS CONT.

PHYSICAL	
Color	Black
Cord Management	Yes
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
Safety Covers	Yes

  

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	7.01 x 3.4 x 30.71 cm
Physical Dimensions - Width/Height/Depth (mm)	70 x 34 x 307 mm
Physical Dimensions - Width/Height/Depth (in.)	2.76 x 1.34 x 12.09 in.
Weight (kg)	0.57 kg
Weight (lb)	1.26 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	5.77 x 37.47 x 11.28 cm
Shipping Dimensions - Width/Height/Depth (mm)	57.66 x 374.65 x 112.78 mm
Shipping Dimensions - Width/Height/Depth (in.)	2.27 x 14.75 x 4.44 in.
Weight (kg)	0.77 kg
Weight (lb)	1.70 lbs.

  

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363

  

WARRANTY	
CEG Amount	\$175,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime Warranty