

## DS-2CD2563G0-IS

### 6 MP Outdoor IR Fixed Mini Network Dome Camera



- 1/2.9" (6 MP) Progressive Scan CMOS
- 3072 x 2048 Resolution @ 30 fps
- 2.8 mm and 4 mm Fixed Lens Options
- EXIR 2.0 Range Up to 35 ft (10 m)
- H.265+, H.265, H.264+, H.264
- 120dB True WDR
- MicroSD Card Slot Supports 128 GB
- IP66, IK08 Protection
- 12 VDC and PoE (802.3af)

The Hikvision DS-2CD2563G0-IS Outdoor IR Fixed Mini Network Dome Camera provides high definition network output. It supports H.265+ video compression, which assures savings in bandwidth and storage.

The camera is equipped with 2.8 mm and 4 mm fixed lens options, and offers an EXIR 2.0 range of up to 35 ft (10 m).

Smart features, such as line crossing and intrusion detection are supported.


**Available models:**  
DS-2CD2563G0-IS










# Specifications

<b>DS-2CD2563G0-IS</b>	
<b>Camera</b>	
Image Sensor	1/2.9" Progressive Scan CMOS
Minimum Illumination	Color: 0.028 lux @ (f/2.0, AGC on), 0 lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Slow Shutter	Yes
Day/Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	120dB
Angle Adjustment	Pan: -30° to 30°, tilt: 0° to 75°, rotate: 0° to 360°
<b>Lens</b>	
Focal Length	2.8 mm and 4 mm lens options
Aperture	f/2.0
Focus	Manual
FOV	2.8 mm, horizontal field of view: 97°, vertical field of view: 67°, diagonal field of view: 121° 4 mm, horizontal field of view: 78°, vertical field of view: 53°, diagonal field of view: 98°
Lens Mount	M12
<b>IR</b>	
IR Range	Up to 35 ft (10 m)
Wavelength	850 nm
<b>Compression Standard</b>	
Video Compression	Main stream: H.265+/H.265/H.264+/H.264, sub-stream: H.265+/H.265/H.264+/H.264/MJPEG6, third stream: H.265+/H.265/H.264+/H.264
H.264 Type	Main profile/high profile
H.264+	Main stream supported
H.265 Type	Main profile
H.265+	Main stream supported
Video Bit Rate	32 Kbps to 16 Mbps
Audio Compression	G722.1/G711Lulaw/G711alaw/G726/MP2L2/PCM
Audio Bit Rate	64 kbps [G.711]/16 kbps [G.722.1]/16 kbps [G.726]/32 to 192 kbps [MP2L2]
<b>Smart Features</b>	
Behavior Analysis	Line crossing detection, intrusion detection
Exception Detection	Yes
Region of Interest	One fixed region for main stream and sub-stream
<b>Image</b>	
Maximum Resolution	3072 x 2048
Main Stream	20 fps (3072 x 2048, 3072 x 1728, 2944 x 1656), 30 fps (2560 x 1440, 1920 x 1080, 1280 x 720)
Sub Stream	30 fps (640 x 480, 640 x 360, 320 x 240)
Third Stream	30 fps (1280 x 720, 640 x 360, 352 x 240)
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness, AGC, and white balance are adjustable by client software or web browser
Image Enhancement	BLC/3D DNR/HLC
Day/Night Switching	Day/night/auto/schedule/triggered by alarm in
<b>Network</b>	
Network Storage	MicroSD/SDHC/SDXC card (128 GB), local storage and NAS (NFS,SMB/CIFS), ANR
Alarm Trigger	Motion detection, video tampering, network disconnected, IP address conflict, HDD full, HDD error, PIR, illegal login
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, QoS, IPv6
General Function	One-key reset, anti-flicker, 5 streams and up to 5 custom streams, heartbeat, password protection, privacy mask, watermark, and IP address filtering
API	ONVIF (PROFILE S, PROFILE G), ISAPI
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users. 3 user levels: administrator, operator and user
Client	iVMS-4200, Hik-Connect, iVMS-4500
Web Browser	Plug-in required live view: IE 8+, Chrome 41.0 to 44, Firefox 30.0 to 51, Safari 8.0 to 11 Plug-in free live view: Chrome 45.0+, Firefox 52.0+
<b>Interface</b>	
Audio	2 inputs: line in, or microphone in (built-in microphone), 1 output: line out, mono sound, terminal block
Alarm	1 input: alarm in, 1 output: alarm out (maximum 12 VDC, 30 mA), terminal block
Communication Interface	1-port RJ45 10M/100M self-adaptive Ethernet port
On-Board Storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
SVC	H.264 and H.265 encoding
Reset Button	Yes
<b>Audio</b>	
Environment Noise Filtering	Yes
Audio Sampling Rate	16 kHz/32 kHz/44.1 kHz/48 kHz
<b>General</b>	
Operating Conditions	-22° F to 140° F (-30° C to 60° C); humidity of 95% or less (non-condensing)
Power Supply	12 VDC ± 25%, PoE (802.3af, class 3)
Power Consumption and Current	12 VDC, 0.7 A, maximum 8.5 W, Ø 5.5 mm coaxial plug power, PoE (802.3af, 36 V to 57 V), 0.3 A to 0.1 A, maximum 10 W
Protection Level	IK08, IP66
Material	Front cover: plastic, bottom base: metal
Dimensions	Ø 4.3" x 2.2" (Ø 110 mm x 56.4 mm)
Weight	0.90 lbs (400 g)

## Dimensions



## Accessories

						
<b>WMS</b> Wall Mount with Junction Box	<b>PC120</b> Pendant Cap	<b>CPM</b> Ceiling Pendant Mount	<b>CM</b> Corner Mount	<b>PM</b> Pole Mount	<b>GP120</b> Gang Plate	<b>CBD-MINI</b> Conduit Base