

# 240101-TBK

## INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

### CAUTION

**WARNING:** Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

### GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

### ASSEMBLY AND INSTALLATION

#### 1. Mounting the Hardware

---Thread the fixture screw(1) into the provided holes of the mounting bracket(2).

---Thread the hex nuts(3) onto the fixture screws(1).

---Secure the mounting bracket (2) to the outlet box with the Mounting screws (4).

#### 2. Pull out the wires and ground wire from the Outlet Box.

Make wire connections with Wire nut(5):

---White wire from light to White Wire from power source.

---Black wire from light to Black Wire from power source.

---Attach the Ground Wire to Mounting bracket with a Ground Screw.

Connect Ground Wire from light to Ground Wire from power source.

3. Place the back plate(6) fo the fixture body onto the fixture screws(1).

Secure the back plate(6) into place by using rubber and decorative screw (7) .

4. Install bulbs (8) (bulbs not included, MAX 60W).

5. Place the glass (9) on the cup (10) and place the top cover (11) on the glass. Secure top cover(11) by using cage screws(12).

6. Use silicone adhesive caulking (not included) to seal the gap between the wall plate and the mounting surface to prevent water seepage into the j-box.

