



High Noon®

Urethane Fortified UHS Floor Finish

High Noon® Urethane Fortified UHS Floor Finish is a high solids UHS finish for floors that demand excellent gloss and durability.

Features & Benefits

- Ultra-durable UHS finish allows for reduced labor costs by extending recoat and strip-out cycles
- Built with tough all-acrylic polymers and fortified with urethane for unmatched durability
- Burnishes to a rich deep gloss
- Solids Content 20%
- Meets ASTM D-2047 slip resistance requirements

Applications

- Intended for use on resilient and hard surface floors where burnishing is applicable
- A sealer may be required for highly polished stone surfaces to get adhesion
- Not intended for use on rubber, cork, wood, or bamboo flooring





Use Instructions

Preparation

- Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- Strip floor using any Diversey stripper per the instructions on the stripper label

Coating

- Apply 3 or more medium coats of High Noon® Urethane Fortified UHS Floor Finish using a clean mop or the Diversey ProSpeed™/MC Floor Finish Applicator System. Apply additional coats until desired gloss is obtained. On porous resilient or stone floors, seal first with 2 coats of recommended Diversey sealer.
- Allow 30–45 minutes of drying time between coats. Temperature, humidity and ventilation may affect drying time. Allow finish to cure for 24 hours before burnishing.

Maintenance

- Dust mop or sweep. Clean the floor daily with a mop or an automatic scrubber using the recommended Diversey brand cleaner according to label directions.
- To enhance appearance, burnish using the appropriate pads
- Clean and restore gloss with recommended Diversey Cleaner/Maintainer
- Apply Cleaner/Maintainer using an autoscrubber or damp mop, let floor dry and then burnish

Recoating

- Dust mop or sweep
- Clean the floor with a mop or an automatic scrubber using the recommended Diversey cleaner according to label directions
- Blockade area and apply 1–2 uniform coats of finish using a clean finish mop
- Allow finish to cure for 24 hours before burnishing

Technical data	High Noon®
Color/Form	Opaque white, liquid
pH	8.5
Scent	Characteristic
Shelf Life	2 Years

Product	Pack size	Dilution	Product code	
High Noon®	6 x 2.5 L / 2.64 Qt. ProSpeed™/MC BIB (Bag-in-Box)	Ready-to-use	4972051	
High Noon®	4 x 1 gal. / 3.78 L Containers	Ready-to-use	4003110	
High Noon®	1 x 5 gal. / 18.9 L Envirobox™/MC	Ready-to-use	5104829	

Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up-to-date shipping information.