

## ANALYSIS



### ANALYSIS

The sample is first weighed and then dissolved in water. The solution is then filtered to separate the solid residue from the filtrate. The residue is dried and weighed to determine the percentage of the component in the sample. The filtrate is evaporated to separate the residue from the filtrate. The residue is dried and weighed to determine the percentage of the component in the sample. The filtrate is evaporated to separate the residue from the filtrate. The residue is dried and weighed to determine the percentage of the component in the sample.

The sample is first weighed and then dissolved in water. The solution is then filtered to separate the solid residue from the filtrate. The residue is dried and weighed to determine the percentage of the component in the sample. The filtrate is evaporated to separate the residue from the filtrate. The residue is dried and weighed to determine the percentage of the component in the sample. The filtrate is evaporated to separate the residue from the filtrate. The residue is dried and weighed to determine the percentage of the component in the sample.

### ANALYSIS

The sample is first weighed and then dissolved in water. The solution is then filtered to separate the solid residue from the filtrate. The residue is dried and weighed to determine the percentage of the component in the sample. The filtrate is evaporated to separate the residue from the filtrate. The residue is dried and weighed to determine the percentage of the component in the sample. The filtrate is evaporated to separate the residue from the filtrate. The residue is dried and weighed to determine the percentage of the component in the sample.