



# Attac<sup>®</sup> SC

73

## High Efficiency Floor Stripper

Highly concentrated low odor floor stripper formulated to meet Green Seal<sup>®</sup> requirements.

### Features & Benefits

- Powerful, fast-acting, low foam formula quickly bites through layers of finish as soon as it is applied
- Delivers fast, consistent removal of floor finish
- Not formulated with butyl or ammonia resulting in a minimal odor, suitable for facilities where odor is a concern
- Meets Green Seal<sup>®</sup> GS 40 standard based on effective performance and protective limits on VOCs

### Applications

- Designed for floor finish removal on VCT, terrazzo, and concrete flooring
- Not intended for use on wood, linoleum, rubber, marble, painted surfaces, on surface colored and acid dyed concrete floors as this product may harm these surfaces
- Test for softening or color bleeding on asphalt floors before using





# Attac<sup>®</sup> SC

## High Efficiency Floor Stripper

### Use instructions

- Use appropriate personal protective equipment.
- **Dilute product as follows:** Dispense stripper solution from dispenser using cold water at 1:13 for heavy duty stripping (14 + coats) or 1:20 for light/medium duty stripping (4-13 coats) into appropriate container.
- Blockade areas to be stripped. Floors will be very slippery when stripper is applied. Exercise caution.
- Apply liberal amounts of solution uniformly to floor with a mop. Start with the edges to give them more soak time. If splashing occurs, wipe off surfaces with a clean rag dampened with water.
- Let stripper solution soak for 10-15 minutes. Mop agitate to loosen finish or sealer. Re-wet as necessary, do not allow stripper to dry on the floor. Longer soak times may be necessary in cases of extreme buildup.
- Hand or machine scrub thoroughly using appropriate stripper pads or stripping brush.
- Pick-up all of the solution with a clean mop, wet vac or automatic scrubber.
- Mop up any "tracks" left by wet vacs or automatic scrubbers before they dry. Thoroughly rinse floor with clean water, using a mop and bucket.
- Let floor dry completely before applying a Diversey Green Seal<sup>®</sup>- certified finish or other recommended Diversey brand floor finish or sealer.

Technical data	Attac <sup>®</sup> SC
Certifications	Green Seal <sup>®</sup>
Color/Form	Clear Light Amber Orange, liquid
pH	12.25
Scent	Solvent
Shelf Life	2 Years

Product	Pack size	Dilution	Product code
Attac <sup>®</sup> SC	1 x 5 L / 1.32 gal. RTD <sup>®</sup> Unit	1:13, 1:20	95580067* 

\* Green Seal GS-40 Certified

### Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at [www.diversey.com](http://www.diversey.com) or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate.