

FEATURES & SPECIFICATIONS

INTENDED USE

To be powered by 6 or 12 volt battery equipment as part of an emergency lighting system providing light for the path of egress. This remote fixture matches applications using the ELSQ series.

CONSTRUCTION

Matte white polycarbonate frame and black thermoplastic housing are impact-resistant and lightweight.

Durable and corrosion-resistant with a UL94V-0 flame rating.

Prismatic acrylic lens.

OPTICS

Tungsten halogen lamp.

INSTALLATION

Surface mounting.

WARRANTY — 3-year limited warranty. Complete warranty terms located at:

www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application.


Specifications subject to change without notice.

Catalog Number
Notes
Type

Unit Accessories

ELA SQ

Square Fixture



Specifications

Length: 10-5/16" (261.94mm)

Depth: 10-5/16" (116mm)

Height: 3-7/16 (87.31mm)

Shipping Weight: 1 lb(0.45kg)

All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: ELA SQR6V

Series	
ELA SQR6V	(6 Volts, 10 Watts, 787 Lamp no.) ¹
ELA SQR12V	(12 Volts, 12 Watts, 783 Lamp no.) ¹

Note

- For fully recessed mounting, order additional kit ELA FRK (see [ELSQ-M](#)).