



Sheen 17

durable metal interlock floor finish

If you are looking for a hard, durable finish with a pure acrylic foundation, look no further. Sheen 17 creates a clear gloss with excellent coverage. This non-buff, 17% solids finish is recommended for high-traffic areas with low maintenance budgets.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, OH 43537
1-800-537-8990
www.spartanchemical.com

LIGHTER, BRIGHTER FLOORS:

Sheen 17 makes your whole room look lighter and brighter. Its pure acrylic foundation creates a clear gloss, permitting the natural floor color to pass through unobstructed. Recoat, recoat, recoat...and Sheen 17 still won't yellow.

MISTAKE-PROOF APPLICATION:

Easy to apply, put down Sheen 17 with nearly any applicator. Sheen 17 levels well and dries with no fish eyes, no bubbles and no lap marks. Excellent coverage..up to 3,000 square feet per gallon.

LOW MAINTENANCE HARD FINISH:

Sheen 17 is recommended for high traffic areas with low maintenance budgets. A favorite in schools and supermarkets who buff once a week or less.

EASY TO MAINTAIN AND REMOVE:

An excellent choice for top scrub and recoat systems. Even after repeated recoatings, Sheen 17 is easy to strip.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and Safety Data Sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

INITIAL APPLICATION:

1. Completely strip all old wax or floor finish with a Spartan stripper.

2. Remove the stripping solution and follow with two to three clear-water rinses. Allow to dry.
3. For maximum durability, two coats of a Spartan sealer are recommended.
4. Apply Sheen 17 in a uniform, thin coat. Let dry thoroughly for 30 to 40 minutes until surface is dry to the touch. Apply subsequent coats in the same manner. Three to five coats are recommended.

MAINTENANCE:

1. Dust mop or sweep floor as necessary with a Spartan Dust Mop/Dust Cloth Treatment.
2. Damp mop using a Spartan neutral cleaner.
3. To easily repair traffic areas between finish applications, use Spartan restorer or spraybuff. Traffic lanes may be recoated as necessary.
4. For heavily-soiled areas, machine scrub using Shinline Multi Surface Cleaner or Industrial Pathmaker at the recommended dilution.

NOTE: For best maintenance results, always use Spartan floor cleaners and strippers.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATIONS:

Total Solids – 20.5%
Non-Volatile Solids – 17%
pH (Concentrate) – 8.5 - 9.0

Stability

- a. Storage @24°C/75°F – One year minimum
- b. Accelerated @49°C/120°F – 30 days minimum
- c. Freeze/Thaw – Can withstand three cycles

Gloss (Gardner)

- a. 1 coat – 75-80
- b. 2 coats – 85-90

Static coefficient of friction meets or exceeds 0.5 as determined by ASTM method D-2047.

COVERAGE:

Up to 3,000 square feet per gallon depending on application method and porosity of floor.

Distributed by:

PACKAGING

401760	275-gallon totes
401755	55-gallon drum
401730	30-gallon drum
401715	15-gallon drum
401705	5-gallon pail
401704	1-gallon (4 per case)



Label copy is available in English and Spanish. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.

For institutional and industrial use only.

© SCC 3/11 L4017