

YOUR AUTHORIZED CONTINENTAL DEALER



GAS FURNACES

# C96Q SERIES

ULTRA-HIGH EFFICIENCY TWO STAGE

**CONTINENTAL**

P: 1-866-820-8686  
continentalcomfort.com



Consult your owner's manual for complete installation instructions, accurate framing dimensions and proper clearances to combustibile material. Check all local and national building codes. All specifications are subject to change without prior notice due to on-going product improvements. Products may not be exactly as shown.

Build Quality, Build Confidence.  
continentalcomfort.com



**CONTINENTAL**

# C96Q SERIES

## Efficiency At Its Best

### WHISPER QUIET™ Soft Start Motor

With a Whisper Quiet™ operation the EnerSave Plus and EnerSave Pro motors will 'soft start' & 'soft stop' gradually changing speed to reduce the noise created by conventional motors.

### Installation Options: Flexfit™ for Convenience

C96Q Series offers zero clearance in all positions, providing installation ease in closets and alcoves with no additional kits required. Installation options: upflow, horizontal right.

### WiFi Compatible

Our furnaces are compatible with any 24V thermostat, including Wifi connected thermostats.

## FEATURES

- 40,000 - 80,000 BTU models available
- Can be used for new construction heat
- High efficiency ECM Constant Torque Blower Motor
- T140 Aluminized Vortex™ Turbulator Heat Exchanger
- Self-Diagnostic Integrated Furnace Control (IFC)
- Two-stage control: first stage start up operates at 70% of full heating capacity
- Manufactured for Natural gas, propane conversion kit available
- Optional SureView™ Wedge Kit available
- Upgraded blue door
- Lifetime heat exchanger warranty (when registered)



## ENERGY STAR RATED

Continental C96Q Series WSX models feature a ECM motor which drastically reduces energy consumption when compared to a traditional PSC motor.



Note: Excludes 120K models

## SureView™ Burner System

Patented SureView™ burner system window allows a unique view of the flames in operation, a first in the industry.



## SPECIFICATIONS

MODEL	WSX040T2AB-C	WSX060T3AB-C	WSX080T3AB-C
<b>HEATING CAPACITIES</b>			
Efficiency (AFUE)	96%	96%	96%
Input High Fire (BTU/H)	40,000	60,000	80,000
Input Low Fire (BTU/H)	28,000	42,000	56,000
<b>DIMENSIONS</b>			
Height (in)	34	34	34
Depth (in)	29 ½	29 ½	29 ½
Width (in)	17 ½	17 ½	17 ½
Weight (lbs)	127	131	141
<b>FURNACE CAPACITY</b>			
CFM High Fire*	557	922	1087
CFM Low Fire*	341	638	669
Return Air (in)	14 X 23	14 X 23	14 X 23
<b>AIRFLOW AND COOLING</b>			
Motor Size	1/3 hp	1/2 hp	1/2 hp



**PARTS AND  
UNIT REPLACEMENT**  
LIMITED WARRANTY