

47005

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

1. Attach mounting strip (1) to outlet box (2) using two outlet box screws (4).
2. Securing the rod A (5) onto the bushing A (6) of fixture and onto bushing B (7).
3. Unscrew the collar loop ring (26) from collar loop (1). If necessary, use pliers (not included) to spread links of chain (9) apart and remove any links to achieve desired hanging height. Once chain (9) is at desired length, unscrew the K/D ring (10) on chain (9), but do not remove. Thread collar loop ring (26) and canopy (11) down chain (9) then attach the top K/D ring (10) to the screw collar loop (12) and the bottom K/D ring (10) to the fixture loop (8).
4. Weave electrical wires and ground wire up through the chain (9), the collar loop ring (26), the canopy (11) and the nipple (3) preassembled on mounting strip (1), then into outlet box (2).
5. Tie the ground wires (13 & 15) from fixture and from outlet box to the ground screw on the mounting strip. Connect the wire (19) without writing on it (with raised ribs) from the fixture to the white wire (neutral wire 20) from the supply circuit. Connect the wire (17) with writing on it from the fixture to the black wire (live wire 18) from the supply circuit. Cover the connections by using provided wire connectors (16). Position wires back inside outlet box (2).
6. Place the canopy (11) over the nipple (3) and tighten the collar loop ring (26) onto the collar loop (12) until the canopy (11) is held firmly against the ceiling.

7. Hang the rod B (21) into top U-shaped plate (22) and into fixture L-shaped plate (23). Make sure the fixture body (24) is hanging up steadily.

8. Install the five bulbs (not included 25) and make sure they do not exceed the maximum wattage specified on the fixture's wattage rating label.

9. Turn on the power.

INSTALLATION IS NOW COMPLETED

