CyberPower

CSB6WS WALL-TAP SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower CSB6WS Surge Protector transforms a standard two-outlet wall socket into six surge-protected outlets, giving you the space and safety your devices need. Perfect for crowded areas where chargers, computers, and electronics compete for limited plugs. Featuring dual swiveling outlet banks, this surge protector offers flexible positioning and improved cord management—keeping your setup neat and organized. With 1800 joules of surge protection, it defends your valuable tech from power spikes and electrical surges. Ideal for safeguarding computers, routers, modems, chargers, and other personal tech essentials.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- Surge suppression: 1800 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- AC Outlets: 6
- Outlet type: NEMA 5-15R
- EMI/RFI Filtration: Yes
- Warranty: Lifetime Limited
- Connected Equipment Guarantee: \$200,000



SPECIFICATIONS

Wall-tap		
NEMA 5-15P		
15 A		
Wall-tap		
OUTPUT		
6 x NEMA 5-15R		
6		

SURGE PROTECTION & FILTERING		
Attenuation	32 dB	
Clamping Voltage	800V (H-N, H-G, N-G)	
EMI/RFI Filtration	150 KHz / 100 MHz	
Maximum Surge Current	60,000 A	
Maximum Surge Current H-G	15,000 A	
Maximum Surge Current H-N	30,000 A	
Maximum Surge Current N-G	15,000 A	
Maximum Surge Voltage	6000	
Surge Suppression (Joules)	1800 J	
	·	

CSB6WS WALL-TAP SURGE PROTECTOR

SPECIFICATIONS CONT.

PHYSICAL		
Color	White	
Form Factor	Wall-tap	
Form Factors Supported	Direct Plug	
Material of Construction	Plastic	
PHYSICAL DIMENSIONS		
Physical Dimensions - Width/Height/Depth (cm)	10.24 x 14.3 x 3.51 cm	
Physical Dimensions - Width/Height/Depth (mm)	102 x 143 x 35 mm	
Physical Dimensions - Width/Height/Depth (in.)	4.03 x 5.63 x 1.38 in.	
Weight (kg)	0.29 kg	
Weight (lb)	0.64 lbs.	
SHIPPING DIMENSIONS		
Shipping Dimensions - Width/Height/Depth (cm)	12.29 x 18.49 x 6.81 cm	
Shipping Dimensions - Width/Height/Depth (mm)	122.94 x 184.91 x 68.07 mm	
Shipping Dimensions - Width/Height/Depth (in.)	4.84 x 7.28 x 2.68 in.	
Weight (kg)	0.36 kg	
Weight (lb)	0.80 lbs.	

CERTIFICATIONS		
Environmental	RoHS Compliant	
Safety	cETLus (UL498A/UL1449)	
WARRANTY		
CEG Amount	\$200,000	
Connected Equipment Guarantee	Lifetime	
Product Warranty	Limited Lifetime Warranty	