

PREMIUM GRADE, HIGH TENSILE STRENGTH FIBERGLASS REINFORCED STRAPPING TAPE

TYPICAL APPLICATIONS

- High tensile strength for heavy duty strapping, packaging, protecting, bundling, reinforcing, sealing, palletizing and “L” clipping

ADVANTAGES AND BENEFITS

- High edge tear
- Backing resists de-lamination, splitting and cracking
- High tensile strength
- Good adhesion

CONSTRUCTION

Overall Grade/Function: Premium
Backing: Fiberglass reinforced, high tensile strength, polyester film
Adhesive: Hot melt, synthetic rubber

COLOR(S)

 Clear (CLR)



STANDARD WIDTH(S)

18 mm 24 mm 36 mm 48 mm 55 mm
Contact your Shurtape sales representative for other available sizes.

STANDARD LENGTH(S)

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	300 lbs/in width	525.4 N/10 mm
Adhesion to Stainless Steel	70 oz/in width	7.66 N/10 mm
Thickness	6.7 mils	0.17 mm
Elongation	3.7%	3.7%
Service Temperature Range	-10 F to 150 F	-23 C to 66 C
Adhesion to Kraft	43 oz/in width	4.71 N/10 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 5330, Type II; FDA Indirect Contact CFR 21, B, 175.105; FDA Indirect Contact CFR 21, 177.1630; PPP-T-0097E, Type II, Class A*

*Standard is obsolete, and provided only as a reference

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-GS531- 06/17/2014