### **CyberPower**

# GXS604C2 GAMING SURGE PROTECTOR



## Protects high end electronics from power interruptions and power surges.

Level up your defense with the CyberPower GXS604C2 Surge Protector – built for gamers who don't mess around. Whether you're grinding through raids on your console or dominating matches on your PC, this surge protector keeps your gear safe from power spikes and surges with a massive 2400 joules of protection. With six wide-spaced outlets, a four-foot power cord, and dual USB-C ports, you've got plenty of room to power your rig, monitors, and charge your controllers—no outlet Tetris required. And the customizable RGB light bar? Yeah, it's there to sync up with your setup and look just as fresh as the rest of your gear. CyberPower's got your back with a one-year limited warranty and a \$300,000 Connected Equipment Guarantee. Stay powered. Stay protected. Stay in the game.

#### **TYPICAL APPLICATIONS**

· Gaming Systems

#### **FEATURES**

- AC Outlets: 6
- Cord Length: 4 ft
- Surge suppression: 2400 J
- Plug type: NEMA 5-15P
- Plug style: Right angle, 45° offset
- Outlet type: NEMA 5-15R
- USB-C charge ports: 2
- USB-C charge output: 18W total
- Volts: 125 V
- · Warranty: One-Year Limited
- Connected Equipment Guarantee: \$300,000

#### **SPECIFICATIONS**

INPUT	
Cord Length	4 ft (1.2 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	45° Offset Right
OUTPUT	
Outlet Type	6 x NEMA 5-15R
USB Charge Port Type	2 x Type C
LICE Character De LAVelland	EVDC
USB Charge Port Voltage	5 VDC
USB Charge Port Voltage USB Charge Port Watts	18 Watts

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	800V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz / 100 MHz
Maximum Surge Current	60,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	15,000 A
Response Time	<1 Nanosecond
Surge Suppression	2400 J

## GXS604C2 GAMING SURGE PROTECTOR

#### SPECIFICATIONS CONT.

PHYSICAL	
Color	Black
Form Factor	Strip
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	12.98 x 3.4 x 21.46 cm
Physical Dimensions - Width/Height/Depth (mm)	130 x 34 x 215 mm
Physical Dimensions - Width/Height/Depth (in.)	5.11 x 1.34 x 8.45 in.
Weight (kg)	0.52 kg
Weight (lb)	1.14 lbs.

Weight (Ib)	1.14 IDS.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	14.0 x 26.01 x 7.01 cm
Shipping Dimensions - Width/Height/Depth (mm)	139.95 x 260.1 x 70.1 mm
Shipping Dimensions - Width/Height/Depth (in)	5.51 x 10.24 x 2.76 in.
Weight (kg)	0.62 kg
Weight (lb)	1.37 lbs.

CERTIFICATIONS		
Environmental	RoHS Compliant	
Safety	cULus UL1363 UL1449 DOE VI/NR Can FCC ICES-003	
WARRANTY		
CEG Amount	\$300,000	
Connected Equipment Guarantee	Lifetime	
Product Warranty	1-Year Limited Warranty	