

PC 945



T-REX® BRUTE FORCE® PREMIUM, CO-EXTRUDED CLOTH TAPE WITH EXTREME TENSILE CLOTH

TYPICAL APPLICATIONS

- Hold More, Do More™
- For the most extreme applications such as securing, hauling, binding, repairing, holding, and more
- Can be used as an alternative to ropes and chains in many applications

PRODUCT FEATURES

- Super-tough, premium, co-extruded cloth tape
- Built with Forge-Link Technology, an extreme tensile cloth, one loop of T-Rex Brute Force holds 800+ pounds of weight*
- Ferocious construction with high tack, double-thick adhesive that sticks to rough and dirty surfaces
- Too tough to tear by hand
- *1 yard of tape looped to itself; tape not weight rated for towing applications, visit T-RexTape.com for details

CONSTRUCTION

Backing: Durable waterproof backing

Adhesive: Natural rubber adhesive

STANDARD WIDTH

1.88 in
48 mm

STANDARD LENGTH

25 yd
22.8 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR

Black (BLK)

PHYSICAL PROPERTIES	STANDARD	METRIC
Adhesion to Stainless Steel	75 oz/in width	8.21 N/10 mm
Elongation	21%	21%
Service Temperature Range	32 F to 200 F	0 C to 93 C
Tensile	250 lbs/in width	437.8 N/10 mm
Thickness - Nominal	17.0 mils	0.43 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



*1 yard of tape looped to itself; Tape not weight rated for towing applications, visit T-RexTape.com for details.